



BlenderWorld: Benchmarking Visual Agents for 3D Creation from Real-World References

Xinyu Fang^{1,2} Yuchi Wang^{2,3} Weihao Yu^{2,3} Rongyao Fang² Zhaohai Li²
 Zhixun Li^{2,3} Tiancheng Gu² Xilin Wei^{2,4} Yuhang Zang⁵ Hongsheng Li³
 Dahua Lin^{3,†} Guofeng Zhang^{1,†} Shuai Bai² Zhibo Yang^{2,†} Dayiheng Liu²

¹Zhejiang University ²Alibaba Token Hub, Alibaba Group ³The Chinese University of Hong Kong

⁴Fudan University ⁵National University of Singapore

✉ fangxinyu09@zju.edu.cn, zhibo.yzb@alibaba-inc.com

🌐 Website: blenderworld.github.io

Abstract

Recent advances in multimodal large language models (MLLMs) have enabled them to act as autonomous agents, creating and editing 3D models via code or direct software manipulation. In practical workflows, these models must infer object shapes, materials, spatial layouts, and lighting from diverse references while strictly following instructions to reconstruct, modify, or design 3D content. However, existing benchmarks provide limited coverage of such open-ended requests across real-world scenarios. To bridge this gap, we introduce **BLENDERWORLD**, the first comprehensive benchmark dedicated to evaluating frontier models on realistic 3D creation tasks. **BLENDERWORLD** comprises 223 tasks spanning architecture, products, natural environments, and scientific visualization, driven by text, image, video, and structured specification inputs. To rigorously assess these complex deliverables, we establish a unified evaluation protocol: we render the submitted Blender projects from multiple viewpoints and evaluate them against 2,651 task-specific binary rubrics alongside holistic visual quality scores. Benchmarking thirteen frontier models reveals that GPT-6-Astra achieves the highest overall fused score of 79.9, followed by Opus-5 (73.0) and GPT-5.6-Sol (67.7). Ultimately, our findings reveal a critical bottleneck: while current models can parse broad instructions, they still profoundly struggle with fine-grained 3D spatial coherence and accurate structural reproduction in Blender, leaving substantial headroom for future 3D-native agentic.

1 Introduction

Visual agents built on multimodal large language models (MLLMs) can interpret visual references, operate design tools, and refine their outputs through visual inspection (Qwen Team, 2026; OpenAI, 2026). These agents have gained traction in two-dimensional (2D) design tasks, including webpage, poster, layout, and presentation creation (Si et al., 2025; Chen et al., 2024; Li et al., 2025; Zhao et al., 2026a), and are increasingly being extended to three-dimensional (3D) modeling and scene creation. 3D modeling is a crucial task and provides a practically valuable testbed for visual agents. First, it involves complex, long-horizon workflows in which agents must coordinate extensive tool use across dozens of interaction turns. Second, it supports applications ranging from everyday personal projects to professional scientific visualization, while spanning scales from individual household objects to entire city blocks. Third, mastering this domain requires spatial reasoning, active visual verification, and sustained tool manipulation within open-ended digital environments, all of which are essential for extending the productivity frontier of AI agents.

However, evaluating agents on practical 3D modeling tasks presents three major challenges: environment selection, task coverage, and output assessment. First, evaluation requires an accessible environment that supports 3D creation, editing, and inspection, yet few available environments provide all three capabilities. We therefore turn to Blender, an open-source platform that supports these capabilities through Python scripting and Model Context Protocol (MCP) interfaces and has been used for agent-driven creation and editing (Hu et al., 2024; Huang et al., 2024; Noor et al., 2026). Second, practical requests vary widely in their reference sources and design goals, ranging from reconstruction based on photographs or illustrations to open-ended design briefs. A realistic benchmark must therefore cover diverse application contexts and user requirements. Existing Blender-based benchmarks typically focus on narrower task classes: 3DCodeBench and 3DHarnessBench emphasize individual objects (Gao et al.,



Figure 1: **BLENDERWORLD** taxonomy and examples. References are shown left/top and GPT-6-Astra results right/bottom.

2026; Liu et al., 2026b), BlenderBench contains a small set of camera and scene-editing tasks (Yin et al., 2026), and SceneActBench covers broader scenes but focuses on predefined geometric objectives (Zhao et al., 2026b). Finally, realistic requests often lack ground-truth 3D assets, while open-ended briefs may admit multiple valid solutions. Reliable evaluation must therefore assess both visual properties and underlying structures, requiring evidence beyond what a single rendered view can reveal.

To address these challenges, we introduce **BLENDERWORLD**, a benchmark for evaluating visual agents on realistic 3D reconstruction, modification, and design tasks in Blender. **BLENDERWORLD** contains 223 tasks spanning 16 practical application scenarios, organized into 9 main categories and 22 subcategories (Fig. 1). The tasks represent diverse user needs, driven by text, image, and video references, with 59 tasks additionally including structured specification files. Agents must synthesize these inputs to produce fully editable Blender projects. To rigorously evaluate these diverse deliverables without a single canonical asset, we design an evidence-routed evaluation protocol. An automatic agent selects and renders multiple task-conditioned views, which are then assessed via 2,651 task-specific binary rubrics and continuous visual-quality dimensions. Crucially, we employ a dual-judge system: a VLM-as-Judge for visual and spatial properties, and an Agent-as-Judge for direct programmatic inspection of scene structures that bypass visual shortcuts. Benchmarking 13 frontier models reveals a stark reality: while models can generate visually plausible outputs and plan extensive tool invocations, they profoundly struggle to translate passive visual feedback into structurally sound 3D corrections.

Contributions. We summarize our main contributions as follows: (1) We introduce **BLENDERWORLD**, a comprehensive benchmark of 223 realistic Blender tasks spanning 22 subcategories, covering diverse text, image, and video reference sources alongside specifications for practical 3D reconstruction, modification, and design requests. (2) We provide a unified evaluation protocol that combines task-conditioned multi-view rendering, task-specific binary rubrics (verified via both visual judges and programmatic scene-state inspection), and a holistic visual quality assessment. (3) We evaluate agents built on thirteen frontier models under a shared task and protocol, establishing strong baselines. Our results reveal that while top-performing models like GPT-6-Astra achieve high overall fused scores (79.9), they still fail to fully satisfy all task requirements, reaching a perfect pass rate on only 42.2% of tasks. (4) Through in-depth trajectory and failure analysis, we expose fundamental bottlenecks in current 3D agents: they frequently rely on 2D visual shortcuts (e.g., view-dependent geometry) and profoundly struggle with fine-grained 3D spatial coherence, physical contact constraints, and translating passive visual inspection into effective structural refinements.

Table 1: **Task coverage and artifact evaluation in programmatic 3D benchmarks.** BLENDERWORLD spans nine task categories, combining multimodal references with task-specific rubrics, agent-selected views, and agent inspection of editable projects.

Benchmark	Task			Evaluation		
	Task scope	Tasks num	Input modes	Task-specific rubrics	Visual evidence	3D checks
3DCodeBench (Gao et al., 2026)	Objects	212	T,I	—	Fixed	Geom.
3DHarnessBench (Liu et al., 2026b)	Objects	100	I,3D	—	Fixed	Geom.
VoxelCodeBench (Zheng & Bordes, 2026)	Voxel scenes	220	T	—	MV	—
BlenderGym (Gu et al., 2025)	Scene edits	245	T,I	—	Fixed	Geom.
BlenderBench (Yin et al., 2026)	Camera / edits	27	T,I	—	Renders	—
Code-as-Room (Yang et al., 2026)	Rooms	41	I	—	Renders	Layout
SceneActBench (Zhao et al., 2026b)	Scene actions	520	I,V	—	—	Geom.
4DBuildBench (Liu et al., 2026a)	Dynamics	50	T	✓	Frames	State
PhysCodeBench (Xie et al., 2026)	Physics	200	T	✓	Video	Physics
WorldCoder-Bench (Core) (Lu et al., 2026)	3D worlds	205	T	✓	—	Contracts
BlenderWorld (ours)	9 categories	223	T,I,V	2,651	Agent	Agent

T/I/V/3D =text/image/video/native 3D reference, visual modes may also include instructions. Fixed =fixed views, MV =multiple views, Frames =sampled video frames, Geom. =geometric metrics, State =scripted scene-state audit.

2 Related Work

Productivity-Oriented and Real-World Agent Benchmarks. Productivity-oriented benchmarks assess whether agents can complete software workflows and produce verifiable deliverables. SaaS-Bench, WildClawBench, and Claw-Eval examine professional workflows (Shi et al., 2026; Ding et al., 2026; Ye et al., 2026), while WebArena, WorkArena, and OSWorld provide browser or desktop tasks (Zhou et al., 2024; Drouin et al., 2024; Xie et al., 2024). BLENDERWORLD extends this focus on practical deliverables to everyday 3D production briefs, including renovation proposals, product visualization, and classroom teaching. Briefs may include photographs, illustrations, videos, and separate specification files. Agents must interpret these inputs together with the user’s instructions and deliver editable Blender projects with the requested media.

Procedural 3D and CAD Benchmarks. Existing Blender-based benchmarks cover object modeling (Gao et al., 2026; Liu et al., 2026b), scene editing (Gu et al., 2025; Yin et al., 2026), and scene reconstruction or dynamics (Yang et al., 2026; Zhao et al., 2026b; Liu et al., 2026a). CADBench, BenchCAD, and MUSE emphasize geometric correctness, engineering intent, or assembly (Doris et al., 2026; Zhang et al., 2026; Dong et al., 2026). Table 1 compares task coverage and artifact evaluation across representative 3D benchmarks. BLENDERWORLD combines reconstruction, modification, and reference-based design across 9 task categories and 16 application scenarios. Generation agents iteratively build editable projects, while evaluator agents select task-relevant views and inspect scene structure. Task-specific binary rubrics assess compliance with each brief, while visual quality scores assess the overall rendered result.

3 BLENDERWORLD

3.1 Task Definition

BLENDERWORLD evaluates interactive 3D creation from production briefs. Each task provides $x = (q, I, F)$: a natural-language request q , optional image or video references I , and optional specification files F . Starting from workspace state s_0 , an agent π uses observations o_t to select actions:

$$a_t = \pi(x, o_{\leq t}), \quad s_{t+1} = \mathcal{E}_B(s_t, a_t), \quad (1)$$

where $\mathcal{E}_B$ updates the Blender workspace state s_t after action a_t . Through Blender’s Python API and MCP tools, actions include scene inspection, Python execution, asset import, and rendering. Rendered views and scene queries guide revisions to geometry, materials, lighting, and animation within the interaction budget. After T steps, the agent outputs $A_T = (B, R, V, X)$: an editable Blender project B , renders R , animations/videos V , and auxiliary files X . Deliverables must support downstream reuse as specified. Our evaluation checks these against the brief and references, accommodating multiple valid 3D implementations.




Figure 2: **Construction and rubric derivation pipeline in BLENDERWORLD.** Illustrating the end-to-end workflow from diversified task and reference curation, application-grounded brief specification with dual-track validation, to multi-model verified and frozen binary rubrics.

3.2 Benchmark Construction

Inspired by practical uses of 3D content in social media, we organize task coverage along two dimensions: category taxonomy and application scenarios. These dimensions guide task specification and MLLM-assisted brief generation. We then check the resulting briefs for structural and semantic consistency before deriving task-specific rubrics (Figure 2).

Task and reference diversity. Task design varies both the production requirements and how references guide the output. **(1) Production requirements.** We vary the target domain, scene complexity, user expertise, and request length. For example, a teaching task may briefly describe a biological cell with multiple internal structures. **(2) Reference use.** We curate diverse reference images spanning interiors, architecture, products, mechanical structures, and natural environments. An MLLM then assesses image quality and structural complexity and we favor images with clearly identifiable structures and detailed information about shape, layout, or materials. We assign each visual reference one of three roles: *recreation* preserves the main shapes and spatial relationships, *modification* makes requested changes while retaining specified structures, and *reference-based design* draws on the depicted form, style, or layout to develop a new design. The reference image and its assigned role guide both initial task generation and request rewriting.

Application-grounded specification. Given the production target and reference role, we situate each specification in a realistic application scenario. For example, construction reports emphasize structural relationships, whereas product presentations emphasize visibility and appearance. We express each specification as a natural-language request that states the production goal and key requirements. Tasks with detailed specifications may also include Markdown, YAML, or JSON attachments containing dimensions, material lists, camera settings, or asset budgets. The request explicitly references these files, which retain the details required to complete the task.

Dual-track validation. We validate each brief for structural and semantic consistency. **Structural checks** ensure that the metadata are compatible, images and attachments are accessible, structured files can be parsed, and the brief explicitly requests both rendered outputs and an editable project. For **semantic review**, a model distinct from the task generator independently examines the initial specification, rewritten request, reference image, and attachments together. It checks image-text alignment, constraint consistency, preservation of key requirements, and task feasibility. Tasks that fail validation are fed back into the generation process for revision.

Rubric generation. A generator extracts requirements from validated briefs, converting them into binary criteria with source links. Each criterion is assigned to one of 13 categories, weighted (3/2/1 for major/secondary/detail), and designated an evidence type: *render* (for visual properties) or *scene_summary* (for project/file inspection). We iteratively refine drafts via pilot evaluations (using GPT-5.6-Sol) to flag ambiguities. Next, at least two independent reviewer models cross-check coverage, source support, and evaluability using concrete counterexamples. An editor resolves flagged issues, with any semantic changes triggering re-review, before freezing the final schema (details in Appendix B).

3.3 Dataset Statistics

BLENDERWORLD contains 223 production briefs across 9 main task categories and 22 subcategories (Figure 1), covering architecture and interiors, products and manufacturing, vehicles and machinery, characters and animals, nature and landscapes, and scientific visualization. The tasks serve 16 application scenarios, with the largest shown in Figure 3a and the full distribution in Appendix A. Visual references are provided for 145 tasks (65.0%): 130 include images, and 15 include videos. Specification files in




Figure 3: Dataset statistics of **BLENDERWORLD**. (a) The 11 largest application scenarios (213 of 223 tasks). (b) Percentages of tasks with each reference or specification type; types may co-occur. (c) Criterion counts by rubric category (inner ring) and importance (outer ring).

Markdown, YAML, or JSON accompany 59 tasks (26.5%), adding requirements on dimensions, materials, and camera settings (Figure 3b). References and specifications can co-occur, combining visual guidance with explicit production constraints.

Evaluation uses 2,651 binary criteria across 13 rubric categories, with 6–22 criteria per task (mean 11.9). Function and geometry together account for 41.7% of criteria. Of all criteria, 83.3% have major importance (weight 3). For judging, 41.8% of criteria are assigned to rendered views and 58.2% to scene inspection. Explicit requirements from specification files account for 500 criteria (18.9%), linking these attachments to evaluation. Table 1 compares **BLENDERWORLD** with existing 3D benchmarks.

4 Evaluation and Metrics

4.1 Evaluation Protocol

For each task, an agent uses a harness equipped with Blender MCP to review the task brief and any provided references or attachments, construct the scene, and save the requested deliverables. We archive the agent’s final workspace, including the editable .blend project, exported media, and auxiliary files. This artifact package is then processed through automatic agent rendering to produce more visual evidence, and finally to get rubric and dimension scores with model judgment.

Automatic Agent Render (AaR). Given the task query, rubrics, reference files, and submitted deliverables, AaR selects eight complementary views to reveal task-relevant details. This adaptive view selection aims to make the required properties observable while maintaining a common rendering budget across submissions. The rendering agent opens the submitted Blender projects and renders each view at 1024×1024 resolution with 64 samples using Cycles. It may adjust cameras, framing, and rendering settings, but must preserve the submitted geometry, materials, lighting, animation, and color management. Invalid views can be re-rendered within two attempts, but defects in the submitted work must not be repaired. Visual judging proceeds only when newly rendered views are available; otherwise, the evaluation is marked as failed. The original exported media remain available as additional evidence alongside the evaluator-generated views.

Evidence-routed rubric judging. Each rubric specifies a binary criterion, an evidence type, and an importance weight. We route criteria to two complementary judges according to the evidence needed to verify them. **Agent-as-Judge** handles scene_summary criteria, which cover requirements on internal scene structure and native-file properties that cannot be reliably verified from rendered views alone. The agent Judge inspects the deliverables through multiple tools provided by Blender and records evidence about internal states. Judge also consults visual evidence when necessary and emits a binary decision with supporting evidence for each assigned criterion. **VLM-as-Judge** handles render criteria, which cover requirements on visual appearance, spatial layout, and motion that can be verified from rendered views and exported media. It receives the task context together with three evidence groups: AaR views, original exported media, and additional ordered frames sampled from exported videos. When visual evidence conflicts, original exported media take precedence over other views to keep scoring faithful to the agent’s final deliverables. Moreover, a separate blind pass produces prompt-free descriptions of submission and reference images as auxiliary grounding evidence. These descriptions supplement the images and are used only by the visual judge. Unsupported rubric claims receive zero.




Figure 4: Evaluation pipeline of **BLENDERWORLD**. Structural and visual evidence support binary rubric decisions, which are fused with dimension scores.

Dimension Judging. To address the limitations of binary rubrics in quantifying continuous perceptual attributes, the VLM additionally evaluates artifact quality along eight dimensions: scene fidelity, physical plausibility, style and color, realism, spatial layout, proportion and scale, lighting and materials, and completeness. Each dimension receives an integer score from 1 to 10 based on the task requirements and available references, with a justification grounded in the visual evidence. Detailed scoring guidelines are provided in Appendix C.

4.2 Metrics

We combine requirement satisfaction and holistic artifact quality into a single score for each task q . Given m binary rubric decisions $\hat{y}_j \in \{0, 1\}$ with importance weights w_j and $K = 8$ dimension ratings $d_k \in [1, 10]$, we compute two scores on a 0–100 scale:

$$S_{\text{rubric}} = 100 \frac{\sum_{j=1}^m w_j \hat{y}_j}{\sum_{j=1}^m w_j}, \quad S_{\text{dim}} = 100 \frac{\sum_{k=1}^K d_k}{10K}. \quad (2)$$

We define the fused task score as $S_{\text{fused}}^{(q)} = \lambda S_{\text{rubric}}^{(q)} + (1 - \lambda) S_{\text{dim}}^{(q)}$. We set $\lambda = 0.5$ to place equal emphasis on functional requirement satisfaction and holistic aesthetic quality (a detailed analysis of the λ coefficient is provided in Appendix E.6). We report the mean score over all $Q = 223$ tasks, $\text{Score} = \frac{1}{Q} \sum_{q=1}^Q S_{\text{fused}}^{(q)}$, together with separate means for the 78 Text and 145 MM tasks. Failed evaluations receive zero and remain in the denominator.

5 Experiments

5.1 Evaluation Setup

Models and environment. We compare thirteen agents on the same 223 tasks: 78 Text and 145 multi-modal tasks with image or video references. GPT-6-Astra and GPT-5.6-Sol use Codex, while all other agents use Claude Code. Each agent is tested once per task, operating at its highest available reasoning intensity. Agents work in isolated Linux containers, each equipped with one NVIDIA GPU and a pre-installed Linux version of Blender LTS. Crucially, artifact generation and evaluation are executed in strictly separated containers; the evaluation rubrics remain completely invisible to the agents during the generation phase to prevent rubric hacking. Shell, file, image-viewing, and Blender MCP tools support scene creation, rendering, inspection, and revision. Appendix D details the tools and runtime settings.

Evaluation metrics. Following the scoring protocol in Section 4, we report mean scores on text-only tasks (Text), multimodal tasks (MM), and all 223 tasks (Score). Rubric / Dimension reports the two component means on a 0–100 scale, measuring weighted requirement satisfaction and overall visual quality. Perfect is the percentage of tasks passing every rubric criterion. Submissions without a .blend file automatically receive a score of zero because they cannot be rendered for evaluation and do not meet the task’s delivery requirements. For generation trajectories, we report mean turns, mean output tokens, and the mean number of tool calls per task. To balance computational cost and evaluation accuracy, we employ GPT-5.6-terra for automatic agent rendering, rubric judging, and dimension judging. A detailed analysis of the judge model is provided in Appendix E.1.

Table 2: **Performance on all 223 BLENDERWORLD tasks.** Models are ranked by mean fused Score; bold marks the best completion values.

Model	Completion					Rollout statistics		
	Text	MM	Score	Rubric / Dimension	Perfect (%)	Turns	Output tokens (K)	Tool calls
 GPT-6-Astra	78.6	80.7	79.9	87.3 / 72.6	42.2	45.6	84.5	79.1
 Opus-5	74.8	72.1	73.0	80.9 / 65.1	25.6	158	241	155
 GPT-5.6-Sol	71.7	65.5	67.7	74.7 / 60.7	15.7	44.9	39.9	44.0
 DeepSeek-V4.1-Flash	66.0	65.5	65.7	72.0 / 59.4	11.7	171	209	168
 Qwen3.8-Max	59.6	61.1	60.6	65.9 / 55.3	10.3	75.1	90.6	72.8
 GLM-5.3-Flash	63.1	57.8	59.7	64.8 / 54.4	6.28	102	145	101
 Grok-4.6	60.0	55.4	57.0	61.4 / 52.7	6.73	93.4	120	89.8
 Opus-4.8	58.6	56.1	57.0	60.2 / 53.7	5.38	97.7	164	95.6
 Seed2.1pro-0915	54.7	49.5	51.3	54.9 / 47.7	3.59	196	122	194
 Qwen3.8-27B	46.1	48.6	47.7	50.0 / 45.5	1.35	90.0	112	87.4
 Kimi-K3	41.3	49.4	46.5	47.9 / 45.2	1.79	60.5	54.3	58.3
 Gemini-3.8-Flash	35.9	33.2	34.2	29.8 / 38.5	0.45	56.6	35.9	54.5
 MiniMax-M3	34.1	30.6	31.8	28.9 / 34.7	0.45	132	72.2	127

5.2 Main Results

GPT-6-Astra leads across all completion metrics. It achieves an overall Score of 79.9, ahead of Opus-5 at 73.0 (Table 2). Its lead over Opus-5 is larger on multimodal tasks (80.7 vs. 72.1) than on text-only tasks (78.6 vs. 74.8). GPT-6-Astra also ranks first in both Rubric and Dimension, indicating advantages in both requirement satisfaction and overall visual quality. **However, satisfying every rubric criterion remains challenging.** GPT-6-Astra achieves a Perfect rate of 42.2%, compared with 25.6% for Opus-5 and at most 15.7% for the remaining agents. Thus, even the highest-scoring agents fully satisfy the rubric on fewer than half of the benchmark tasks.

GPT-5.6-Sol matches DeepSeek-V4.1-Flash on multimodal tasks and achieves a slightly higher overall Score, yet their rollout statistics differ substantially. GPT-5.6-Sol averages 39.9K output tokens and 44.0 tool calls per task, compared with 209K tokens and 168 calls for DeepSeek-V4.1-Flash. The difference in tool use includes GPT-5.6-Sol’s fewer Blender executions and image view tool calls (Figure 6). GPT-6-Astra reinforces this pattern: it achieves the highest overall Score while using fewer output tokens and tool calls than both Opus-5 and DeepSeek-V4.1-Flash. **These patterns suggest different balances between planning and iterative tool use.** The GPT Series Models may favor more extensive planning before acting, whereas DeepSeek-V4.1-Flash relies more on repeated execution and inspection to refine its scenes. Further trajectory analysis could further clarify how planning and iterative refinement contribute to scene quality and interaction efficiency.

5.3 Analysis

5.3.1 Performance across Task Categories

Among the five agents shown in Figure 5a, GPT-6-Astra leads eight of nine categories, scoring highest on Procedural & Game Assets (86.8) and Products & Manufacturing (83.9). Its largest lead over Opus-5, however, occurs in Characters & Animals, where its own score is lower than its overall score (78.7 vs 79.9). The category rankings also contain reversals. Opus-5 outperforms GPT-6-Astra on Rendering & Simulation, while Qwen3.8-Max exceeds DeepSeek-V4.1-Flash on Nature & Landscapes despite ranking below it overall (Table 2). These results suggest that modeling strengths vary across agents, with a shared tendency toward higher scores on procedural assets, manufactured objects, and architectural scenes. Natural scenes and characters remain more challenging.

GPT-6-Astra’s weaker categories reveal distinct trade-offs between visual quality and requirement satisfaction. In *Art & Animation*, the model maintains a high Rubric score (89.6) but suffers the lowest Dimension score (64). Conversely, *Rendering & Simulation* yields the lowest Rubric score (70.6) despite achieving a higher Dimension score (71.6), causing it to rank last. These findings indicate that while




Figure 5: **Category performance and GPT-6-Astra’s score composition.** (a) Mean Overall Score for the five highest-scoring agents. (b) GPT-6-Astra’s mean Rubric and Dimension contributions.




Figure 6: **Tool allocation and interaction volume.** (a) Distribution of five exclusive tool invocation categories (b) Mean calls per task.

GPT-6-Astra reliably fulfills explicit requirements in *Art & Animation*, it struggles with visual quality. In contrast, for *Rendering & Simulation*, the bottleneck lies in faithfully reproducing the required behaviors, as exemplified by the failure case in Figure 7a.

5.3.2 Tool Use

Tool Allocation Discrepancy vs. Interaction Volume. As decoupled in Figure 6, examining proportional tool allocation alongside absolute volume reveals fundamentally different agent strategies. While top performers like **GPT-6-Astra** and **Opus-5** allocate similar budget fractions to *Blender execution* and *Image viewing*, their absolute workloads diverge substantially: **Opus-5** requires roughly twice as many executions (45.5 vs. 23.3) and views (27.1 vs. 15.0) per task, alongside an inflated volume of auxiliary operations. In contrast, **Grok-4.6** uniquely leads in *Asset operations* (13%), demonstrating a new paradigm by prioritizing asset manipulation.

Passive Inspection vs. Effective Corrective Feedback. Conversely, higher visual call volume does not inherently guarantee effective artifact refinement. Models such as **Seed2.1pro-0915** and **DeepSeek-V4.1-Flash** make the most frequent visual queries across all agents (33.9 and 31.3 calls per task), yet their multimodal scores remain moderate or poor. In stark contrast, **GPT-6-Astra** achieves the top multimodal score (80.7) and rubric completion (87.3) with merely 15.0 image inspections. **Viewing volume captures the opportunity for feedback without ensuring that the agent can diagnose defects or enact valid corrections.** These aggregate statistics show that more visual inspections do not necessarily coincide with higher scores. They do not establish how effectively each agent uses visual feedback.

5.3.3 Failure Analysis

Failure Analysis and Bottlenecks. A qualitative audit of failure modes (Figure 7) reveals four recurring failure mechanisms across agents. (1) **Missing Dynamic Interactions:** In Figure 7a, GPT-6-Astra satisfies object presence but fails to generate physical interactions, leaving the canvas blank without converging



Figure 7: **Example of failure modes.** (a) Missing paint trails and central crossing, (b) people absent in a side view, (c) distorted lion-cub anatomy, (d) a reclining person floating above the lawn.

trails. (2) **Viewpoint Inconsistency:** Figure 7b demonstrates a lack of true 3D spatial coherence, where people visible in the submitted camera vanish entirely under alternate viewing angles, revealing brittle, view-dependent shortcuts. (3) **Fine-grained Geometric Distortions:** The generated lion cub exhibits unnatural, finger-like paws and distorted eyes, reflecting the model’s inability to inspect and refine high-frequency anatomical details. (4) **Contact Constraint Violations:** The character visibly floats above the lawn, underscoring weak spatial construction and physical simulation ability. Together, these patterns show that current agents tend to rely on 2D visual shortcuts to make things look right at a glance, but they still struggle to build genuinely solid and physically sound 3D scenes. More thorough failure analysis is provided in Appendix E.8.

6 Conclusion

We introduced **BLENDERWORLD**, a benchmark for evaluating visual agents on practical 3D reconstruction, modification, and design in Blender. Its 223 tasks span text-only, image-conditioned, and video-conditioned requests across 9 categories and 16 application scenarios, requiring editable projects and task-specific deliverables. Our evaluation combines task-conditioned multi-view rendering, scene inspection, 2,651 binary criteria, and visual quality assessment to measure both requirement satisfaction and artifact quality. Across 13 agents, GPT-6-Astra achieves the highest overall score of 79.9, yet passes every rubric criterion on only 42.2% of tasks. Qualitative analyses expose incomplete interactions, inconsistencies across views, geometric distortions, and contact violations, highlighting the challenge of translating task requirements and visual references into coherent 3D structure and behavior. **BLENDERWORLD** provides a basis for comparing complete agents and diagnosing these gaps, supporting future work on agents that verify and refine their artifacts against both visual evidence and explicit constraints.

7 Future Work

We plan to extend BlenderWorld in five directions, covering evaluation, task design, and experimental scope.

Interactive and Parametric Evaluation. We plan to give the agent judge Computer-Use Agent (CUA) tools to interact with .blend projects and check rigs, animations, and simulations. By manipulating specified controls and inspecting the resulting states, the judge could test whether mechanisms behave as intended. We will pair structured parameter extraction with deterministic scripts for reproducible checks of dimensions, tolerances, and geometric constraints. For precision-critical tasks, reference solutions and geometric metrics could supplement rubric-based judgments. For example, voxel intersection-over-union would be computed using consistent alignment and scale conventions.

Higher Complexity and Task Diversification. We will expand the benchmark to cover more categories and application scenarios, with an emphasis on demanding professional workflows. Planned tasks include localized editing, mesh fault diagnosis and repair, topology optimization, and retopology, alongside scene creation from scratch. We also plan to introduce engineering drawings and dimensional tolerances as richer specifications, and tasks that require revisions to previously delivered projects. These tasks will assess whether agents preserve existing content, satisfy interacting constraints, and keep projects editable as they revise them.

Expert-Aligned and Fine-Grained Rubrics. We will work with professional 3D artists to iteratively refine the rubrics to reflect practical acceptance standards, with particular attention to modeling reliability, geometric stability, structural consistency, and production readiness. For organic subjects and other cases in which binary checks offer limited discrimination, we will explore graded assessments of individual parts against reference materials. Expert review and agreement studies will guide rubric calibration and assess consistency across viewpoints, animation frames, and application domains.

Multi-DCC Ecosystem and Asset Integration. We aim to support other mainstream digital content creation (DCC) applications, including Maya and 3ds Max, as well as additional Blender versions and MCP tools. Shared task specifications and comparable checks of submitted artifacts will support evaluation across applications. We also plan to integrate external asset repositories, such as the Mixamo motion library, to study workflows that retrieve, adapt, and compose existing assets. Evaluating settings with and without access to these repositories will help assess how external assets affect performance.

Broader Model, Reasoning, Harness, and Platform Coverage. We plan to evaluate more models across supported thinking-effort settings and agent harnesses. Within-model studies will vary reasoning effort under a fixed harness, or compare harnesses with reasoning settings and tool access kept comparable where supported. Experiments will run under documented resource budgets and report task quality together with token usage, latency, tool calls, and cost. Repeated runs on representative configurations will estimate variability and assess the stability of rankings. We will also extend the current Linux-based evaluation to Windows and macOS, and explore providing models with CUA tools for operating Blender through its graphical interface. This would let us observe how models navigate the viewport, manipulate objects, and use visual feedback to inspect and revise their work. Comparisons with API/MCP-based workflows will examine how task performance, interaction efficiency, and failure modes differ across interfaces and operating systems.

References

- Jian Chen, Ruiyi Zhang, Yufan Zhou, Jennifer Healey, Jiuxiang Gu, Zhiqiang Xu, and Changyou Chen. Textlap: Customizing language models for text-to-layout planning. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 14275–14289, 2024. doi: 10.18653/v1/2024.findings-emnlp.833. URL <https://aclanthology.org/2024.findings-emnlp.833/>.
- Shuangrui Ding, Xuanlang Dai, Long Xing, Shengyuan Ding, Ziyu Liu, Yang JingYi, Penghui Yang, Zhixiong Zhang, Xilin Wei, Xinyu Fang, Yubo Ma, Haodong Duan, Jing Shao, Jiaqi Wang, Dahua Lin, Kai Chen, and Yuhang Zang. Wildclawbench: A benchmark for real-world, long-horizon agent evaluation, 2026. URL <https://arxiv.org/abs/2605.10912>.
- Xiaoyu Dong, Zhi Li, and Xiao-Ming Wu. Muse: Benchmarking manufacturable, functional, and assemblable text-to-cad generation, 2026. URL <https://arxiv.org/abs/2605.28579>.
- Anna C. Doris, Jacob Thomas Sony, Ghadi Nehme, Era Sylva, Amin Heyrani Nobari, and Faez Ahmed. Cadbench: A multimodal benchmark for ai-assisted cad program generation, 2026. URL <https://arxiv.org/abs/2605.10873>.
- Alexandre Drouin, Maxime Gasse, Massimo Caccia, Issam H. Laradji, Manuel Del Verme, Tom Marty, Léo Boisvert, Megh Thakkar, Quentin Cappart, David Vazquez, Nicolas Chapados, and Alexandre Lacoste. Workarena: How capable are web agents at solving common knowledge work tasks?, 2024. URL <https://arxiv.org/abs/2403.07718>.
- Yipeng Gao, Lei Shu, Genzhi Ye, Xi Xiong, Ameesh Makadia, Meiqi Guo, Laurent Itti, and Jindong Chen. 3dcodebench: Benchmarking agentic procedural 3d modeling via code, 2026. URL <https://arxiv.org/abs/2606.01057>.
- Yunqi Gu, Ian Huang, Jihyeon Je, Guandao Yang, and Leonidas Guibas. Blendergym: Benchmarking foundational model systems for graphics editing, 2025. URL <https://arxiv.org/abs/2504.01786>.
- Ziniu Hu, Ahmet Iscen, Aashi Jain, Thomas Kipf, Yisong Yue, David A. Ross, Cordelia Schmid, and Alireza Fathi. Scenecraft: An llm agent for synthesizing 3d scene as blender code, 2024. URL <https://arxiv.org/abs/2403.01248>.
- Ian Huang, Guandao Yang, and Leonidas Guibas. Blenderalchemy: Editing 3d graphics with vision-language models, 2024. URL <https://arxiv.org/abs/2404.17672>.

-
- Ryan Li, Yanzhe Zhang, and Diyi Yang. Sketch2code: Evaluating vision-language models for interactive web design prototyping. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 3921–3955. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.naacl-long.198. URL <https://aclanthology.org/2025.naacl-long.198/>.
- Chunjiang Liu, Xiaoyuan Wang, Haoyu Chen, Yizhou Zhao, Ming-Hsuan Yang, and László A. Jeni. Simworlds: A multi-agent system for dynamic 3d scene creation, 2026a. URL <https://arxiv.org/abs/2607.01766>.
- Ling Liu, Bingchen Gong, Amal Dev Parakkat, and Maks Ovsjanikov. 3dharnessbench: Probing agentic 3d-to-code capabilities of frontier vision-language models, 2026b. URL <https://arxiv.org/abs/2609.06535>.
- Shuo Lu, Yinuo Xu, Kecheng Yu, Siru Jiang, Yongcan Yu, Yubin Wang, Haitao Yang, Yuxiang Zhang, Bin Wang, Ran He, and Jian Liang. Worldcoder-bench: Benchmarking physically grounded 3d world synthesis, 2026. URL <https://arxiv.org/abs/2606.01869>.
- Nimra Noor, Muhammad Bilal, Abdullah Hussain, and Hassan Baig. Nova3d: Code-native generation of programmable 3d assets, 2026. URL <https://arxiv.org/abs/2607.22738>.
- OpenAI. GPT-6 Astra: A new generation of intelligence, September 2026. URL <https://openai.com/index/gpt-6-astra/>. Accessed: 2026-09-18.
- Qwen Team. Qwen3.8-max: A new bar for coding and cowork, August 2026. URL <https://qwen.ai/blog?id=qwen3.8>.
- Kean Shi, Zihang Li, Tianyi Ma, Zengji Tu, Jialong Wu, Xinbo Xu, Qingyao Yang, Ruoyu Wu, Weichu Xie, Ming Wu, Jason Zeng, Michael Heinrich, Elvis Zhang, Liang Chen, Kuan Li, and Baobao Chang. Saas-bench: Can computer-use agents leverage real-world saas to solve professional workflows?, 2026. URL <https://arxiv.org/abs/2605.15777>.
- Chenglei Si, Yanzhe Zhang, Ryan Li, Zhengyuan Yang, Ruiibo Liu, and Diyi Yang. Design2code: Benchmarking multimodal code generation for automated front-end engineering. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 3956–3974. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.naacl-long.199. URL <https://aclanthology.org/2025.naacl-long.199/>.
- Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments, 2024. URL <https://arxiv.org/abs/2404.07972>.
- Tianyidan Xie, Peiyu Wang, Hu Jiaxin, Yuyi Qian, Yuxuan Wang, Shenyi Wang, Rui Ma, Yanlun Peng, Lanjun Wang, Ying Tai, Jian Yang, and Zili Yi. Physcodebench: Benchmarking physics-aware symbolic simulation of 3d scenes via self-corrective multi-agent refinement, 2026. URL <https://arxiv.org/abs/2604.23580>.
- Yixuan Yang, Zhen Luo, Wanshui Gan, Jinkun Hao, Junru Lu, Jinghao Yan, Zhaoyang Lyu, and Xudong Xu. Code-as-room: Generating 3d rooms from top-down view images via agentic code synthesis, 2026. URL <https://arxiv.org/abs/2605.18451>.
- Bowen Ye, Rang Li, Qibin Yang, Yuanxin Liu, Linli Yao, Hanglong Lv, Zhihui Xie, Chenxin An, Lei Li, Lingpeng Kong, Qi Liu, Zhifang Sui, and Tong Yang. Claw-eval: Towards trustworthy evaluation of autonomous agents, 2026. URL <https://arxiv.org/abs/2604.06132>.
- Shaofeng Yin, Jiaxin Ge, Zora Zhiruo Wang, Chenyang Wang, Xiuyu Li, Michael J. Black, Trevor Darrell, Angjoo Kanazawa, and Haiwen Feng. Vision-as-inverse-graphics agent via interleaved multimodal reasoning, 2026. URL <https://arxiv.org/abs/2601.11109>.
- Haozhe Zhang, Kaichen Liu, Miaomiao Chen, Lei Li, Shaojie Yang, Cheng Peng, and Hanjie Chen. Benchcad: A comprehensive, industry-standard benchmark for programmatic cad, 2026. URL <https://arxiv.org/abs/2605.10865>.
- Bo Zhao, Maosheng Pang, Chen Zhang, Huan Yang, Yixin Cao, and Wei Ji. Unipptbench: A unified benchmark for presentation generation across diverse input settings, 2026a. URL <https://arxiv.org/abs/2605.17356>.

Yifei Zhao, Xiangxin Zhou, Wenhao Yang, Jiaqi Tang, Pu Jian, Huanjin Yao, Jiarui Yao, Haowei Lin, Chunchao Guo, Zhuo Chen, Wenkai Lyu, Jianzhu Ma, Xueqian Wang, and Wenxi Zhu. Sceneactbench: Can agents act on the 3d scenes they see?, 2026b. URL <https://arxiv.org/abs/2607.22393>.

Yan Zheng and Florian Bordes. Voxelcodebench: Benchmarking 3d world modeling through code generation, 2026. URL <https://arxiv.org/abs/2604.02580>.

Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. Webarena: A realistic web environment for building autonomous agents. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun (eds.), *International Conference on Learning Representations*, volume 2024, pp. 15585–15606, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/file/4410c0711e9154a7a2d26f9b3816d1ef-Paper-Conference.pdf.

A Task Coverage

Each task has one application-scenario label describing its intended use. Table 3 completes the distribution in Figure 3a, including the five smaller scenarios with ten tasks in total.

Table 3: All 16 application scenarios. Counts sum to 223 tasks.

Application scenario	Tasks	Application scenario	Tasks
Storyboarding / previsualization	35	Safety training	15
Product launches	21	Exhibition planning	15
Game assets	21	Construction reporting	15
E-commerce visuals	20	Creative photography	3
Real-estate marketing	19	Interactive exhibits	3
Scientific illustration	18	Travel promotion	2
Renovation proposals	18	Animation / rigging	1
Classroom teaching	16	AR avatars	1

The input combinations are 56 briefs without references or attachments, 22 with specifications only, 93 with images only, 37 with images and specifications, and 15 with videos. Thus, Text denotes the 78 tasks without image or video references, including 22 with specifications; Multimodal denotes the other 145 tasks. The 59 specification attachments comprise 28 Markdown, 20 YAML, and 11 JSON files.

B Rubric Construction

From sources to acceptance conditions. The generator reads the query, actual references, and full attachments, then records binding requirements with source locations and verification methods. This ledger covers structure, space, appearance, function, presentation, and delivery as applicable. Requirements are extracted before compression, preserving both explicit constraints and allowed design freedom.

Related requirements form a coherent acceptance unit, such as a component, interface, functional outcome, or deliverable. Each criterion records its identifier, subject, source, category, importance, evidence type, and self-contained pass/fail conditions. A merged criterion passes only when *all* constituent conditions hold; its fail condition is the logical complement. Major, secondary, and detail criteria receive weights 3, 2, and 1.

Category vocabulary. Each criterion receives one of the 13 categories in Table 4, according to its principal focus. Its full acceptance conditions retain any requirements spanning several aspects. The six ledger dimensions guide source coverage; these categories describe the resulting criteria. The *holistic* category is a task-specific binary check, separate from the eight quality ratings in Appendix C.

Table 4: Category vocabulary for binary rubrics. Properties are checked when required by the task materials.

Category	Principal focus
presence	Required subjects or components and their recognizable identity.
count	Number of objects, parts, or repeated units.
geometry	Shape, silhouette, topology, modeling details, and structural completeness.
scale	Absolute dimensions and relative proportions.
layout	Placement, arrangement, and pose of objects or components.
space_layout	Scene organization, zoning, clearances, and circulation.
material	Surface identity, texture, roughness, transparency, and reflection.
color	Specified colors, palettes, and their distribution.
lighting	Light configuration, illumination effects, shadows, and brightness.
composition	Viewpoint, framing, subject coverage, occlusion, and visual readability.
physics	Contact, support, collision, deformation, and motion.
function	Functional outcomes, editability, engineering settings, and file delivery.
holistic	Task-specific overall identity, style, and completeness.

Assigning observable evidence. Rendered views and exported media support visible shape, appearance, composition, and motion. Scene/file inspection supports exact dimensions, topology, internal structure, configuration, and output metadata. A criterion combining native properties and visible effects

uses the scene-inspection route, whose judge can also consult images. The frozen set assigns 1,107 criteria to render and 1,544 to scene_summary.

Pilot diagnosis and independent review. GPT-5.6-Sol drafts and edits the rubrics. Pilot judgments of its outputs flag ambiguity, repeated decisions, and missing evidence. Review traces each issue to criterion content, evidence collection, or judge execution; corrections require support from the task sources. At least two models independently inspect the same candidate and materials without seeing other reviews or evaluated-model scores. Reviewers include GPT-5.6-Sol, Gemini 3.1 Pro Preview, and Claude Opus 4.8. They check coverage, unsupported constraints, duplication, merging, weights, pass/fail consistency, and evidence suitability. Human review complements this process.

Cross-checking and freezing. Findings cite sources and a counterexample: a valid output that would fail, or a violating output that would pass. Reviewers cross-check these findings, and the editor records the adopted corrections and reasons. Changes in meaning receive another independent review. Finalization requires resolution of substantive findings and checks of identifiers, category/evidence values, weights, binary fields, and source coverage. Snapshots and review records preserve provenance; accepted conditions, weights, and evidence assignments are frozen for evaluation.

C Scoring Details

Dimension definitions and anchors. Table 5 summarizes the eight dimensions in the judge instructions. Each receives an integer rating using the same anchors: **1–2**, absent, broken, or unrecognizable; **3–4**, major failures and only loose resemblance; **5–6**, acceptable with clear defects; **7–8**, mostly correct with minor issues; and **9–10**, essentially faithful with only trivial flaws. The judge cites decisive files or views and records the observed issues for each rating. The brief and references define the target, including any intended stylization.

Table 5: Dimension-specific assessment. These visual ratings complement the binary checks of task requirements and native project properties.

Dimension	Assessment focus
Scene fidelity	Recognizable target scene, principal subjects, and overall arrangement.
Physical plausibility	Support, attachment, thickness, coherent structures, and absence of floating or intersecting parts.
Style and color	Recognizable object shapes and silhouettes, with colors appropriate to the target.
Realism	A believable, coherent image with adequate contrast and render quality; appropriate simplification may preserve object identity.
Spatial layout	Relative positions, orientations, and spacing, including adjacency and front-back relationships.
Proportion and scale	Plausible size ratios between objects, their parts, and the surrounding scene.
Lighting and materials	Surface appearance, illumination, and shadows appropriate to the intended result; suitable matte finishes are acceptable.
Completeness	Presence of the required objects in approximately the right counts, without important omissions.

D Runtime and Resource Accounting

D.1 Runtime Configuration

The reference runtime uses Blender 4.2.10 LTS, Codex CLI 0.147.0, Claude Code 2.1.220, and Node.js 22.17.0. GPT-6-Astra and GPT-5.6-Sol use Codex; the other eleven systems use Claude Code. MiniMax-M3’s 48-task batch uses Claude Code 2.1.241. Isolated Linux workspaces provide one NVIDIA GPU per task, a virtual display, and Cycles rendering through OptiX or CUDA. The final workspace is archived for evaluation.

D.2 Available Tools

The harness provides shell execution, file operations, and local image viewing. Agents can write scripts, launch Blender in background mode, inspect renders, and revise their projects. FFmpeg and ImageMagick support media processing, alongside NumPy, Pillow, SciPy, and ImageIO. The Blender MCP endpoints below omit the common mcp__blender__ prefix.

- **Scene editing and inspection.** `execute_blender_code` runs Python inside Blender. `get_scene_info` and `get_object_info` return scene structure and object properties; `get_viewport_screenshot` provides visual feedback.
- **Materials and environment assets.** `get_polyhaven_status`, `get_polyhaven_categories`, `search_polyhaven_assets`, and `download_polyhaven_asset` support availability checks, discovery, and retrieval. `set_texture` applies textures.
- **External model retrieval.** `get_sketchfab_status`, `search_sketchfab_models`, `get_sketchfab_model_preview`, and `download_sketchfab_model` provide availability checks, search, previews, and model import.

D.3 Resource Accounting

We record resource counters (including output tokens, interaction turns, and tool calls) across the full suite of 223 tasks for all evaluated agents. These counters incorporate unsuccessful calls. Output tokens reflect provider-reported completion counts. A turn is uniformly defined as a single model-response round within the agent runtime.

As shown in Figure 6, tool calls are grouped into five exclusive categories: *Blender execution* (direct Blender/Python and MCP code calls); *image viewing* (reference images, renders, and viewport screenshots); *scene queries* (scene/object information); *asset operations* (discovery, status, retrieval, generation, import, and texture assignment); and *other*. Compound calls are counted as a single operation. Category means are computed by dividing pooled counts by the total 223 tasks, and shares are calculated against total tool calls. These metrics strictly describe requested operations, rather than guaranteed successful executions or matched compute costs.

E Supplementary Analysis and Examples

E.1 Detailed Analysis of Judge Model

We evaluate the judge models on 150 pairs of artifacts generated for the same input, with each pair assessed by three human reviewers. The majority human preference label, C_i , requires at least two of the three reviewers to agree on A, B, or a tie. Three cases where A, B, and a tie each received one vote are excluded, leaving 147 cases for evaluation. For each judge, we examine the Rubric, Dimension, and Overall scores, where the Overall score is the equally weighted average of the Rubric and Dimension scores (i.e., $0.5 \text{ Rubric} + 0.5 \text{ Dimension}$). To calculate agreement, the majority preference label C_i is encoded as +1 for preferring A, -1 for preferring B, and 0 for a tie. The machine’s predicted preference, $J_i = \text{sign}(s_{iA} - s_{iB})$, must exactly match the majority label C_i . Preference correlation metrics (Pearson’s r , Spearman’s ρ , and Kendall’s τ_b) are derived by computing the correlation between the raw score difference $s_{iA} - s_{iB}$ and the majority label C_i across these 147 cases.

We additionally report pairwise agreement on cases with a small average score gap (< 10 points). This small-gap subset contains 70 eligible cases satisfying $|\bar{s}_A - \bar{s}_B| < 10$, where $\bar{s}_X$ is the mean Overall score of artifact X across the three judge models (GPT-5.6-terra, Gemini-3.8-Flash, and DeepSeek-V4.1-Flash).

Table 6 shows that the Overall scores achieve the highest pairwise agreement on the full set of 147 cases for all judge models: 82.99% for GPT-5.6-terra, 77.55% for Gemini-3.8-Flash, and 76.87% for DeepSeek-V4.1-Flash. However, on the small-gap subset, the agreement for these three models decreases to 68.57%, 58.57%, and 55.71%, respectively. This indicates that alignment between machine and human judgments becomes significantly more difficult when the artifacts receive very similar average scores. We also observe that the Dimension scores consistently outperform the Rubric scores in terms of agreement across all models. For all preference correlation metrics, GPT-5.6-terra’s Overall score performs the best (Pearson’s $r = 0.714$, Spearman’s $\rho = 0.744$, Kendall’s $\tau_b = 0.607$). **These findings denote that GPT-5.6-terra is the judge model that best aligns with human scoring preferences. Its scoring is relatively reliable and accurate.**

E.2 Completion across Rubric Thresholds

Figure 8 measures the fraction of tasks whose weighted Rubric score reaches threshold t : $C_m(t) = \frac{1}{223} \sum_{q=1}^{223} \mathbf{1}[R_{mq} \geq t]$. Missing scores remain zero. Because every criterion has positive weight, $t = 100$ recovers Perfect. GPT-6-Astra covers 143 tasks at $t = 90$ but 94 at $t = 100$; Opus-5 drops from 85 to 57. Thus, 49 GPT-6-Astra outputs and 28 Opus-5 outputs satisfy at least 90% of the criterion weight while still missing at least one rubric. The curves distinguish high weighted coverage from complete acceptance on the fixed task set; only the reporting threshold changes.

Table 6: **Alignment of automatic judges with human preferences.** We evaluate 150 pairs of different artifacts generated for the same input, each rated by three human reviewers. Three cases with one vote for each category are excluded, leaving 147 cases. We compare rubric, dimension, and overall scores with the majority human preference.

Judge model	Aspect	Pairwise agreement ($\uparrow$)		Preference correlation ($\uparrow$)		
		Overall 147 cases	Mean score gap < 10 70 cases	Pearson r	Spearman ρ	Kendall τ_b
GPT-5.6-terra	Rubric	73.47%	51.43%	0.643	0.674	0.554
	Dimension	79.59%	64.29%	0.708	0.722	0.596
	Overall	82.99%	68.57%	0.714	0.744	0.607
Gemini-3.8-Flash	Rubric	56.46%	32.86%	0.535	0.559	0.474
	Dimension	76.19%	58.57%	0.622	0.691	0.569
	Overall	77.55%	58.57%	0.652	0.681	0.556
DeepSeek-V4.1-Flash	Rubric	65.99%	38.57%	0.593	0.609	0.503
	Dimension	74.83%	57.14%	0.623	0.634	0.522
	Overall	76.87%	55.71%	0.657	0.674	0.549




Figure 8: **Coverage at increasing Rubric thresholds.** (a) Fraction of the 223 tasks at or above each threshold; gray curves represent the other nine systems. (b) Thresholds 90 and 100 for the four highest-scoring systems. Bar labels give task counts.

E.3 Component Scores and Unmet Criteria

Figure 9 places the two component means alongside the number of unmet criteria per task. GPT-6-Astra and Opus-5 lead on both components, but their full-pass counts conceal additional variation: GPT-6-Astra has 94 fully passing outputs and 64 with one unmet criterion, compared with 57 and 51 for Opus-5. Moreover, one criterion may combine several conditions, so a single unmet criterion does not establish that repair is easy.

E.4 Overlap in Fully Completed Tasks

Figure 10 compares each system’s fully passing tasks with GPT-6-Astra’s on the same 223 task identifiers. GPT-6-Astra and Opus-5 both pass 40 tasks; 54 pass only under GPT-6-Astra and 17 only under Opus-5, leaving 112 passed by neither. GPT-5.6-Sol and DeepSeek-V4.1-Flash contribute 11 and 7 additional tasks, respectively, beyond GPT-6-Astra. These counts show that the successful task sets are not fully nested, even the worst Minimax-M3 still has 1 perfect task beyond GPT-6.




Figure 9: **Score components and unmet requirements.** (a) Task-mean Rubric and Dimension scores, retaining all 223 tasks with missing components set to zero. (b) Task counts by number of unmet binary criteria, with unscored evaluations shown separately. Zero unmet criteria corresponds to Perfect.




Figure 10: **Paired overlap in complete rubric satisfaction.** Each bar partitions the same 223 tasks by whether GPT-6-Astra and the comparator pass every binary criterion. The dotted line marks GPT-6-Astra's 94 full passes; +n counts comparator-only passes beyond that set.

E.5 Dimension and Rubric Profiles

Figure 11 separates eight quality ratings from the 13 binary-criterion categories. Realism has the lowest mean dimension rating for every system. For GPT-6-Astra, it averages 6.61/10, compared with 7.89/10 for completeness; Opus-5 averages 5.62/10 on realism. The criterion profiles reveal variation in requirement satisfaction: Opus-5 passes 87.6% of function criteria, compared with 73.5% for geometry, 71.8% for material, and 66.1% for physics, while GPT-6-Astra exceeds 80% in every category. These criterion rates pool different numbers of checks, shown below the heatmap. They summarize category-specific outcomes, whereas the main Rubric score normalizes importance weights within each task.




Figure 11: **Quality dimensions and binary-criterion categories.** (a) Mean 1–10 ratings over valid dimension judgments only. (b) Unweighted criterion pass rates, counting missing outcomes as non-passes; Parentheses give criteria per system.

E.6 Sensitivity to the Fusion Weight

We recompute $S = \lambda S_{\text{rubric}} + (1 - \lambda) S_{\text{dim}}$ at $\lambda \in \{0, 0.25, 0.5, 0.75, 1\}$, holding the selected artifacts and judgments fixed. Each mean retains 223 tasks, unscored evaluations remain zero. The ranking is unchanged at these weights except for Grok-4.6 and Opus-4.8: Opus-4.8 ranks seventh at 0 and 0.25, and Grok-4.6 ranks seventh at 0.5, 0.75, and 1 (Figure 12b).

Although the overall model rankings are highly stable, at a micro level, the two scoring criteria actually show differences when evaluating specific 3D artifacts. As illustrated by the scatter plot in Figure 12a, the Spearman correlation coefficient across the 2,899 output artifacts is 0.630. **While this indicates a positive**

overall trend—meaning artifacts that follow instructions better generally tend to have better visual quality, the data points are still widely dispersed rather than tightly hugging the diagonal line. The underlying reason is that they measure completely different aspects of capability. For instance, some outputs dutifully satisfy all objective instructions (achieving a high Rubric score), but their rendered visual and physical quality is poor, suffering from issues like mesh clipping or unnatural lighting (resulting in a low Dimension score). Conversely, some outputs look visually stunning and realistic, but fail to strictly follow the specific task constraints. Therefore, even though these two measurement methods yield a largely consistent overall model leaderboard, they retain their own distinct and irreplaceable focuses when evaluating individual generated artifacts.




Figure 12: **Score components and fusion-weight sensitivity.** (a) Paired scores for 2,899 outputs, with logarithmic bin counts. (b) System ranks at five rubric weights; the main Score uses $\lambda = 0.5$. All 223 tasks remain in each system mean.

E.7 Task-Category Profiles for All Systems

Figure 13 extends the five-system comparison in Figure 5a to all thirteen systems. Every system scores higher on Procedural & Game Assets than on Art & Animation or Characters & Animals. GPT-6-Astra leads eight categories; Rendering & Simulation is the exception, where Opus-5 scores 74.5 versus GPT-6-Astra’s 71.1. GPT-6-Astra’s category means range from 71.1 in Rendering & Simulation to 86.8 in Procedural & Game Assets.

The leading-system ranking persists under equal category weighting. Because the nine categories contain 9–72 tasks, we also average their mean Scores with equal weights, keeping the same 223 outputs per system. The macro-average and task-level rankings have Spearman $\rho = 0.995$ and Kendall $\tau = 0.974$: the top four retain their order, and only Qwen3.8-Max and GLM-5.3-Flash exchange fifth and sixth place (Figure 14).

E.8 Connecting Defects to Actions

Two artifacts in Figure 7 are linked to their selected generation traces with explanations below. Figure 15 details selected operations for the *viewpoint inconsistency* and *missing ground contact* cases, and also adds an Opus-5 example to explain another defect.

Viewpoint inconsistency. For this case, GPT-6-Astra segments the two people from the reference and maps each crop onto a single flat quad, with separate shadow proxies. The trajectory analysis in the figure 15 also indicates that the established character object is bound to a camera-facing photographic projection, rather than to a human model with a skeleton. This representation explains their appearance from the submitted camera and disappearance in the side view. The frozen judgment likewise identifies one-sided photographic cards. The defect is the missing volume needed for this scene’s alternate views; texture refinement alone cannot supply it.




Figure 13: **Task-category scores for all thirteen systems.** Cells show mean fused Score on each category’s fixed task subset, including assigned zeros. Category sizes appear below the columns; cells are rounded to the nearest integer.




Figure 14: **Rankings are largely stable under equal category weighting.** (a) Bars show each category’s weight in the task-level mean; labels give task counts. The dashed line marks the equal 1/9 weight used by the macro-average. (b) Scores and ranks under the two aggregation rules for the same thirteen systems and 223 selected outputs per agent. Colored paths mark the sole rank exchange: Qwen3.8-Max and GLM-5.3-Flash at positions 5 and 6. Scores beside each endpoint follow that side’s rank order.

Missing Ground Contact. In this task, the goal was to generate a forced-perspective image featuring a person lying on the grass with their shoes visually aligned with a distant tower. GPT-5.6-Sol demonstrated intelligence and rigor by utilizing code tools to establish alignment markers and precisely calculate projection errors; it even implemented a strict validation step requiring the alignment error to remain below 1×10^{-6} . However, the model’s fatal flaw lay in its obsessive focus on satisfying the mathematical constraints of the 2D projection while completely overlooking fundamental 3D physical realities—specifically, the need for the figure to be physically supported by the ground. As shown in the detailed view on the right, although the feet and the tower aligned perfectly from the specific camera angle, the person’s body was actually suspended absurdly in mid-air above the grass, leaving a clearly visible gap. This highlights a common limitation in current agents: they tend to solve specific, explicit instructions mechanically but lack a holistic grasp of 3D spatial structures and physical laws such as gravity and contact.

Specification drift in a self-check. For this case, the input brief requires 150 mm wooden legs with brass casters. Opus-5’s TaskCreate instead specifies 150 mm including the casters, and its geometry script builds 102 mm of timber on 48 mm casters (Figure 15c). The subsequent verifier measures the floor-to-frame height and reports 150.0 mm as passing. The frozen scene inspection separately measures the timber at 102 mm, 32% shorter than required, and marks R02 as failed. The self-check thus confirms the false measurement target while leaving the original component-length requirement unsatisfied.




Figure 15: **Selected operations in three failure trajectories.** (a) GPT-6-Astra maps reference people onto textured flat quads. (b) GPT-5.6-Sol checks projection markers while the body remains unsupported. (c) Opus-5 checks the combined leg-and-caster height in place of the specified timber length. Images in (a) and (b) are archived renders; the dimension bars in (c) are schematic.

E.9 Paired Case Studies across Six Tasks

(a) Exhibition booth. Recreate the reference layout, branded panels, and hatch with a visible lunar rover.

Opus-5 Rubric 100.00 · Dimension 81.25 · Total 90.62

TRACE SUMMARY · trace-based paraphrase
Build a 3D lunar set behind the hatch, clear sightlines with ray casting and mesh repairs, then tune lighting and render at 4K.

SELECTED TOOL CALLS

Read + get_scene_info → execute_blender_code → execute_blender_code
Inspect photo and scene → Ray-cast; repair hatch cuts → Render 4K; save project

CODE EXCERPT · Blender MCP · hatch visibility check

```
dg = bpy.context.evaluated_depsgraph_get()
o, chain = eye.copy(), []
for i in range(24):
    ok, loc, nrm, idx, obj, _m = bpy.context.scene.ray_cast(dg, o, d)
    ...
    o = loc + d * 0.004
```

FINAL OUTPUT · original delivered pixels



3840 × 2160 PNG · physical lunar diorama behind the hatch
csa_capsule_booth.blend + csa_capsule_booth_4K.png

GPT-6 Rubric 100.00 · Dimension 85.00 · Total 92.50

TRACE SUMMARY · trace-based paraphrase
Build the booth in named modules. Render a separate lunar scene, pack it into a self-lit hatch display, then refine the final presentation.


SELECTED TOOL CALLS

exec_command → apply_patch → execute_blender_code
Locate reference; inspect inputs → Build lunar and booth scripts → Render vista, booth and export

CODE EXCERPT · 03_hatch_ceiling.py · image-backed hatch

```
tx=n.new('ShaderNodeTexImage')
tx.image=lm
em=n.new('ShaderNodeEmission')
em.inputs['Strength'].default_value=9
l.new(tx.outputs['Color'],em.inputs['Color'])
l.new(em.outputs[0],out.inputs[8])
```

FINAL OUTPUT · original delivered pixels



3840 × 2560 PNG · packed lunar image behind a modeled hatch
CSA_Space_Capsule_Booth.blend + CSA_Booth_Hero.png

(b) Lion cub. Recreate the central cub with realistic anatomy and distinct fur, whiskers, and nose; deliver three 1080p views.

Opus-5 Rubric 55.56 · Dimension 37.50 · Total 46.53

TRACE SUMMARY · trace-based paraphrase
Block out and resculpt the cub, retopologize and UV it, then generate regional fur curves, add a rig and export three product views.

SELECTED TOOL CALLS

Write / Blender MCP → execute_blender_code → Read / Blender MCP
Blockout, sculpt and retopology → Generate fur; bake and rig → Review and render three views

CODE EXCERPT · s05_fur.py · region-weighted fur sampling

```
cen = (a + b + c) / 3.0
dens = region_blend(cen)[3] * bald_mask(cen)
w = area * dens
...
w = w / w.sum()
idx = RNG.choice(len(tri), size=n_target, p=w)
```

FINAL OUTPUT · original delivered pixels

Hero view Paw view



Three 1920 × 1080 PNGs · procedural fur, whiskers and a rig
Blender project + 01_hero / 02_threequarter / 03_paw.png

GPT-6 Rubric 68.89 · Dimension 53.75 · Total 61.32

TRACE SUMMARY · trace-based paraphrase
Build the body and zoned fur in stages; refine the face and paws, then add a rig, normal maps and three product views.

SELECTED TOOL CALLS


exec_command → execute_blender_code → get_viewport_screenshot
Write staged body/groom scripts → Refine face; bake; bind rig → Inspect final saved scene

CODE EXCERPT · 02_groom.py · surface sampling for hair roots

```
inds=rng.choice(len(tris),count,p=areas/total)
tw=tris[inds]
a=rng.random(count); b=rng.random(count)
sq=np.sqrt(a)
weights=np.stack([1-sq,sq*(1-b),sq*b],axis=1)
```

FINAL OUTPUT · original delivered pixels

Hero view Forepaw view



Three 1920 × 1080 PNGs · zoned fur, baked maps and a rig
Soleil_Lion_Cub.blend + 01_Hero / 02_Three_Quarter / 03_Forepaw.png

(c) Chesterfield sofa. Build a 2200 × 950 × 750 mm sofa with 150 mm wooden legs plus casters; render at 4K.

Opus-5 Rubric 75.00 · Dimension 87.50 · Total 81.25

TRACE SUMMARY · trace-based paraphrase
Build shell, cushions and trim; use 102 mm timber plus 48 mm casters. Calibrate the geometry with a floor-to-frame check.

SELECTED TOOL CALLS

TaskCreate + Write → download_polyhaven_asset → execute_blender_code
Split shell, cushions, trim, legs → Load HDRI for the studio → Run verify.py; render and save

CODE EXCERPT · verify.py · floor-to-frame measurement

```
base = world_verts(grp("SofaBaseUnder"))
line("leg height (floor to frame)", base[:, 2].mean(), SPEC("leg height"))
legs = world_verts(grp("Leg"))
line("caster tread touches floor", legs[:, 2].min(), 0.0)
```

FINAL OUTPUT · original delivered pixels



3840 × 2160 PNG · verifier reports 150 mm floor-to-frame: ok
chesterfield_3seat.blend + chesterfield_hero_3840x2160.png

GPT-6 Rubric 90.62 · Dimension 70.00 · Total 80.31

TRACE SUMMARY · trace-based paraphrase
Create parametric tufting and trim, lathe 150 mm timber legs with separate casters, then add leather, HDRI and studio lighting.

SELECTED TOOL CALLS

search_polyhaven_assets → apply_patch → execute_blender_code
Find leather and HDRI → Build parametric sofa scripts → Finalize materials and exports

CODE EXCERPT · sofa_builder.py · separate timber leg geometry

```
p[:,1]=np.clip(p[:,1],.035,.185)
vv,ff=lathe_geometry(p,64)
...
ob["timber height mm"]=150.0
o["wheel diameter mm"]=32.0
```

FINAL OUTPUT · original delivered pixels



3840 × 2160 PNG · timber profile spans x = 0.035–0.185 m
Chesterfield_220_Studio.blend + Chesterfield_220_Hero_4K.png

Figure 16: Construction and verification across three typical workflows. Opus-5 is on the left and GPT-6-Astra on the right. Both booth outputs pass all binary criteria. Both lion cub pipelines construct fur and rigging, yet their dimension scores remain 37.50 and 53.75. The sofa reverses the ordering across components: Opus-5 has higher Dimension (with better lighting), while GPT-6-Astra has higher Rubric; Figure 15c details the timber-length error.

(d) **Treasure chest.** Build a chest with a lid, hinges, lock, and riveted trim; bake details onto a mesh of at most 3,000 faces.

Opus-5 Rubric 100.00 · Dimension 82.50 · Total 91.25

TRACE SUMMARY · trace-based paraphrase
Build high/low meshes and audit UVs; bake matched parts into normal/AO maps, then shade, render and export FBX.

SELECTED TOOL CALLS

Write / Blender MCP Build high and low meshes	execute_blender_code Audit UVs; bake normals/AO	execute_blender_code Render 45° view; export FBX
---	---	--

CODE EXCERPT · 04_bake.py · selected-to-active texture baking

```
bk = sc.render.bake
bk.use_selected_to_active = True
bk.cage_extrusion = 0.014
bk.max_ray_distance = 0.055
...
bpy.ops.object.bake(type='bake_type')
```

FINAL OUTPUT · original delivered pixels




1920 × 1080 showcase · separate high/low meshes and baked detail
medieval_chest.blend + lowpoly.fbx + normal/AO maps + PNG

GPT-6 Rubric 100.00 · Dimension 96.25 · Total 98.12

TRACE SUMMARY · trace-based paraphrase
Build paired meshes and PBR maps, repair bake artifacts and audit UVs, then re-import GLB/FBX exports to validate the asset.

SELECTED TOOL CALLS

apply_patch Write builder, UV and bake scripts	execute_blender_code Bake; repair and audit textures	exec_command / MCP Validate exported GLB and FBX
--	--	--

CODE EXCERPT · chest_bake.py · tangent-space normal baking

```
s.render.bake.use_selected_to_active=True
s.render.bake.cage_extrusion=.027
s.render.bake.normal_space='TANGENT'
...
bpy.ops.object.bake(type='NORMAL')
IPAGES['Normal_GL'].save()
```

FINAL OUTPUT · original delivered pixels




1900 × 1600 beauty · 2,756 triangles in saved runtime QA reports
Warden_Coffer_Master.blend + Game.glb / .fbx + PBR maps

(e) **Cell membrane.** Illustrate a curved bilayer with inward tails, membrane protein, glycoproteins, and DNA.

Opus-5 Rubric 100.00 · Dimension 66.25 · Total 83.12

TRACE SUMMARY · trace-based paraphrase
Build a domed membrane with a shared cutaway plane and batched meshes; refine protein placement, DNA scale, framing and materials.


SELECTED TOOL CALLS

Read + Write Inspect reference; write builders	execute_blender_code Batch lipids; solve cutaway view	execute_blender_code Inspect crops; render and reopen
--	---	---

CODE EXCERPT · build_scene.py · consistent cut across both leaflets

```
for leaflet in ('outer', 'inner'):
    outward = (leaflet == 'outer')
    r_layer = R_MID + T_HALF if outward else R_MID - T_HALF
    if cut_away(world_pt(n, R_MID)):
        continue
```

FINAL OUTPUT · original delivered pixels



3840 × 1536 PNG · domed cutaway with repeated molecular geometry
cell_membrane_schematic.blend + cell_membrane_schematic.png

GPT-6 Rubric 100.00 · Dimension 68.75 · Total 84.38

TRACE SUMMARY · trace-based paraphrase
Place heads on two curved leaflets, give each head two inward tails, then add proteins, DNA and a clean explanatory camera view.


SELECTED TOOL CALLS

exec_command + apply_patch Inspect input; write scene modules	execute_blender_code Build bilayer, proteins and DNA	execute_blender_code Finalize Cycles render and project
---	--	---

CODE EXCERPT · 02_bilayer.py · two inward tails per lipid head

```
for side in (1,-1):
    ...
    center=pside*HALF*n
    for branch in (-1,1):
        inward=side*n
        off=branch*.896*u
```

FINAL OUTPUT · original delivered pixels



4800 × 3000 PNG · explicit head/tail pairs and open membrane section
membrane_schematic.blend + membrane_schematic.png

(f) **Model-train animation.** Match the reference train and camera motion with an editable rig; deliver ~2.7 s at 1080p/30 fps.

Opus-5 Rubric 93.88 · Dimension 45.00 · Total 69.44

TRACE SUMMARY · trace-based paraphrase
Sample the reference video, build the diorama and one progress control, verify axle/path motion, then render and encode the clip.

SELECTED TOOL CALLS

bash ffprobe / ffmpeg: sample frames	Write / Blender MCP Build rig; check path offsets	bash ffmpeg: encode H.264 video
--	---	---

CODE EXCERPT · s3_rig.py · progress-driven code path offsets

```
fc = con.driver_add('offset_factor')
d = fc.driver
d.type = 'SCRIPTED'
v.targets[0].data_path = '["progress_m"]'
v2.targets[0].data_path = '["off_m"]'
d.expression = "((p + o) / %.9f) * 1.0" % CIRC
```

FINAL OUTPUT · original delivered pixels





1920 × 1080 H.264 · 30 fps · 80 frames · editable train/camera controls
miniature_railway_previz.blend + miniature_railway_previz.mp4

GPT-6 Rubric 100.00 · Dimension 68.75 · Total 84.38

TRACE SUMMARY · trace-based paraphrase
Fit the camera with SciPy least_squares, drive cars on a shared loop, refine scenery, then render 80 frames and encode the clip.

SELECTED TOOL CALLS

exec_command ffprobe / ffmpeg: sample frames	exec_command / MCP Fit camera; build path-driven rig	exec_command ffmpeg: encode H.264 video
--	--	---

CODE EXCERPT · 01_foundation.py · shared path, per-car offset

```
con=root.constraints.new('FOLLOW_PATH')
con.use_curve_follow=True
con.use_fixed_location=True
d=con.driver_add('offset_factor').driver
d.type='SCRIPTED'
d.expression="(p-o*s/c)*1.0"
```

FINAL OUTPUT · original delivered pixels





1920 × 1080 H.264 · 30 fps · 80 frames · editable path and camera keys
miniature_railway_previz.blend + miniature_railway_previz.mp4

Figure 17: **Construction and verification across another three workflows.** Opus-5 is on the left and GPT-6-Astra on the right. Both systems use high-to-low texture baking for the chest and construct two membrane leaflets, with all binary criteria passing in both tasks. Their checks differ in the train task: Opus-5 inspects axle/path parameterization, while GPT-6-Astra fits the camera numerically. Both deliver 80-frame clips at 30 fps, but GPT-6-Astra has higher frozen Rubric and Dimension scores. The frames show 0.00, 1.30, and 2.60 s.