

UniACE: A Unified Framework for Evaluating LLM Agentic Capabilities

Pengyu Zhu^{1,2*}, Lijun Li^{2*†}, Yaxing Lyu^{2*}, Qianxin Luo⁴, Jingyi Yang⁴, Yi Liu¹, Tingfeng Hui¹, Xinyu Yuan⁴, Li Sun^{1†}, Sen Su^{1,3†}, Jing Shao^{2†}

¹Beijing University of Posts and Telecommunications

²Shanghai Artificial Intelligence Laboratory

³Chongqing University of Posts and Telecommunications

⁴North China Electric Power University

whfelingyu_zhupengyu@bupt.edu.cn

Abstract

Agent benchmarks are increasingly used to compare large language models (LLMs) across domains, yet a reported score reflects a complete model–harness–environment configuration rather than the model alone. Benchmark packages couple native tasks with specific prompts, tool protocols, orchestration logic, and sometimes dynamic external resources, making cross-benchmark comparisons sensitive to implementation and resource conditions. We present **UniACE**, a unified framework for model-centric evaluation under an explicit, common execution condition. UniACE represents each benchmark as an instruction–tool–environment triplet, executes LLMs through a shared, task-agnostic harness in isolated per-task runtimes, and preserves native success criteria. For tasks that rely on dynamic resources, an optional offline mode replaces live access with fixed, pre-collected snapshots. Its evaluation protocol further standardizes efficiency measurement, execution records, and trace-based failure attribution. We migrate 7 benchmarks spanning 24 domains and evaluate 15 models in more than 400K rollouts consuming 5B tokens. Comparisons with source implementations show large bidirectional score changes and model-ranking reversals, while matched online and offline runs reveal substantial sensitivity to accessible evidence and its representation. Under the shared UniACE configuration, efficiency and failure profiles expose task-dependent model behaviors hidden by task-success scores alone. These findings motivate reporting agent benchmark outcomes as properties of an explicit evaluation configuration, enabling more interpretable and reproducible cross-benchmark comparisons.

1 Introduction

Large language models (LLMs) increasingly serve as the main component of agents that plan, interact with environments, and perform complex multi-step tasks (Yehudai et al. 2026; Xi et al. 2025; Pati 2025; Wang et al. 2024; Qin et al. 2023). Correspondingly, a growing number of benchmarks have been developed to evaluate model behavior in agentic settings, including software engineering, web interaction, function calling, customer service, multi-agent collaboration, and safety-critical scenarios. (Jimenez et al. 2024; Team

2025; Mialon et al. 2024; Wei et al. 2025; Liu et al. 2024; Yao et al. 2022, 2025; Barres et al. 2025; Zhu et al. 2025a; Zhang et al. 2025). As these results are increasingly used to compare LLMs across domains, a key question is how sensitive the resulting comparisons are to benchmark-specific harnesses and environments.

This sensitivity arises because the benchmark score is produced by a complete model–harness–environment configuration rather than by the model in isolation. Most benchmarks are released as executable packages that couple task data and success criteria with benchmark-specific system prompts, memory formats, tool schemas, orchestration logic, retry policies, and termination rules (Liu et al. 2024; Patil et al. 2025; Yao et al. 2025; Barres et al. 2025; Zhu et al. 2025a). Although these choices are necessary for execution, they can interact with models differently: one model may benefit from a particular action format or retry policy while another may not. Prior studies report substantial performance variation across agent scaffolds (Kapoor et al. 2026; Zhu et al. 2026; Hui et al. 2026; Bandel et al. 2026). Consequently, comparisons assembled from independently packaged benchmarks can mix model behavior with compatibility with their surrounding implementations.

Recent systems address this heterogeneity, but target different evaluation objects. HAL evaluates benchmark-specific and general-purpose scaffolds, while General Agent Evaluation connects heterogeneous complete agents to multiple benchmarks; Harbor primarily provides execution and mediation infrastructure (Harbor Framework Team 2026; Kapoor et al. 2026; Bandel et al. 2026). These efforts compare or support complete agent systems, in which the scaffold remains part of the evaluated object. What remains missing is a model-centric setting that holds a common harness fixed across benchmark-native tasks while making the execution condition explicit. Such a setting must preserve native tasks and success criteria, isolate task state, and record efficiency and failure evidence alongside task success. It must also address dynamic resources: on live-web tasks, changes in page availability, retrieval results, tool output can appear as model failures even when the required evidence was inaccessible.

We introduce **UniACE** to provide this controlled evaluation setting. Its central design separates benchmark-specific

*These authors contributed equally.

†Corresponding author.

content from shared execution choices through three stages. In **Benchmark Setup**, UniACE accepts benchmarks specified as an instruction–tool–environment triplet, preserves its native success criteria, and records shared execution choices in a common configuration. In the **Agent Sandbox**, UniACE instantiates the LLM in a shared, task-agnostic harness and creates an isolated runtime for each task. For tasks that depend on dynamic resources, the sandbox optionally replaces live access with fixed, pre-collected snapshots, holding accessible content and its representation constant across runs. Finally, the **Evaluation Protocol** applies the native success criteria while standardizing the collection of interaction steps, token usage, runtime, and trace-based failure attributions. UniACE thus makes harness and environment choices explicit experimental conditions rather than claiming to eliminate their effects.

We instantiate UniACE on 7 widely used benchmarks spanning 24 domains and evaluate 15 models in more than 400K rollouts consuming 5B tokens. Comparisons with the source implementations exhibit large bidirectional score changes and, in some cases, model-ranking reversals, showing that leaderboard conclusions can depend on the harness. Matched online and offline runs on retrieval-heavy tasks further show substantial sensitivity to accessible evidence and its representation, although the contrast is not a causal decomposition of environmental volatility. Under the shared UniACE configuration, effectiveness, efficiency, and failure profiles reveal task-dependent model behaviors hidden by task-success scores alone. We also migrate a safety benchmark to demonstrate support for evaluation dimensions beyond task completion.

Our contributions are threefold: (1) UniACE, a unified framework that represents benchmark-native tasks through a common instruction–tool–environment interface and evaluates LLMs using a shared, task-agnostic harness with isolated runtimes and optional fixed snapshots; (2) an evaluation protocol that preserves native success criteria while standardizing efficiency measurement and trace-based failure attribution; and (3) the migration of 7 benchmarks across 24 domains and a study of 15 models, 400K rollouts, and 5B tokens, revealing sensitivity to harness and environment

2 Related Work

LLM Agentic Capabilities and Benchmarks. LLM agents extend static text generation by combining language models with planning, memory, tool use, and feedback-driven interaction with external environments (Mialon et al. 2023; Xi et al. 2025; Wang et al. 2024; Yao et al. 2023). To evaluate these capabilities, existing agent benchmarks span broad-coverage suites (Liu et al. 2024; Ma et al. 2024) and domain-specific evaluations of software engineering (Jimenez et al. 2024), web interaction (Yao et al. 2022), function calling (Patil et al. 2025), and customer service (Yao et al. 2025). Beyond single-agent settings, evaluating multi-agent systems further requires assessing inter-agent communication, role specialization, and collaborative problem solving (Wu et al. 2023; Tang et al. 2024; Zhu et al. 2025b). However, these benchmarks are often released as benchmark-specific evaluation packages that bundle task-tailored agent

harnesses, tool interfaces, and execution environments. Such coupling can affect reported performance and complicate fair cross-benchmark comparisons (Kapoor et al. 2026; Zhu et al. 2026; Hui et al. 2026), motivating a model-centric evaluation setting with a shared harness and explicitly specified execution conditions.

Agent Evaluation Approaches. Recent work has begun to standardize different components of agent evaluation. HAL evaluates general-purpose and benchmark-specific scaffolds across multiple benchmarks, showing that scaffold choice can substantially affect measured performance (Kapoor et al. 2026). Harbor provides containerized infrastructure for executing and optimizing CLI-based agents (Harbor Framework Team 2026). General Agent Evaluation and AgentCompass introduce mediation that connect heterogeneous complete agents to multiple benchmarks, and report performance variation across agent implementations (Bandel et al. 2026; Chen et al. 2026a). However, their primary goal is not to compare LLMs under a fixed, task-agnostic harness shared across benchmarks. UniACE instead targets this model-centric setting by turning heterogeneous and implicit framework choices into an explicit, shared, and reproducible evaluation condition. Its instruction–tool–environment specification and isolated per-task runtimes instantiate this condition while preserving each benchmark’s native task definitions and success criteria.

3 UniACE Framework

As depicted in Figure 1, the **UniACE** consists of three stages, each described in the subsequent sections.

3.1 Benchmark Setup

To run heterogeneous agent benchmarks under a shared evaluation protocol, we introduce a standardized benchmark representation and a unified configuration system for specifying execution settings. This design enables new benchmarks to be integrated with minimal changes to the execution and evaluation pipeline.

Standardized Datasets. Unlike traditional LLM benchmark datasets that primarily consist of question–answer pairs (Chang et al. 2024), agent benchmarks must additionally specify the tools and environments required for agent execution. We therefore organize the dataset associated with each agent benchmark as a standardized triplet: $\mathcal{D} = \langle \mathcal{I}, \mathcal{T}, \mathcal{E} \rangle$, where $\mathcal{I}$, $\mathcal{T}$, and $\mathcal{E}$ denote the instruction, tool, and environment sets, respectively. Each task instance in $\mathcal{I}$ specifies an instruction together with the task-specific information required for execution and evaluation. The tool set $\mathcal{T}$ exposes standardized callable interfaces, while the environment set $\mathcal{E}$ contains the task-specific resources available during execution, typically represented as local files, interactive services, or references to external resources. For dynamic tasks, $\mathcal{E}$ may additionally include fixed snapshots for controlled offline evaluation. Specifications and examples of the standardized dataset representation appear in Appendix B.

Unified Configuration. To support controlled and reproducible evaluation, we decouple experimental specification




Figure 1: **Overview of the UniACE framework.** (1) **Benchmark Setup** standardizes benchmarks into instruction, tool, and environment triplets, driven by a configuration system for streamlined deployment; (2) **Agent Sandbox** instantiates a fixed agent harness to manage interactions within isolated environments; and (3) **Evaluation Protocol** unifies task-completion scoring, efficiency metrics, and failure analysis, while supporting additional evaluation dimensions.

from execution logic through a unified configuration system. An experiment is specified as $\mathcal{C} = (\mathcal{C}_{\text{sys}}, \mathcal{C}_{\text{agent}})$, where $\mathcal{C}_{\text{sys}}$ specifies benchmark-level and execution settings, while $\mathcal{C}_{\text{agent}}$ defines agent-level behavior and interaction structure. This separation allows models, benchmarks, and agent topologies to be varied under a shared execution protocol without modifying the core evaluation logic. Detailed schemas and examples are provided in Appendix C.

3.2 Agent Sandbox

The sandbox couples a unified, task-agnostic agent harness with an isolated runtime environment for each task.

Agent Instantiation. The unified harness implements a common agent architecture that standardizes LLM invocation, system prompt, tool invocation and error handling. For each task $i \in \mathcal{I}$, the framework instantiates the agent using the corresponding agent-level configuration $\mathcal{C}_{\text{agent}}$ and the required tools from $\mathcal{T}$. Task instructions and tool access remain benchmark-specific, while agent structures remain configurable and the core execution protocol is held fixed across benchmarks. Rather than eliminating harness effects, UniACE makes the shared harness an explicit and reproducible evaluation condition.

Environment Instantiation. For each task i , the corresponding environment resource $e_i \in \mathcal{E}$ is used to create an isolated runtime instance with initial state $E_0^{(i)}$. For tasks involving dynamic external resources, such as web search, the runtime instance can operate either online through live interaction or offline over fixed, pre-collected snapshots. The offline mode holds the accessible environment content fixed, reducing external volatility and enabling reproducible analysis (Chen et al. 2026b; Zhou et al. 2024).

At step t , an agent action a_t updates the runtime state according to $E_{t+1}^{(i)} = \delta(E_t^{(i)}, a_t)$, where δ denotes the environment transition function. Because all state changes are confined to the task-specific runtime instance, the underlying environment resource e_i remains unchanged across executions. The terminal runtime state is retained for evaluation as the result environment state, denoted by $E_{\text{res}}^{(i)} := E_T^{(i)}$.

3.3 Evaluation Protocol

After agent execution, the framework evaluates each run using the agent output, terminal environment state, and execution logs. Our unified evaluation protocol covers three core dimensions: task completion, resource efficiency, and failure attribution. Details are provided in Appendix D.

Task Completion. We preserve the original task-success criteria of each benchmark within a unified scoring procedure. For each task i , we compute an output-level score S_i^{out} using the rule-based evaluator or LLM-based judge specified by the original benchmark. For tasks involving environment state changes, we additionally compute an environment-level score S_i^{env} by comparing the agent-produced terminal state $E_{\text{res}}^{(i)}$ with the ground-truth terminal state $E_{\text{gt}}^{(i)}$, obtained by replaying the benchmark-provided reference trajectory from the same initial state (Yao et al. 2025; Liu et al. 2024). The per-task Task Completion Score combines the applicable signals according to the benchmark’s evaluation requirements, and the overall benchmark score $\overline{\text{TCS}}$ is computed by averaging across all tasks.

Efficiency. For each run, we extract four measures of operational usage from the execution logs: interaction steps, input tokens, output tokens, and elapsed time. Token counts are obtained from the usage metadata returned by each model’s serving backend under its native tokenizer, while steps denote complete iterations of the shared agent loop. We average each measure over tasks within each benchmark domain to compare model-specific operational usage under matched harness and tool conditions.

Failure Analysis. For each unsuccessful run, we attribute the failure using a unified taxonomy that covers decision-level and execution-level errors. The taxonomy consolidates categories from existing agent benchmarks (Yao et al. 2025; Barres et al. 2025; Patil et al. 2025; Liu et al. 2024) with recurring failure patterns observed in our execution traces. Failure analysis is based on the agent output and execution logs, with LLM-based classifiers used to support large-scale analysis. The complete taxonomy is provided in Appendix D.3.

Customized Metrics. Beyond these core dimensions, the framework supports benchmark-specific and user-defined evaluation functions. We retain comprehensive execution records, including tool trajectories, terminal environment states, execution logs, and runtime metadata. These records allow additional evaluation dimensions, such as safety, to be assessed after execution without rerunning the agents.

4 Experiment

4.1 Experiment Setting

Benchmarks. We evaluate our framework on seven agent benchmarks: AgentBench (Liu et al. 2024), BFCL (Patil et al. 2025), τ -bench (Yao et al. 2025), τ^2 -bench (Barres et al. 2025), BrowseComp (Wei et al. 2025), MultiAgentBench (Zhu et al. 2025a), and Agent-SafetyBench (Zhang et al. 2025). All benchmarks are represented as standardized instruction–tool–environment triplets while preserving their original task semantics and evaluation criteria; for benchmarks involving dynamic external resources, an optional offline mode based on fixed snapshots is provided for reproducible evaluation. Details are in Appendix H.

Models and Settings. For each benchmark we evaluate two of its reference models, plus four advanced agentic

models—Gemini-3-Flash (Google DeepMind 2025), GPT-5-mini (Singh et al. 2025), Qwen3-235B-A22B (Yang et al. 2025), and DeepSeek-V3.2 (DeepSeek-AI et al. 2025). Gemini-3-Flash serves as the judge when LLM-based evaluation is required; LLM–human agreement is reported in Appendix F. All models are queried through OpenAI-compatible API interfaces or served locally with vLLM (Kwon et al. 2023), with temperature set to 0 to reduce decoding variability. Tool calls are executed sequentially, and each agent is allowed a maximum of 20 steps.

4.2 Comparison with Original Benchmarks

Table 1 compares benchmark-reported scores (Orig.) obtained under their original frameworks with results from our UniACE framework (Ours), which incorporates efficiency metrics absent from prior evaluations. Three findings challenge common readings of existing agent leaderboards.

Finding 1: Scores shift bidirectionally under the shared UniACE configuration. On AgentBench Database, where we preserve the original tool functionality and evaluation rule, GPT-3.5-Turbo improves by 26.6 points. Execution traces suggest that this gain largely results from a reduction in parsing failures caused by the original text-based action format through our structured tool-call interface. Conversely, DeepSeek-V3.2 drops by 23.8, 35.5, and 11.1 points across the three τ^2 -bench domains, while Llama-3.1-70B decreases by 33.7 points on MAB Bargaining when benchmark-specific orchestration, prompts, and tool-call formats are replaced by a unified task-agnostic scaffold. This effect is particularly relevant to legacy models without tool-calling post-training, such as Llama-2-70B, which rely on prompt-based JSON generation and are therefore more susceptible to formatting violations that cascade into task failure. The bidirectional shifts show that applying a shared UniACE condition does not systematically raise or lower benchmark scores.

Finding 2: Framework standardization can alter relative model rankings. On AgentBench Database, the gap between GPT-3.5-Turbo and Llama-2-70B narrows from 23.7 to 7.8 points under our unified framework. More notably, on τ -bench Retail, the original ordering GPT-4o(61.2%) > GPT-3.5-Turbo(20.0%) reverses to GPT-3.5-Turbo(55.7%) > GPT-4o(28.7%). Qualitative trajectory inspection suggests that GPT-3.5-Turbo more often produces concise and directly executable tool calls, whereas GPT-4o’s more verbose outputs can delay tool execution or introduce formatting mismatches. Framework choice affects not only individual scores but also the model ordering inferred from benchmark leaderboards.

Finding 3: Efficiency distinguishes models with similar performance. Similar TCS values can mask substantial differences in recorded interaction steps, model-reported token usage, and observed elapsed time. On AgentBench Database, GPT-3.5-Turbo and Llama-2-70B achieve 63.3% and 55.5% TCS, respectively, yet Llama-2-70B uses $3.2\times$ the steps, $6.4\times$ the input tokens, and $2.5\times$ the execution time. On AgentBench Web Shopping, their scores differ by fewer than two points (56.5% vs. 54.9%), while Llama-2-

Benchmark	Domain	Orig.		Ours				Orig.		Ours			
		TCS [↑] (%)	TCS [↑] (%)	Stp [↓] (#)	Tk.In [↓] (k)	Tk.Out [↓] (k)	Time [↓] (s)	TCS [↑] (%)	TCS [↑] (%)	Stp [↓] (#)	Tk.In [↓] (k)	Tk.Out [↓] (k)	Time [↓] (s)
AgentBench		GPT-3.5-Turbo						Llama-2-70B					
	Database	36.7	63.3	2.5	2.7	0.1	5.4	13.0	55.5	7.9	17.3	0.8	13.5
	Knowledge Graph	25.9	58.0	8.3	25.4	0.3	14.7	8.0	2.0	13.9	64.5	1.5	34.6
	Digital Card Game	33.7	26.9	27.0	182.3	0.7	42.4	21.3	0.6	5.1	13.7	0.3	7.9
	Lateral Thinking Puzzle	10.5	13.5	14.5	29.8	0.5	60.3	0.0	7.8	16.7	51.8	1.7	60.6
	Web Shopping	64.1	56.5	4.2	8.5	0.2	5.9	5.6	54.9	21.0	131.8	1.5	47.5
	Web Browsing	20.0	24.3	9.7	44.6	0.2	24.8	19.0	0.0	10.5	33.5	1.4	27.7
BFCL		Qwen3-30B-A3B						Gemini-2.5-Flash					
	Web Search	22.5	59.0	4.3	16.9	0.3	1.7	59.0	78.5	6.5	36.8	2.0	40.6
	Memory	17.6	47.3	3.7	31.3	0.1	1.0	41.3	46.2	2.9	10.2	0.4	8.4
	Multi Turn	30.0	38.6	5.0	192.0	0.6	4.1	36.3	61.4	6.0	180.0	2.4	53.7
	Single Turn(Non-live)	85.8	69.7	2.6	84.9	0.2	2.0	85.0	79.3	3.0	79.0	0.7	15.5
	Single Turn(Live)	77.9	80.6	4.0	21.6	0.3	1.5	74.4	77.6	3.0	15.9	0.6	11.3
	Hallucination(Relevance)	81.3	37.5	3.2	27.1	0.2	1.3	75.0	81.3	1.9	6.1	0.5	8.2
	Hallucination(Irrelevance)	79.9	79.8	1.2	1.7	0.08	2.6	93.7	77.7	1.6	30.8	0.4	9.5
τ -bench		GPT-4o						GPT-3.5-Turbo					
	Airline	35.2	44.0	9.3	52.6	0.9	32.8	10.8	38.0	7.9	38.5	0.8	29.1
	Retail	61.2	28.7	9.5	66.0	0.8	27.3	20.0	55.7	8.5	53.4	0.8	24.5
τ^2 -bench		DeepSeek-V3.2						GPT-4.1-mini					
	Airline	63.8	40.0	24.2	166.2	3.5	275.0	48.7	26.0	7.3	33.9	0.8	32.2
	Retail	81.1	45.6	21.7	167.5	3.6	244.5	61.4	40.4	8.3	48.9	0.8	29.1
	Telecom	96.2	85.1	34.6	246.9	2.8	175.2	48.9	69.3	18.9	99.4	1.2	93.7
BrowseComp	-	DeepSeek-V3.1						Qwen3-235B-A22B					
		2.6	6.4	4.8	238.6	0.4	153.3	0.5	3.8	5.5	268.4	0.2	51.3
MultiAgentBench		Llama-3.1-70B						GPT-4o-mini					
	Research	80.8	33.3	9.3	51.7	2.3	290.7	84.1	68.3	10.1	184.4	2.7	398.1
	Database	53.0	57.0	17.2	28.9	2.2	56.8	45.0	52.0	12.7	19.0	1.9	43.2
	Coding	62.1	52.1	12.0	38.6	2.4	343.1	65.1	46.3	12.1	37.7	2.2	285.4
	Bargaining	72.1	38.4	11.7	42.2	1.7	216.6	74.5	57.7	21.2	110.4	3.5	308.5

Table 1: TCS performance comparison of our UniACE framework versus original implementations. Our framework also provides comprehensive efficiency metrics across diverse agent benchmarks, using the respective LLMs in their original evaluations. Efficiency metrics are reported in thousands (k) for tokens and seconds (s) for time.

70B consumes $5\times$ the steps, $15\times$ the input tokens, and $8\times$ the execution time. Thus, similar task-completion scores can correspond to substantially different operational costs.

4.3 Impact of Environmental Volatility

Benchmarks relying on dynamic environments conflate agentic capability with both environmental reliability and framework-level choices. To examine these sources of variation under matched settings, we compare two retrieval benchmarks, *BFCL Web Search* and *MultiAgentBench (MAB) Research*, under three settings: the original implementation (**Orig.**), UniACE framework with live external access (**Online**), and UniACE framework with pre-curated local snapshots (**Offline**, built by crawling the officially provided reference sources and manually verifying the crawled content; see Appendix H). Results appear in Table 2.

Finding 1: Online–offline differences reveal sensitivity to accessible evidence and its representation. Offline TCS is higher in all four comparisons, with gains of +34.5 for Qwen3-30B-A3B on BFCL and +37.7 for GPT-4o-mini

on MAB. Trajectory analyses illustrate three mechanisms: reference pages becoming unavailable due to site updates, anti-crawling mechanisms returning empty or garbled content, and retrieval tools producing ad- and boilerplate-heavy outputs that consume the token budget. However, snapshot-based environments also change the accessible corpus and evidence representation, so the observed gaps should not be interpreted as causal estimates of environmental volatility. The case studies in Appendix E further show that apparent “agentic failures” on live-web benchmarks arise from environment or tooling conditions rather than model capability.

Finding 2: Source-implementation gaps persist under live retrieval. Comparing Orig. with Online provides a comparison of framework-level choices under the same live retrieval stack. The gaps remain large and directionally inconsistent: Qwen3-30B-A3B on BFCL rises from 22.5 to 24.5, while Llama-3.1-70B on MAB drops from 80.8 to 26.3. Reported numbers on retrieval-heavy benchmarks thus depend not only on the environment but also on framework-level choices that prior evaluations rarely control for. The matched

Bench.	Model	Orig.	Online					Offline				
		TCS (%)↑	TCS (%)↑	Stp. (#)↓	Tok. In (k)↓	Tok. Out (k)↓	Time (s)↓	TCS (%)↑	Stp. (#)↓	Tok. In (k)↓	Tok. Out (k)↓	Time (s)↓
BFCL	Qwen3-30B-A3B	22.5	24.5	4.3	126.9	0.3	42.8	59.0	4.3	16.9	0.3	1.7
	Gemini-2.5-Flash	59.0	71.0	6.5	66.2	1.2	82.9	78.5	6.5	36.8	2.0	40.6
MAB	Llama-3.1-70B	80.8	26.3	13.2	141.5	1.9	729.1	33.3	9.3	51.7	2.3	290.7
	GPT-4o-mini	84.1	30.6	9.7	181.3	1.0	376.6	68.3	10.1	184.4	2.7	398.1

Table 2: Comparison of task performance and execution efficiency under the original, online, and offline evaluation settings.

BFCL case study in Appendix E.1 illustrates how memory representation and retry handling can alter termination behavior under an otherwise matched live retrieval setting.

4.4 Agentic Capabilities of Advanced Models

We apply UniACE to four advanced models to characterize their agentic capability profiles under the shared UniACE scaffold and explicitly specified execution conditions. Table 3 reports results across 6 benchmarks spanning 23 domains. We summarize the key findings below.

Finding 1: Relative model strengths vary substantially across task types. Gemini-3-Flash leads on structured short-horizon tasks (AgentBench DB 74.3%, BFCL Single-Turn 83.1%) but collapses on complex service workflows (τ^2 -bench Telecom 35.1%, where DeepSeek-V3.2 reaches 85.1%). GPT-5-mini shows the opposite bias: weaker on non-live single-shot function calling (Single-Turn Non-live 54.8% vs. Gemini-3-Flash 83.1% and Qwen3 81.4%) but strongest on stateful dialogue (τ -bench Retail 59.1%). These results show that model strengths and rankings vary substantially by task type under the shared evaluation configuration.

Finding 2: Efficiency reveals execution differences invisible to TCS. On AgentBench LTP, Gemini-3-Flash and GPT-5-mini achieve comparable TCS (32.3% vs. 27.3%), yet Gemini consumes $34\times$ higher input-token usage (1,539.6k vs. 45.4k). Inspection of the execution traces shows that Gemini repeatedly revisits prior reasoning states and reformulates previously attempted actions, producing runaway reasoning loops in some cases that are not observed in the GPT-5-mini runs. Conversely, Qwen3-235B reaches comparable TCS to GPT-5-mini on Web Shopping (40.6% vs. 40.4%) using $7.0\times$ fewer input tokens (13.9k vs. 97.7k). These cases show that comparable TCS can be associated with markedly different efficiency.

Finding 3: Open- and closed-weight models exhibit domain-dependent strengths under a unified scaffold. Under our shared scaffold, closed-weight models do not consistently outperform open-weight models across domains. DeepSeek-V3.2 leads on τ^2 -bench Telecom (85.1%, vs. GPT-5-mini’s 79.9% and Gemini-3-Flash’s 35.1%) and BFCL Hallucination-Irrelevance (74.5%, vs. 73.0% and 67.0%, respectively). On AgentBench Database, it remains within 3 points of GPT-5-mini (74.0%) and Gemini-3-Flash (74.3%), achieving 71.3%. Conversely, closed-weight models retain advantages in several domains, such as stateful service dialogue on τ -bench Retail.




Figure 2: Distribution of failure categories across models.

4.5 Failure Analysis

Figure 2 reveals failure categories across models, grouped into *decision-level* (Parsing Failure, Tool Invocation Error, Reasoning Deficit) and *execution-level* (Iteration Limit Exceeded, Context Overflow, Timeout); per-domain breakdowns are provided in Appendix G. (1) **Reasoning Deficit is the most frequently assigned category for most models.** *Reasoning Deficit* accounts for the largest failure share on Gemini-3-Flash (52.1%), GPT-5-mini (49.2%), and Qwen3-235B (71.6%), making it the most frequently assigned failure category for these models. DeepSeek-V3.2 is the exception, with *Parsing Failure* (37.8%) edging out *Reasoning Deficit* (31.8%). (2) **Secondary decision-level failures expose distinct weaknesses.** Beyond reasoning, models fail in characteristic ways: Gemini-3-Flash and DeepSeek-V3.2 are prone to format brittleness (*Parsing Failure*: 16.9% and 37.8%); and *Tool Invocation Error* remains non-trivial on GPT-5-mini (12.9%) and Qwen3-235B (13.6%), showing that native function-calling does not eliminate malformed or non-existent tool calls. (3) **Execution-level failures concentrate on step budget.** GPT-5-mini and DeepSeek-V3.2 frequently

Benchmark	Domain	Gemini-3-Flash					GPT-5-mini					Qwen3-235B-A22B					DeepSeek-V3.2				
		TCS [↑]	Stp [↓]	Tok [↓]		Time [↓]	TCS [↑]	Stp [↓]	Tok [↓]		Time [↓]	TCS [↑]	Stp [↓]	Tok [↓]		Time [↓]	TCS [↑]	Stp [↓]	Tok [↓]		Time [↓]
				In	Out				In	Out				In	Out				In	Out	
				(k)	(k)				(k)	(k)				(k)	(k)				(k)	(k)	
		(%)	(#)	(k)	(k)	(s)	(%)	(#)	(k)	(k)	(s)	(%)	(#)	(k)	(k)	(s)	(%)	(#)	(k)	(k)	(s)
AgentBench	DB	74.3	4.5	14.9	5.3	60.0	74.0	4.3	6.5	2.3	30.8	53.7	2.3	3.0	0.1	21.5	71.3	7.5	15.9	0.7	30.2
	KG	44.0	9.2	52.9	1.1	77.6	72.7	9.3	29.6	7.3	89.4	31.3	11.0	43.7	0.5	67.2	34.0	20.0	84.9	1.4	69.9
	DCG	62.2	20.0	126.8	13.7	112.3	73.6	17.7	94.0	11.8	306.0	51.2	18.1	116.2	0.6	7.8	29.1	20.3	127.0	0.7	76.8
	LTP	32.3	17.4	1539.6	295.1	1974.0	27.3	19.5	45.4	21.7	497.7	21.6	12.0	26.8	0.5	63.8	12.6	20.4	51.8	1.0	74.8
	WS	52.0	12.6	77.0	5.7	79.9	40.4	16.6	97.7	7.9	126.2	40.6	4.8	13.9	0.2	8.9	32.0	16.4	5.5	0.9	35.7
	WB	26.6	10.6	76.3	2.9	210.7	36.2	14.5	80.1	4.6	82.1	10.7	5.9	25.3	0.1	75.0	4.0	19.9	93.5	0.9	149.4
BFCL	Web Search	86.5	10.2	75.4	15.5	90.2	83.5	11.3	65.6	6.5	116.8	68.0	4.7	17.5	0.3	3.8	80.0	7.1	31.5	0.4	8.5
	Memory	63.4	5.9	56.5	8.1	155.3	44.7	15.3	78.5	11.0	139.0	41.9	3.4	10.9	0.1	6.7	59.1	8.8	41.6	0.6	24.7
	Multi Turn	57.5	9.4	462.0	22.0	331.8	27.3	19.2	801.6	44.0	1025.8	59.4	5.2	190.6	0.5	36.9	26.3	15.3	680.2	1.5	502.3
	Single Turn(Non-live)	83.1	2.8	83.9	1.9	87.3	54.8	4.3	33.2	5.1	308.8	81.4	2.4	70.4	0.1	12.9	74.8	3.4	115.2	0.4	33.3
	Single Turn(Live)	83.0	3.3	20.8	2.2	77.9	71.8	6.7	28.8	6.0	167.4	77.6	2.8	12.7	0.2	20.8	81.4	3.7	20.9	0.4	42.9
	Hallucination(Relevance)	75.0	2.8	15.9	2.0	131.0	43.8	8.6	37.6	7.8	231.7	37.5	2.1	10.2	0.2	29.3	75.0	4.1	27.5	0.6	38.9
τ -bench	Hallucination(Irrelevance)	67.0	2.2	58.6	2.3	37.0	73.0	3.2	10.2	3.9	198.6	62.7	1.4	23.7	0.1	6.5	74.5	1.7	28.1	0.3	9.3
	Airline	58.0	9.0	77.6	6.8	233.0	46.0	16.0	112.2	32.1	1022.7	52.0	11.2	86.0	1.4	54.0	38.0	18.8	128.3	3.1	236.9
τ^2 -bench	Retail	24.4	11.7	102.4	6.6	340.6	59.1	17.0	143.9	29.5	1003.0	31.3	10.8	90.2	1.2	51.0	41.7	20.4	155.2	3.5	238.3
	Airline	42.0	8.5	72.0	5.9	159.2	30.0	19.7	146.0	45.9	1352.8	26.0	9.9	68.2	1.2	51.6	40.0	24.2	166.2	3.5	275.0
τ^2 -bench	Retail	31.6	10.8	83.8	3.8	303.9	59.6	20.4	193.2	36.6	1378.0	33.3	9.8	77.0	1.1	43.6	45.6	21.7	167.5	3.6	244.5
	Telecom	35.1	23.2	197.9	6.5	404.9	79.9	32.9	296.4	41.4	1479.3	67.5	24.8	180.2	1.8	200.4	85.1	34.6	246.9	2.8	175.2
BrowseComp -		10.3	7.0	562.1	66.9	813.6	16.7	17.6	482.0	12.6	291.2	3.8	5.5	268.4	0.2	51.3	12.9	19.7	340.3	1.7	137.0
Multi-AgentBench	Research	89.7	52.8	2310.1	126.3	3091.7	88.0	14.4	445.6	13.5	297.4	85.0	27.2	684.7	6.9	169.8	81.2	24.0	322.2	8.0	289.3
	Database	80.7	19.9	88.7	62.0	585.3	99.3	18.3	46.2	30.2	474.6	84.0	16.7	46.7	3.7	83.5	88.7	15.7	56.1	6.2	327.4
	Coding	46.4	28.2	203.6	30.6	1191.3	50.7	12.0	67.1	33.0	10425.6	28.2	25.5	161.5	20.9	1253.9	33.5	22.8	117.9	9.0	639.8
	Bargaining	91.0	15.3	66.8	16.0	205.6	79.4	15.4	62.1	21.7	2221.3	70.3	15.0	61.5	3.9	529.3	79.0	24.9	138.0	5.5	599.9

Table 3: Evaluation of advanced LLMs across diverse agent benchmarks. We report Task Completion Score (TCS) for effectiveness, alongside efficiency metrics including average steps (Stp), token consumption (Tok. In/Out), and execution time.




Figure 3: Safety scores (% , higher is safer) on Agent-SafetyBench under the original benchmark implementation and our UniACE framework.

exhaust the iteration limit (32.4% and 24.5%), reflecting weak termination on long-horizon tasks, whereas Timeout and Context Overflow remain below 5% for all models and are comparatively rare under the evaluated budgets.

4.6 Safety Domain Extension

To demonstrate UniACE’s extensibility beyond capability evaluation, we integrate AgentSafetyBench while preserving its tasks and scoring protocol (Appendix H.6). Following the

original benchmark, the scorer classifies each interaction as safe or unsafe, and the Safety Score is defined as the percentage of interactions classified as safe, with higher values indicating safer behavior. As shown in Figure 3, the scores decrease from 31.2 to 21.0 for Llama-3.1-70B and from 37.3 to 22.9 for Qwen2.5-72B under our framework. Qualitative inspection suggests that the standardized tool-call interface allows more actions to be executed, exposing unsafe behaviors that may otherwise be obscured by parsing failures or incomplete executions. These results indicate that safety can also be sensitive to the surrounding agent framework, even when the original evaluation protocol is preserved.

5 Conclusion

We presented **UniACE**, a unified framework for model-centric evaluation of LLM agentic capabilities under a common execution condition. UniACE represents benchmarks as instruction–tool–environment triplets, executes agents through a shared harness in isolated runtimes, and standardizes efficiency measurement and failure attribution while preserving native success criteria. It also supports offline evaluation of dynamic resources and a minimal specification for integrating new benchmarks. Across seven benchmarks, 24 domains, 15 models, 400K rollouts, and 5B tokens, comparisons with source implementations reveal bidirectional score

shifts and model-ranking reversals, while matched online–offline runs expose sensitivity to accessible evidence and its representation. Rather than eliminating framework effects, UniACE turns heterogeneous and implicit framework choices into ashaed, and reproducible evaluation condition.

References

- Bandel, E.; Yehudai, A.; Eden, L.; Sagron, Y.; Perlitz, Y.; Venezian, E.; Razinkov, N.; Ergas, N.; Ifergan, S. S.; Shlov, S.; Jacovi, M.; Choshen, L.; Ein-Dor, L.; Katz, Y.; and Shmueli-Scheuer, M. 2026. General Agent Evaluation. arXiv:2602.22953.
- Barres, V.; Dong, H.; Ray, S.; Si, X.; and Narasimhan, K. 2025. τ^2 -Bench: Evaluating Conversational Agents in a Dual-Control Environment. arXiv:2506.07982.
- Chang, Y.; Wang, X.; Wang, J.; Wu, Y.; Yang, L.; Zhu, K.; Chen, H.; Yi, X.; Wang, C.; Wang, Y.; Ye, W.; Zhang, Y.; Chang, Y.; Yu, P. S.; Yang, Q.; and Xie, X. 2024. A Survey on Evaluation of Large Language Models. *ACM Trans. Intell. Syst. Technol.*, 15(3).
- Chen, K.; Ding, Z.; Ge, J.; Jiang, S.; Li, M.; Li, Q.; Li, Z.; Li, Z.; Liang, T.; Liu, S.; Ma, Z.; Shang, Z.; Tian, W.; Wang, Z.; Wu, L.; Wu, Z.; Xu, J.; Yang, B.; Yuan, D.; Zhang, Q.; Zhang, S.; Zhou, P.; and Zhu, D. 2026a. AgentCompass: A Unified Evaluation Infrastructure for Agent Capabilities. arXiv:2607.13705.
- Chen, Z.; Ma, X.; Zhuang, S.; Nie, P.; Zou, K.; Sharif-moghaddam, S.; Liu, A.; Green, J.; Patel, K.; Meng, R.; Su, M.; Li, Y.; Hong, H.; Shi, X.; Liu, X.; Oyarhoseini, H.; Thakur, N.; Zhang, C.; Gao, L.; Chen, W.; and Lin, J. 2026b. BrowseComp-Plus: A Fair and Disentangled Evaluation Benchmark for Deep Search Agents. In Liakata, M.; Moreira, V. P.; Zhang, J.; and Jurgens, D., eds., *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 22349–22370. San Diego, California, United States: Association for Computational Linguistics. ISBN 979-8-89176-390-6.
- Cohen, J. 1960. A coefficient of agreement for nominal scales. *Educational and psychological measurement*, 20(1): 37–46.
- DeepSeek-AI; Liu, A.; Mei, A.; Lin, B.; Xue, B.; et al. 2025. DeepSeek-V3.2: Pushing the Frontier of Open Large Language Models. arXiv:2512.02556.
- Google DeepMind. 2025. Gemini 3 Flash Model Card.
- Harbor Framework Team. 2026. Harbor: A framework for evaluating and optimizing agents and models in container environments.
- Hui, T.; Xu, H.; Zhu, P.; Xin, H.; Zhan, K.; Su, S.; Liu, C.; and Miao, N. 2026. STT-Arena: A More Realistic Environment for Tool-Using with Spatio-Temporal Dynamics. arXiv:2605.18548.
- Jimenez, C. E.; Yang, J.; Wettig, A.; Yao, S.; Pei, K.; Press, O.; and Narasimhan, K. R. 2024. SWE-bench: Can Language Models Resolve Real-world Github Issues? In *The Twelfth International Conference on Learning Representations*.
- Kapoor, S.; Stroebel, B.; Kirgis, P.; Nadgir, N.; Siegel, Z. S.; Wei, B.; Xue, T.; Chen, Z.; Chen, F.; Utpala, S.; Ndzomga, F.; Oruganty, D.; Luskin, S.; Liu, K.; Yu, B.; Arora, A.; Hahm, D.; Trivedi, H.; Sun, H.; Lee, J.; Jin, T.; Mai, Y.; Zhou, Y.; Zhu, Y.; Bommasani, R.; Kang, D.; Song, D.; Hender-son, P.; Su, Y.; Liang, P.; and Narayanan, A. 2026. Holistic Agent Leaderboard: The Missing Infrastructure for AI Agent Evaluation. In *The Fourteenth International Conference on Learning Representations*.
- Kwon, W.; Li, Z.; Zhuang, S.; Sheng, Y.; Zheng, L.; Yu, C. H.; Gonzalez, J. E.; Zhang, H.; and Stoica, I. 2023. Efficient Memory Management for Large Language Model Serving with PagedAttention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*.
- Landis, J. R.; and Koch, G. G. 1977. The measurement of observer agreement for categorical data. *biometrics*, 159–174.
- Liu, X.; Yu, H.; Zhang, H.; Xu, Y.; Lei, X.; Lai, H.; Gu, Y.; Ding, H.; Men, K.; Yang, K.; Zhang, S.; Deng, X.; Zeng, A.; Du, Z.; Zhang, C.; Shen, S.; Zhang, T.; Su, Y.; Sun, H.; Huang, M.; Dong, Y.; and Tang, J. 2024. AgentBench: Evaluating LLMs as Agents. In *The Twelfth International Conference on Learning Representations*.
- Ma, C.; Zhang, J.; Zhu, Z.; Yang, C.; Yang, Y.; Jin, Y.; Lan, Z.; Kong, L.; and He, J. 2024. AgentBoard: An Analytical Evaluation Board of Multi-turn LLM Agents. arXiv:2401.13178.
- Mialon, G.; Dessi, R.; Lomeli, M.; Nalmpantis, C.; Pasunuru, R.; Raileanu, R.; Roziere, B.; Schick, T.; Dwivedi-Yu, J.; Celikyilmaz, A.; Grave, E.; LeCun, Y.; and Scialom, T. 2023. Augmented Language Models: a Survey. *Transactions on Machine Learning Research*. Survey Certification.
- Mialon, G.; Fourrier, C.; Wolf, T.; LeCun, Y.; and Scialom, T. 2024. GAIA: a benchmark for General AI Assistants. In *The Twelfth International Conference on Learning Representations*.
- Pati, A. K. 2025. Agentic AI: A Comprehensive Survey of Technologies, Applications, and Societal Implications. *IEEE Access*, 13: 151824–151837.
- Patil, S. G.; Mao, H.; Yan, F.; Ji, C. C.-J.; Suresh, V.; Stoica, I.; and Gonzalez, J. E. 2025. The Berkeley Function Calling Leaderboard (BFCL): From Tool Use to Agentic Evaluation of Large Language Models. In *Forty-second International Conference on Machine Learning*.
- Qin, Y.; Liang, S.; Ye, Y.; Zhu, K.; Yan, L.; Lu, Y.; Lin, Y.; Cong, X.; Tang, X.; Qian, B.; Zhao, S.; Tian, R.; Xie, R.; Zhou, J.; Gerstein, M.; Li, D.; Liu, Z.; and Sun, M. 2023. ToolLLM: Facilitating Large Language Models to Master 16000+ Real-world APIs. arXiv:2307.16789.
- Roucher, A.; del Moral, A. V.; Wolf, T.; von Werra, L.; and Kaunismäki, E. 2025. ‘smolagents’: a smol library to build great agentic systems. <https://github.com/huggingface/smolagents>.
- Singh, A.; Fry, A.; Perelman, A.; Tart, A.; Ganesh, A.; et al. 2025. OpenAI GPT-5 System Card. arXiv:2601.03267.
- Tang, X.; Zou, A.; Zhang, Z.; Li, Z.; Zhao, Y.; Zhang, X.; Co-han, A.; and Gerstein, M. 2024. MedAgents: Large Language

- Models as Collaborators for Zero-shot Medical Reasoning. arXiv:2311.10537.
- Team, T. T.-B. 2025. Terminal-Bench: A Benchmark for AI Agents in Terminal Environments.
- Wang, L.; Ma, C.; Feng, X.; Zhang, Z.; Yang, H.; Zhang, J.; Chen, Z.; Tang, J.; Chen, X.; Lin, Y.; et al. 2024. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6): 186345.
- Wei, J.; Sun, Z.; Papay, S.; McKinney, S.; Han, J.; Fulford, I.; Chung, H. W.; Passos, A. T.; Fedus, W.; and Glaese, A. 2025. BrowseComp: A Simple Yet Challenging Benchmark for Browsing Agents. arXiv:2504.12516.
- Wolf, T.; Debut, L.; Sanh, V.; Chaumond, J.; Delangue, C.; Moi, A.; Cistac, P.; Rault, T.; Louf, R.; Funtowicz, M.; Davison, J.; Shleifer, S.; von Platen, P.; Ma, C.; Jernite, Y.; Plu, J.; Xu, C.; Scao, T. L.; Gugger, S.; Drame, M.; Lhoest, Q.; and Rush, A. M. 2020. Transformers: State-of-the-Art Natural Language Processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, 38–45. Online: Association for Computational Linguistics.
- Wu, Q.; Bansal, G.; Zhang, J.; Wu, Y.; Li, B.; Zhu, E.; Jiang, L.; Zhang, X.; Zhang, S.; Liu, J.; Awadallah, A. H.; White, R. W.; Burger, D.; and Wang, C. 2023. AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversation. arXiv:2308.08155.
- Xi, Z.; Chen, W.; Guo, X.; He, W.; Ding, Y.; Hong, B.; Zhang, M.; Wang, J.; Jin, S.; Zhou, E.; et al. 2025. The rise and potential of large language model based agents: A survey. *Science China Information Sciences*, 68(2): 121101.
- Yang, A.; Li, A.; Yang, B.; Zhang, B.; Hui, B.; Zheng, B.; Yu, B.; Gao, C.; Huang, C.; Lv, C.; Zheng, C.; Liu, D.; Zhou, F.; Huang, F.; Hu, F.; Ge, H.; Wei, H.; Lin, H.; Tang, J.; Yang, J.; Tu, J.; Zhang, J.; Yang, J.; Yang, J.; Zhou, J.; Zhou, J.; Lin, J.; Dang, K.; Bao, K.; Yang, K.; Yu, L.; Deng, L.; Li, M.; Xue, M.; Li, M.; Zhang, P.; Wang, P.; Zhu, Q.; Men, R.; Gao, R.; Liu, S.; Luo, S.; Li, T.; Tang, T.; Yin, W.; Ren, X.; Wang, X.; Zhang, X.; Ren, X.; Fan, Y.; Su, Y.; Zhang, Y.; Zhang, Y.; Wan, Y.; Liu, Y.; Wang, Z.; Cui, Z.; Zhang, Z.; Zhou, Z.; and Qiu, Z. 2025. Qwen3 Technical Report. arXiv:2505.09388.
- Yao, S.; Chen, H.; Yang, J.; and Narasimhan, K. R. 2022. WebShop: Towards Scalable Real-World Web Interaction with Grounded Language Agents. In Oh, A. H.; Agarwal, A.; Belgrave, D.; and Cho, K., eds., *Advances in Neural Information Processing Systems*.
- Yao, S.; Shinn, N.; Razavi, P.; and Narasimhan, K. R. 2025. τ -bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains. In *The Thirteenth International Conference on Learning Representations*.
- Yao, S.; Zhao, J.; Yu, D.; Du, N.; Shafran, I.; Narasimhan, K. R.; and Cao, Y. 2023. ReAct: Synergizing Reasoning and Acting in Language Models. In *The Eleventh International Conference on Learning Representations*.
- Yehudai, A.; Eden, L.; Li, A.; Uziel, G.; Zhao, Y.; Bar-Haim, R.; Cohan, A.; and Shmueli-Scheuer, M. 2026. A Survey on Evaluation of LLM-based Agents. In Liakata, M.; Moreira, V. P.; Zhang, J.; and Jurgens, D., eds., *Findings of the Association for Computational Linguistics: ACL 2026*, 26690–26714. San Diego, California, United States: Association for Computational Linguistics. ISBN 979-8-89176-395-1.
- Zhang, Z.; Cui, S.; Lu, Y.; Zhou, J.; Yang, J.; Wang, H.; and Huang, M. 2025. Agent-SafetyBench: Evaluating the Safety of LLM Agents. arXiv:2412.14470.
- Zhou, S.; Xu, F. F.; Zhu, H.; Zhou, X.; Lo, R.; Sridhar, A.; Cheng, X.; Ou, T.; Bisk, Y.; Fried, D.; Alon, U.; and Neubig, G. 2024. WebArena: A Realistic Web Environment for Building Autonomous Agents. In *The Twelfth International Conference on Learning Representations*.
- Zhu, K.; Du, H.; Hong, Z.; Yang, X.; Guo, S.; Wang, Z.; Wang, Z.; Qian, C.; Tang, R.; Ji, H.; and You, J. 2025a. Multi-AgentBench: Evaluating the Collaboration and Competition of LLM agents. In Che, W.; Nabende, J.; Shutova, E.; and Pilehvar, M. T., eds., *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 8580–8622. Vienna, Austria: Association for Computational Linguistics. ISBN 979-8-89176-251-0.
- Zhu, K.; Du, H.; Hong, Z.; Yang, X.; Guo, S.; Wang, Z.; Wang, Z.; Qian, C.; Tang, X.; Ji, H.; and You, J. 2025b. MultiAgentBench: Evaluating the Collaboration and Competition of LLM agents. arXiv:2503.01935.
- Zhu, P.; Sun, L.; Yu, P. S.; and Su, S. 2026. The Necessity of a Unified Framework for LLM-Based Agent Evaluation. arXiv:2602.03238.

UniACE: A Unified Framework for Evaluating LLM Agentic Capabilities

Supplementary Material

A Comparison with Recent Agent Evaluation Frameworks

Table 4 compares UniACE with recent general-purpose agent evaluation frameworks across framework design, evaluation protocol, and task scope. A feature is marked as supported only when the cited work explicitly implements and demonstrates it in the complete form defined by the corresponding column. The comparison shows that existing frameworks cover complementary subsets of these properties, whereas UniACE integrates standardized benchmark representation, controlled execution, and comprehensive evaluation within a unified model-centric framework.

B Standardized Benchmark Specification

This appendix provides detailed specifications and examples of the standardized benchmark specification introduced in Section 3.1. Each agent benchmark dataset consists of an Instruction Set, a Tool Set, and an Environment Set, which jointly specify the information required for agent execution and evaluation.

B.1 Instruction Set Example

The Instruction Set $\mathcal{I}$ contains the task instances used for agent execution and evaluation. Each instance can be represented as

$$i = \langle p_i, g_i, m_i^* \rangle, \quad (1)$$

where p_i denotes the task instruction, g_i denotes the ground-truth information used for evaluation, and m_i contains optional task-specific information required for execution. $*$ denotes an optional component determined by the task requirements. Depending on the benchmark, g_i may consist of an expected output and, when available, a benchmark-provided reference tool trajectory, or both. While m_i may specify a task-specific tool subset, an environment reference, or other benchmark-specific metadata.

As illustrated in Figure 4, each task is stored as a structured JSON object. The `task_id` field uniquely identifies the task, and `instruction` contains the input presented to the agent. The `label` and `actions` fields store the available ground-truth output and reference trajectory, respectively. The `environment_paths` and other optional fields provide the task-specific resources and metadata required for execution. Ground-truth information is used only for evaluation and is not exposed to the evaluated agent.

B.2 Tool Set Example

The Tool Set $\mathcal{T} = \{\tau_1, \dots, \tau_K\}$ contains the callable tools available to agents for task completion. As illustrated in Figure 5, each tool is implemented as a typed Python function and registered as an agent-accessible tool using the `@tool` decorator. The decorator converts the function signature and docstring into a structured tool schema containing the tool name, description, input parameters, and return information.

This standardized interface enables consistent tool invocation, validation, extension, and reuse across benchmarks while preserving the original task-specific tool semantics.

B.3 Environment Set Example

The Environment Set $\mathcal{E}$ contains the source resources required for task execution. These resources may include structured files, databases, local servers, containerized services, and references to external systems. Supported local formats include JSON, JSONL, CSV, and SQLite databases.

For each task i , the corresponding environment resource $e_i \in \mathcal{E}$ is copied or instantiated as an isolated runtime environment with initial state $E_0^{(i)}$. All tool actions operate on this task-specific runtime instance rather than on the source resource. At execution step t , the runtime state is updated according to the agent’s actions, and the terminal state is retained as the result environment state $E_{\text{res}}^{(i)}$ for evaluation. The source resource e_i remains unchanged across runs.

The isolation mechanism depends on the resource type. Static files and databases are replicated for each task, while local servers and containerized services are isolated through per-task service instantiation, scoped access, or snapshot-and-reset mechanisms. These mechanisms prevent cross-task state contamination while preserving a common execution and evaluation pipeline.

For tasks involving dynamic external resources, such as web search, the framework supports either online interaction with live services or offline execution over fixed, pre-collected snapshots. The offline mode holds the accessible environment content fixed, reducing external volatility and enabling reproducible and traceable evaluation (Chen et al. 2026b; Zhou et al. 2024).

C Configuration Example

Our framework adopts a configuration-driven design, where all components of agent execution and evaluation—including benchmark selection, environment instantiation, tool loading, model serving, and evaluation settings—are fully specified via configuration files. This design enables reproducible experiments and plug-and-play integration of different benchmarks and models without modifying framework code.

C.1 System-level Configuration

Specified via YAML files, $\mathcal{C}_{\text{sys}}$ governs global execution environments. It encompasses dataset settings, inference and agent parameters, output and evaluation settings, and model backend specifications (supporting diverse deployments such as vLLM (Kwon et al. 2023), Hugging Face Transformers (Wolf et al. 2020), and the OpenAI API). Externalizing these parameters ensures zero-code modifications when switching models or datasets, thereby maintaining experimental consistency. Listing I.1 shows a representative system-level configuration.

Framework	Framework Design				Evaluation Protocol			Evaluation Scope	
	Standard Benchmark Representation	End-to-End Configuration	Unified Task-Agnostic Harness	Online/Offline Control	Efficiency Metrics	Failure Attribution	Extensible Evaluation	Single- and Multi-Agent Evaluation	Safety-Critical Evaluation
HAL (Kapoor et al. 2026)	✗	✗	✗	✗	✗	✗	✗	✗	✗
Harbor (Harbor Framework Team 2026)	✗	✓	✗	✗	✓	✗	✓	✓	✗
General Agent Evaluation (Bandel et al. 2026)	✗	✗	✗	✗	✗	✗	✗	✗	✗
AgentCompass (Chen et al. 2026a)	✗	✓	✗	✗	✓	✗	✓	✗	✗
UniACE	✓	✓	✓	✓	✓	✓	✓	✓	✓

Table 4: Comparison with recent general-purpose agent evaluation frameworks. A checkmark indicates that the complete feature is explicitly implemented and demonstrated.

C.2 Agent-level Configuration

Stored in JSONL format, $\mathcal{C}_{agent}$ defines a set of individual agent specifications $\mathcal{C}_{agent} = \{c_1, \dots, c_N\}$. Each configuration instance $c_i = \langle n_i, d_i, \mathcal{T}_i^*, \nu_i^*, s_i^* \rangle$ initializes an agent with a name n_i and description d_i . The optional field $\mathcal{T}_i^*$ explicitly defines agent-specific tool access; if omitted, the agent inherits all globally available tools from $\mathcal{C}_{sys}$. Furthermore, ν_i^* serves as an optional routing node to dictate the subsequent acting agent, inherently supporting complex multi-agent interaction graphs. Finally, s_i^* denotes an optional task-specific system prompt, serving as injected execution priors or domain knowledge. Listing I.2 provides a representative agent-level configuration.

D Evaluation Protocol Details

This appendix provides the formal definitions of the metrics summarized in Section 3.3.

D.1 Task Completion Score

Let r_i be the agent-generated response, τ_i^{pred} the reconstructed trajectory from agent memory, and y_i the ground-truth label for task i . We compute an output-level score:

$$S_i^{\text{out}} = f_{\text{out}}(r_i, \tau_i^{\text{pred}} | y_i), \quad (2)$$

where $f_{\text{out}}(\cdot)$ uses deterministic rule-based matching or an LLM-based judge as specified by the benchmark. Following τ -bench (Yao et al. 2025), for tasks with environment-level supervision, we construct the ground-truth terminal state by replaying the canonical tool trajectory τ_i^* from y_i from the same initial state:

$$E_{\text{gt}}^{(i)} := \delta^* \left(E_0^{(i)}, \tau_i^* \right), \quad (3)$$

where δ^* denotes the iterative application of the environment transition function along the trajectory. We then compare the agent-produced terminal state $E_{\text{res}}^{(i)}$ with $E_{\text{gt}}^{(i)}$ using hash-based matching following prior works (Yao et al. 2025; Liu et al. 2024):

$$S_i^{\text{env}} = \mathbb{1} \left[\mathcal{H} \left(E_{\text{res}}^{(i)} \right) = \mathcal{H} \left(E_{\text{gt}}^{(i)} \right) \right]. \quad (4)$$

With $\mathcal{K}_i \in \{\text{Both}, \text{Out}, \text{Env}\}$ indicating each task’s dependency category, the task completion score (TCS) for instance i is defined as:

$$\text{TCS}_i = \begin{cases} S_i^{\text{out}} \cdot S_i^{\text{env}}, & \text{if } \mathcal{K}_i = \text{Both}, \\ S_i^{\text{out}}, & \text{if } \mathcal{K}_i = \text{Out}, \\ S_i^{\text{env}}, & \text{if } \mathcal{K}_i = \text{Env}. \end{cases} \quad (5)$$

The final score is computed as the average over all N instances:

$$\overline{\text{TCS}} = \frac{1}{N} \sum_{i=1}^N \text{TCS}_i. \quad (6)$$

D.2 Efficiency Metrics

For each task i , we measure four aspects of execution cost: interaction steps, input tokens, output tokens, and elapsed time.

An interaction step corresponds to one complete ReAct (Yao et al. 2023) iteration, consisting of reasoning, action, and the resulting observation. For multi-agent tasks, the interaction steps performed by all participating agents are aggregated.

Let $\mathcal{C}_i$ denote the set of model API calls made by all agents during task i . Input- and output-token counts are obtained from the usage metadata returned by each API call and accumulated over the entire task:

$$m_{\text{Tok}_{\text{in}},i} = \sum_{c \in \mathcal{C}_i} \text{Tok}_{\text{in}}(c), \quad m_{\text{Tok}_{\text{out}},i} = \sum_{c \in \mathcal{C}_i} \text{Tok}_{\text{out}}(c). \quad (7)$$

Elapsed time is measured as the end-to-end wall-clock duration from task initialization to termination:

$$m_{\text{Time},i} = t_i^{\text{end}} - t_i^{\text{start}}. \quad (8)$$

For multi-agent tasks, this metric records the completion time of the entire task rather than the sum of the execution times of individual agents.

Let $m_{k,i}$ denote the value of metric k for task i , where

$$k \in \{\text{Steps}, \text{Tok}_{\text{in}}, \text{Tok}_{\text{out}}, \text{Time}\}.$$

```

1  {
2    "task_id": 1,
3    "instruction": "A string describing the task or goal.",
4    "label": ["ground-truth values"],
5    "actions": [
6      {
7        "tool_name": "name1",
8        "kwargs": {
9          "arg1": "a",
10         "arg2": "b"
11       }
12     }
13   ],
14   "environment_paths": [
15     "Path to the required environment resource."
16   ],
17   "other": {
18     "key": "benchmark-specific metadata"
19   }
20 }

```

Figure 4: Example of a standardized task instance in the Instruction Set.

The benchmark-level efficiency metric is computed by averaging over all N tasks:

$$\bar{E}_k = \frac{1}{N} \sum_{i=1}^N m_{k,i}. \quad (9)$$

D.3 Failure Taxonomy

Table 5 presents the six-category failure taxonomy, covering decision-level and execution-level failures.

Failure analysis is applied only to runs identified as unsuccessful according to the benchmark-specific task-success criterion. For each failed run, an LLM-based failure classifier receives the complete agent trajectory recorded in `final_memory`, the runtime error message, and the evaluation reasoning produced during task-completion scoring. Based on these inputs, the classifier assigns one or more applicable failure categories and generates a brief justification.

Execution-level failures, including timeout, iteration-limit exceedance, and context overflow, are identified primarily from explicit runtime signals. Decision-level failures are determined from the execution trajectory, including output-format violations, invalid tool invocations, and reasoning errors. Multiple labels are permitted when several failure modes jointly contribute to an unsuccessful outcome.

For model m , let $N_{m,c}$ denote the number of failure-label assignments to category c , and let $\mathcal{C}$ denote the set of all failure categories. We report the normalized distribution of

Dimension	Failure Type	Definition
Decision	Parsing Failure	Output violates the required format and cannot be parsed.
	Tool Invocation Error	The agent calls nonexistent tools or uses invalid parameters.
	Reasoning Deficit	The action is formally valid but logically inconsistent with the goal.
Execution	Iteration Limit Exceeded	The agent fails within the maximum allowed turns.
	Context flow	Interaction history exceeds the token limit and gets truncated.
	Timeout	Execution stops due to time or latency constraints.

Table 5: A taxonomy of agent failure modes grouped by decision-level and execution-level characteristics.

failure-label assignments as

$$P_{m,c} = \frac{N_{m,c}}{\sum_{c' \in \mathcal{C}} N_{m,c'}}. \quad (10)$$

A failed run assigned to multiple categories contributes once to each corresponding category. Therefore, $P_{m,c}$ represents the distribution over failure-label assignments rather than the proportion of failed runs.

E Case Study

We use the BFCL Web Search domain to examine two sources of variation that aggregate benchmark scores can

Standardized Tool Example in the Tool Set

```
1 @tool
2 def tool_name(
3     param1: type,
4     param2: type
5 ) -> return_type:
6     """
7
8     Short description of the tool.
9
10    Args:
11        param1: Description of parameter 1.
12        param2: Description of parameter 2.
13
14    Returns:
15        Description of the return value.
16
17    """
18    # Tool implementation
19    return result
```

Figure 5: Example of a typed Python function registered as an agent-accessible tool using the `@tool` decorator.

conflate. The first is the agent framework: even when the model, task, live retrieval backend, and tool interfaces are held fixed, differences in prompt structure, memory representation, error feedback, and termination rules can lead to different outcomes. The second is the environment and retrieval layer: once the framework is fixed, live web access introduces additional variation through stale snippets, inaccessible pages, search-index drift, and noisy tool outputs.

This appendix follows this two-level structure. Case E.1 fixes the task, model, live environment, and retrieval tools while varying the agent framework. Case E.2 fixes our unified framework and examines four environment- and tool-level failure cases across three BFCL Web Search tasks: (i) snippet-level staleness, (ii) anti-bot blocking of an authoritative source, (iii) mismatch between the live search ranking and the benchmark’s reference chain, and (iv) tool-output bloat. These trajectory analyses are diagnostic rather than causal: they identify plausible sources of variation visible in the execution traces but do not isolate each design choice through independent ablations.

E.1 Same Task, Same Live Web, Same Model, Same Tools — BFCL Framework vs. Our Unified Framework

To examine framework-level variation, we run BFCL Web Search task #61 with `gemini-2.5-flash` against the live web under (a) BFCL’s original evaluation framework (Patil et al. 2025) and (b) our unified framework. The instruction, model, retrieval backend, and web-search tool implementations are held fixed. For identical tool calls, both frameworks use the same Python signatures and return

schema. The surrounding agent framework differs in how it constructs the system prompt, represents memory, surfaces tool errors, and handles termination. The resulting trajectories therefore illustrate how framework-level choices can affect the outcome of an otherwise matched task.

Instruction (BFCL Web Search, task #61). “Olympic success often brings greater national recognition and influence in sports. As of April 2025, who is the current headmistress of the high school attended by the head coach of the team that set the record for the most Olympic Women’s Football titles won, according to the 2024 Guinness World Records?”

Ground truth. Sarah Creasey.

The intended chain is four-hop: record-holder → team (USWNT) → head coach (Emma Hayes) → high school (Parliament Hill School, London) → current headmistress (Sarah Creasey).

The BFCL run terminates after three of the twenty allowed steps while the latest observation contains an Emma Hayes Wikipedia snippet, one additional `fetch_url_content` call away from identifying her school. The matched runs begin with the same three search queries but diverge at the next agent decision. The trajectory comparison suggests four plausible contributing factors: (M1) prompt structure, (M2) memory representation and retry feedback, (M3) the answer-format directive, and (M4) the tool-invocation and termination contract. Because these choices vary jointly, the following discussion should be interpreted as a diagnostic analysis rather than an attribution of the outcome to any single mech-

Framework wrapper	Variant	Steps used	Final answer	Correct?
BFCL original	snippet	3 / 20	{‘answer’: ‘I do not know’, ...}	×
BFCL original	no-snippet	3 / 20	{‘answer’: ‘I do not know’, ...}	×
Ours (unified)	online snippet	5 / 20	Sarah Creasey	✓
Ours (unified)	online no-snippet	8 / 20	Sarah Creasey	✓

Table 6: Outcomes on BFCL Web Search task #61 using gemini-2.5-flash and the live web. BFCL returns the prescribed “I do not know” response after three steps, whereas our unified framework reaches the reference answer in five or eight steps, depending on the retrieval-output variant.

anism.

Potential mechanism 1: prompt structure and worked multi-hop examples. The two frameworks differ in the volume and structure of their system prompts. For this task, BFCL uses the three-sentence `ADDITIONAL_SYSTEM_PROMPT_FOR_AGENTIC_RESPONSE_FORMAT` inserted by `process_agentic_test_case`. It specifies the final-answer format but does not describe an Action/Observation loop, provide a worked multi-hop retrieval example, introduce an explicit planning template, or discourage repeated tool calls.

Our framework’s system prompt is generated from the smolagents prompt templates (Roucher et al. 2025) and runs to roughly 120 lines after the tools are inlined. It includes a description of the agent role, an explicit Action/Observation loop, a single-step tool-use example, and a worked multi-search example whose structure resembles task #61:

```
Task: "Which city has the highest
population, Guangzhou or Shanghai?"
Action: {"name": "web_search",
"arguments": "Population Guangzhou"}
Observation: ['Guangzhou has a
population of 15 million inhabitants
as of 2021.']
Action: {"name": "web_search",
"arguments": "Population Shanghai"}
Observation: '26 million (2019)'
Action: {"name": "final_answer",
"arguments": "Shanghai"}
```

The prompt further includes the rendered tool list, an explicit `final_answer` termination instruction, and rules such as avoiding an identical repeated tool call. Between turns, a separate planning prompt (`toolcalling_agent.yaml`) asks the agent to track known facts, missing facts, derivations, and the remaining step budget.

On task #61, the BFCL agent is instructed how to format a final answer but is not given an explicit multi-step retrieval pattern or planning channel. When the third search does not directly return “Sarah Creasey,” it emits the prescribed “I do not know” response. The verbatim match with the fallback specified in the system prompt is consistent with prompt structure contributing to early termination. Under our framework, the model instead has an explicit precedent for continuing with additional retrieval steps. This comparison suggests that prompt structure may influence whether the model continues searching when the current evidence is informative but incomplete.

Potential mechanism 2: memory representation and retry feedback. BFCL constructs the model input by appending role-tagged strings to a growing message list. Tool results are inserted as tool-role messages, while malformed actions are logged by the handler. In the observed run, the feedback available to the model does not provide a dedicated instruction to retry with a different strategy after an invalid action or incomplete result.

Our framework stores each step as an `ActionStep` object with separate `tool_calls`, `observations`, and `error` fields, and rematerializes these records into messages before each model call. This representation distinguishes successful observations from action errors and supports an explicit retry message:

```
Error: <error>\n
Now let's retry: take care not to
repeat previous errors!
If you have retried several times, try
a completely different approach.
```

The retry message is supplied as a `TOOL_RESPONSE` after a failed action and is visible in the subsequent generation.

For task #61, the third observation identifies Emma Hayes but not her school. Under our framework, the structured history preserves this observation as an intermediate result and supports a follow-up query. The agent subsequently reformulates the search as “headmistress Parliament Hill School April 2025”, which resolves the remaining hop. This trace is consistent with structured memory and explicit retry feedback supporting continued search, although the other scaffold choices also differ between the two frameworks.

Potential mechanism 3: a prescribed fallback in the answer template. BFCL’s `process_agentic_test_case` prepends a fixed system message to the agent test case:

```
For your final answer to the user, you
must respond in this format:
{'answer':..., 'context':...}.
If you do not know the answer, respond
with
{'answer': 'I do not know', 'context':
'I do not know'}.
If you think the question cannot
be properly answered, respond with
{'answer': 'I cannot answer this
question',...}.
```

The BFCL agent’s final output on task #61 exactly matches the prescribed “I do not know” fallback. At that point, the

context already contains a relevant Emma Hayes snippet, but the agent has not yet retrieved the school page. Thus, the template provides a syntactically valid termination response for an intermediate state of uncertainty.

Our framework does not impose this answer schema. Termination instead occurs through a `final_answer` tool call. A bare-text “I don’t know” response is therefore not treated as a valid termination action and can trigger another iteration. This difference offers a plausible explanation for why uncertainty ends the BFCL run but not the corresponding run in our framework.

A related BFCL-specific consideration is that successful responses must also populate the `context` field, which can increase output-token usage relative to a bare final answer. Token comparisons involving this domain should therefore be interpreted with this formatting difference in mind. The cross-model efficiency comparisons in Section 4.4 include benchmarks without this prescribed answer template.

Potential mechanism 4: the termination contract. BFCL exposes its web-search functions through Gemini’s native function-calling API. Function declarations are constructed from the Python signatures, and tool results are returned as function-response parts. The framework has no dedicated termination tool; a run completes when the model stops emitting a function call and returns plain text, which the handler treats as the final response.

Our framework registers the same two web-search functions through `ToolCallingAgent` and adds a synthetic `final_answer` tool. The agent terminates only through a valid `final_answer(answer=...)` call. Otherwise, the step is treated as an invalid or incomplete action and the retry path can continue the interaction.

Together with the prescribed fallback described in M3, this difference offers a plausible account of the divergence at the next decision after the third search. Under BFCL, the “I do not know” string is both encouraged by the answer template and accepted as a terminal plain-text response. Under our framework, the same string is not a valid termination action, leaving room for another retrieval step and query reformulation. These are properties of the agent loop rather than changes to the underlying web-search functions.

Implication for unified evaluation. The verdict on task #61 changes under four jointly varying scaffold choices: prompt structure, memory and retry feedback, the answer template, and the termination contract. The case does not identify the independent contribution of each choice, but it demonstrates that the statement “gemini-2.5-flash fails task #61” is conditional on the surrounding agent framework.

Similar scaffold-level mechanisms may contribute to the bidirectional score changes reported in Section 4.2. Standardizing the scaffold does not remove engineering choices; rather, it holds those choices fixed and makes them explicit, allowing model comparisons to be conducted under a common execution condition.

E.2 Case Studies on Environmental and Tool-Level Failure Modes

We next hold the model and our unified framework fixed and vary the information returned by the environment and retrieval layer. Four failure cases across three BFCL Web Search tasks illustrate how live external resources can affect benchmark outcomes:

- 2.1 *Snippet staleness*: an outdated indexed paragraph supports a confident but incorrect answer (task #1).
- 2.2 *Authoritative-source denial*: the page containing the relevant evidence repeatedly returns 403 (task #55).
- 2.3 *Search-index mismatch*: the live top-ranked result follows a different resolution chain from the benchmark’s reference chain (task #59).
- 2.4 *Tool-output bloat*: raw page extraction introduces navigation, advertisements, and boilerplate that reduce the information density of the agent context (a sub-case of task #1).

In these selected cases, the offline snapshot supports successful completion whereas the online run does not. The divergence is initiated by differences in the environment or tool output rather than changes to the model or agent configuration. These cases illustrate concrete mechanisms that can contribute to the aggregate online–offline gaps reported in Section 4.3.

Snippet Staleness Producing a Confident Wrong Answer

Instruction (BFCL Web Search, task #1). “Some countries are known for producing luxury goods, including the world’s most expensive tea. In April 2025, who is the richest billionaire (according to Forbes) from the country that produces the most expensive tea?”

Ground truth. Zhang Yiming.

The instruction requires two hops: resolving the country associated with the most expensive tea to China, and then identifying the richest Chinese billionaire according to the specified Forbes reference and date. In the offline setting, the relevant pages are fixed at curation time; in the live setting, the indexed snippets and accessible pages can change.

Offline trajectory (snippet variant).

- S1 `search_engine_query`(“most expensive tea in the world country”) → results identifying Da Hong Pao and China.
- S2 `search_engine_query`(“richest billionaire China Forbes 2024”) → the curated Forbes snapshot reports Zhang Yiming’s wealth ranking and net worth.
- S3 `final_answer`(“Zhang Yiming”). ✓

The no-snippet variant follows the same plan but performs two additional page fetches before returning the same answer. In both variants, each step is linked to a fixed document that can be inspected after execution.

Online trajectory (snippet variant). For the query “richest billionaire China Forbes latest,” the live search service returns a highly ranked Wikipedia snippet stating that Zhong Shanshan is the current richest Chinese billionaire.¹ The agent follows the same two-hop structure but receives different evidence:

- S1 `search_engine_query`(“most expensive tea in the world country”) → Da Hong Pao (China).
- S2 `search_engine_query`(“richest billionaire China Forbes latest”) → snippet naming Zhong Shanshan.
- S3 `final_answer`(“Zhong Shanshan”). ×

The resulting answer is consistent with the snippet returned by the live service but conflicts with the benchmark’s fixed reference answer. From the final score alone, this appears as a model error; the trajectory shows that the divergence originates in the retrieved content.

Online trajectory (no-snippet variant). When the snippet body is removed, the agent must fetch pages before answering. Several authoritative or relevant sources are inaccessible:

- S1–S3 The agent identifies China and searches for the April 2025 Forbes China ranking.
- S4 `fetch`(forbes.com/sites/ywang/...10-richest-chinese-billionaires-2025) → 403 Forbidden.
- S5 `fetch`(forbes.com/lists/china-billionaires/) → 403 Forbidden.
- S7 `fetch`(forbesmiddleeast.com/...10-richest-chinese-billionaires) → a landing-page heading without the ranking content.
- S9 `fetch`(coinedition.com/binance-cz-richest-forbes-list/) → a reachable article naming Changpeng Zhao as the richest Chinese person.
- S10 `fetch`(forbeschina.com/leadership/70612) → Max retries exceeded.
- S11 `fetch`(baike.baidu.com/en/...) → “The entry does not exist.”
- S13–S17 Three additional Forbes fetches return 403.
- S18–S19 Further query reformulations return the same inaccessible sources.
- S20 At the step limit, the agent returns Changpeng Zhao, the only candidate supported by a fully accessible article. ×

The offline run follows a similar high-level plan and returns the reference answer in five steps. The primary difference is the set of documents the agent can access. The online trajectory contains repeated denials, incomplete pages, and one accessible third-party article supporting a different answer. A score or step-limit label alone cannot distinguish weak planning from restricted access to evidence.

¹At evaluation time, the indexed page reflected an older ranking in which Zhong Shanshan occupied the top position.

Anti-Bot Blocking of an Authoritative Source

Instruction (BFCL Web Search, task #55). “Education plays a key role in shaping future political leaders and policymakers. Who is the current headmaster of the secondary school attended by the president of the country that is home to the world’s largest building shaped like a chicken, according to the 2024 Guinness World Records?”

Ground truth. Stuart McPherson.

The reference chain is building → country (Philippines) → president (Bongbong Marcos) → secondary school (Worth School, UK) → current headmaster. The online and offline trajectories diverge at the final hop, which depends on pages hosted by the school’s website.

Offline trajectory. The fixed snapshot contains two Worth School pages that distinguish the incoming and current headmasters:

- S6 `fetch`(worthschool.org.uk/new-head-of-worth-school-announced/) → a page announcing Ben Pennington’s future appointment.
- S7 `fetch`(worthschool.org.uk/head-masters-welcome/) → a page identifying Stuart McPherson as Head Master.
- S8 `final_answer`(“Stuart McPherson”). ✓

The two pages allow the agent to distinguish an announced successor from the current office holder.

Online trajectory. In the live run, the Worth School origin returns 403 Forbidden to the agent’s fetch client on repeated attempts:

- S6 `fetch`(worthschool.org.uk/Head-Masters-welcome/) → 403 Forbidden.
- S8 `fetch`(worthschool.org.uk/new-head-of-worth-school-announced/) → 403 Forbidden.
- S16 A later retry of the headmaster page again returns 403 Forbidden.

The agent then reformulates the query and consults secondary sources, some of which refer to the incoming rather than current headmaster. It eventually searches for “Stuart McPherson Worth School current headmaster” but cannot access the school page needed to verify the candidate and reaches the step limit without a definitive answer.

The two runs expose different evidence under the same model and agent configuration. The offline snapshot preserves the pages needed for the final disambiguation, whereas the live fetch client is denied access. This case therefore illustrates an environment-access failure that would otherwise be recorded as an unsuccessful agent run.

Search-Index Mismatch in a Multi-Hop Chain

Instruction (BFCL Web Search, task #59). “Athletes’ hometowns often play a role in shaping their careers and influence local politics. Who is the current spouse of the current mayor (as of April 2025) of the hometown of the player who achieved the most UFC title bout wins by November 2024?”

Ground truth. Shawanda Evans.

This task illustrates a less visible source of online evaluation variation: a mismatch between the resolution chain assumed by the benchmark’s fixed ground truth and the chain returned by the live search index. If a live result maps an intermediate entity differently from the benchmark’s reference chain, all subsequent steps may remain internally coherent while producing a different final answer.

The benchmark’s reference chain is

```
most UFC title-bout wins by Nov. 2024
→ Jon Jones
→ Rochester, NY
→ Mayor Malik D. Evans
→ Shawanda Evans.
```

The disputed hop is the interpretation of Jon Jones’s hometown. The reference chain uses Rochester, NY, while the live search result foregrounds Endicott, NY, his birthplace. This routes the online agent into a different downstream chain.

Offline trajectory.

```
S1  search(“UFC player most title bout wins November 2024”) → Jon Jones.
S2–S3 Searches for the mayor of Rochester and Malik Evans’s spouse → Malik D. Evans and Shawanda Evans.
S4  fetch(en.wikipedia.org/wiki/Malik_Evans) → a biography listing Shawanda Evans as spouse.
S5  final_answer(“Shawanda Evans”). ✓
```

The snapshot holds the benchmark’s reference chain fixed and makes every hop inspectable.

Online trajectory. The live search index foregrounds Endicott, NY, and the subsequent searches follow that interpretation:

```
S3  search(“Jon Jones hometown”) → Endicott, NY.
S5  search(“current mayor of Endicott, New York April 2025”) → Nick Burlingame.
S6–S10 Repeated searches for the mayor’s spouse return campaign pages and local news without the requested information.
S11 final_answer(“I could not find information...”). ✗
```

The trajectory is locally coherent after the hometown resolution, but it no longer follows the chain against which the ground truth was authored. The mismatch occurs at the intermediate entity resolution rather than in the subsequent search procedure.

Measurement implication. The instruction and reference answer are fixed, whereas the live ranking is not controlled by the evaluator. The resulting score therefore reflects both the agent’s behavior and the particular resolution chain exposed by the live search service. In Case E.2, holding the retrieval corpus and ranking fixed through a snapshot removes this source of variation and makes the remaining decisions more directly attributable to agent behavior under the specified environment.

Tool-Output Bloat — Raw HTML vs. Curated Extracts

The preceding cases concern the content or accessibility of retrieved evidence. This case concerns how the retrieval tool packages that evidence. A live page extractor may return navigation menus, cookie notices, advertisements, related links, footers, and other boilerplate in addition to the article text. Such output consumes context and lowers the density of information relevant to the task. A more sophisticated live tool could apply boilerplate removal and length budgeting; the offline setting instead performs this processing once during snapshot construction.

We illustrate the output-density difference using two representative fetches from task #1: an online Wikipedia page returned by the live extractor and the curated Forbes snapshot used for the second hop of the offline trajectory. These examples do not compare the same URL; they demonstrate the contrast between raw live extraction and the fixed, processed content available in the offline environment.

Online fetch: approximately 13,000 characters with substantial boilerplate. The online fetch of `en.wikipedia.org/wiki/Da_Hong_Pao` returns roughly 13,000 characters. Its opening segment consists largely of page chrome:

```
Da Hong Pao - Wikipedia\n
Jump to content\n
Main menu\n
Main menu\n
move to sidebar\n
hide\n
Navigation\n
Main page\n
Contents\n
Current events\n
Random article\n
About Wikipedia\n
Contact us\n
:\n
Personal tools\n
Donate...
```

The task-relevant article content appears only after navigation and interface text. Consequently, a substantial portion of the returned context is not directly useful for resolving the task.

Offline fetch: a compact curated evidence record. The curated Forbes snapshot used in the offline trajectory returns a 176-character record:

```
{"content": "ByteDance cofounder Zhang Yiming moved up to second place on a wealth ranking after increasing his
```

net worth by \$23.7 billion, reaching a total of \$69.3 billion."}

The fixed record is substantially more information-dense and directly supports the corresponding resolution step.

Measurement implication. The model, prompt, and planning mechanism are unchanged across the online and offline settings, but the information density of the tool output differs. In the raw live setting, each token of the available context carries less task-relevant information, and repeated fetches can fill the context with boilerplate before the relevant evidence is synthesized. A final failure may therefore reflect the retrieval tool’s output processing as well as the model’s reasoning.

In principle, a benchmark could implement a live boilerplate-removal pipeline. However, such heuristics can vary across sites and page redesigns, introducing additional maintenance and evaluation variance. Snapshot construction performs this processing once and exposes the resulting representation consistently across runs.

Joint takeaway. The four cases operate at different layers: indexed snippet content, page access, search ranking, and tool-output formatting. These factors arise outside the model parameters but can still appear in aggregate results as wrong answers or exhausted budgets. Some produce explicit runtime evidence, such as 403 responses, while others create latent mismatches that resemble reasoning errors. Fixed snapshots do not eliminate all evaluation choices, but they hold the accessible content and its packaging constant, reducing these sources of run-to-run variation.

E.3 What the Cases Have in Common

Together, the cases identify three layers that influence agent benchmark outcomes: the framework mediating between the model and tools, the content and accessibility of evidence exposed by the environment, and the representation of that evidence returned by the retrieval tool. In each case, the final score cannot be attributed to the model alone; it is jointly determined by the agent framework, the environment, and the information delivered through tool observations.

Running agents under a shared framework and a fixed environment reduces these uncontrolled sources of variation and makes outcomes more interpretable under explicitly specified evaluation conditions. Live-web evaluation remains useful for measuring end-to-end robustness, but its results should be interpreted as properties of the complete model–framework–environment system rather than as model-only capability estimates.

F Consistency of Evaluation Model

Several benchmarks rely on an LLM-based judge to score outputs. To validate our default judge, Gemini-3-Flash, we randomly sample 300 rollouts stratified across benchmarks and agents, and have two human annotators independently label each sample (disagreements resolved by a third annotator) to produce a human-gold reference. Three candidate judges—Gemini-3-Flash, GPT-5-mini, and Qwen3-235B-A22B—are then scored against this reference using Cohen’s κ (Cohen 1960).

Judge model	Cohen’s κ ($\uparrow$)
Gemini-3-Flash	0.95
GPT-5-mini	0.93
Qwen3-235B-A22B	0.91
Human (inter-annotator)	0.97

Table 7: Cohen’s κ between each judge and the human-gold label on 300 stratified samples.

All three judges reach almost-perfect agreement (Landis and Koch 1977) with human-gold labels. Gemini-3-Flash is closest to the human ceiling (0.95 vs. 0.97), with GPT-5-mini and Qwen3-235B-A22B trailing only marginally; the relative ordering of evaluated agents in the main text is therefore robust to the specific judge choice within this set, supporting our use of Gemini-3-Flash by default.

G Distribution of Failure Analysis for Each Benchmark

This section provides a detailed breakdown of failure distributions across individual benchmarks. While Section 4.5 presents the aggregated failure patterns across all advanced models, the following subsections examine how failure modes vary across different benchmark domains. These benchmark-specific analyses reveal that failure profiles are not only model-dependent but also task-dependent, with certain benchmarks exposing particular weaknesses in reasoning, parsing, or planning capabilities. Understanding these domain-specific failure patterns provides deeper insights into the limitations of current LLM-based agents and informs targeted improvements for specific application scenarios. Note that MultiAgentBench evaluates each task on a multi-dimensional 1–5 scale; for failure attribution, we treat task scoring below 3 (less than half of the full score) as failures.

Failure Analysis Distribution of AgentBench in the Database Domain




Figure 6: Failure Analysis Distribution of AgentBench in the Database Domain

- G.1 AgentBench
- G.2 BFCL
- G.3 τ -bench
- G.4 τ^2 -bench
- G.5 BrowseComp
- G.6 MultiAgentBench

Failure Analysis Distribution of AgentBench in the Knowledge Graph Domain




Figure 7: Failure Analysis Distribution of AgentBench in the Knowledge Graph Domain

Failure Analysis Distribution of AgentBench in the Digital Card Game Domain




Figure 8: Failure Analysis Distribution of AgentBench in the Digital Card Game Domain

Failure Analysis Distribution of AgentBench in the Lateral Thinking Puzzle Domain




Figure 9: Failure Analysis Distribution of AgentBench in the Lateral Thinking Puzzle Domain

Failure Analysis Distribution of AgentBench in the Web Shopping Domain




Figure 10: Failure Analysis Distribution of AgentBench in the Web Shopping Domain

Failure Analysis Distribution of AgentBench in the Web Browsing Domain




Figure 11: Failure Analysis Distribution of AgentBench in the Web Browsing Domain

Failure Analysis Distribution of BFCL in the Web Search Domain




Figure 12: Failure Analysis Distribution of BFCL in the Web Search Domain

Failure Analysis Distribution of BFCL in the Memory Domain




Figure 13: Failure Analysis Distribution of BFCL in the Memory Domain

Failure Analysis Distribution of BFCL in the Multi Turn Domain




Figure 14: Failure Analysis Distribution of BFCL in the Multi Turn Domain

Failure Analysis Distribution of BFCL in the Single Turn(live) Domain




Figure 15: Failure Analysis Distribution of BFCL in the Single Turn(live) Domain

Failure Analysis Distribution of BFCL in the Single Turn(Non-live) Domain




Figure 16: Failure Analysis Distribution of BFCL in the Single Turn(Non-live) Domain

Failure Analysis Distribution of BFCL in the Hallucination(Relevance) Domain




Figure 17: Failure Analysis Distribution of BFCL in the Hallucination(Relevance) Domain

Failure Analysis Distribution of BFCL in the Hallucination(Irrelevance) Domain




Figure 18: Failure Analysis Distribution of BFCL in the Hallucination(Irrelevance) Domain

Failure Analysis Distribution of τ -bench in the Airline Domain




Figure 19: Failure Analysis Distribution of τ -bench in the Airline Domain

Failure Analysis Distribution of τ -bench in the Retail Domain




Figure 20: Failure Analysis Distribution of τ -bench in the Retail Domain

Failure Analysis Distribution of τ^2 -bench in the Airline Domain




Figure 21: Failure Analysis Distribution of τ^2 -bench in the Airline Domain

Failure Analysis Distribution of τ^2 -bench in the Retail Domain




Figure 22: Failure Analysis Distribution of τ^2 -bench in the Retail Domain

Failure Analysis Distribution of τ^2 -bench in the Telecom Domain




Figure 23: Failure Analysis Distribution of τ^2 -bench in the Telecom Domain

Failure Analysis Distribution of BrowseComp




Figure 24: Failure Analysis Distribution of BrowseComp

Failure Analysis Distribution of MultiAgentBench in the Research Domain




Figure 25: Failure Analysis Research of MultiAgentBench

Failure Analysis Distribution of MultiAgentBench in the Database Domain




Figure 26: Failure Analysis Database of MultiAgentBench

Failure Analysis Distribution of MultiAgentBench in the Coding Domain




Figure 27: Failure Analysis Coding of MultiAgentBench

Failure Analysis Distribution of MultiAgentBench in the Bargaining Domain




Figure 28: Failure Analysis Bargaining of MultiAgentBench

H Benchmark Migration and Adaptation

In this appendix, we outline the process of migrating and adapting various benchmarks to our unified framework. Each benchmark is restructured into three core components: the Instruction Set, the Tool Set, and the Environment Set. This migration ensures that all benchmarks are compatible with our standardized sandbox, allowing for consistent, reproducible, and fair evaluations of LLM-based agents.

H.1 AgentBench

Instruction Set The instruction set represents the primary task goals, directly derived from the original dataset’s objective descriptions. We maintain consistency with the original benchmark, only reformatting the instructions to meet the deterministic entry requirements of our sandbox. Both the instructions and the evaluation labels remain identical to the original, with necessary adaptations made to environment data paths for per-task execution.

Database Tasks Preserved as natural language queries requiring SQL translation. Constraints in the instructions (e.g., "return only the name") are used by the judge to verify output precision.

Knowledge Graph Tasks Mapped from the original `question` field. We enforced an implicit "Entity Resolution" protocol where instructions involving natural language names require an initial mapping to unique identifiers (e.g., `m.0xxxx`) using the toolkit before graph traversal.

Card Game Tasks Each instruction describes a 2-player turn-based fish battle: both sides field four fish drawn from nine species, each with 400 HP, 200 base attack, a passive ability (auto-triggered) and an active ability. The agent’s own team composition and all nine fish-type descriptions are provided; the enemy team’s identities are hidden.

Lateral Thinking Puzzle Tasks Includes game rules and initial story. The agent asks one question at a time, with 'yes/no/irrelevant' responses, progressively narrowing down the truth. The agent cannot declare the task finished or give up, cannot repeat story information, and must avoid asking "why" or requesting details directly. Each puzzle has hidden truth and key details for offline evaluation, with a link to the puzzle snapshot via `'environment_path'`.

Web Shopping Derived from WebShop-style product search tasks. Each instruction is a natural-language shopping request (e.g., product type + attributes + constraints). We pair it with a structured ground-truth label (from `extracted_samples.jsonl`) containing a target `asin`, a list of required attributes, and explicit options (e.g., "color: blue"). The judge computes a *fractional* reward based on attribute/option/budget overlap, and assigns **0.0** if the agent never finalizes a purchase (i.e., no terminal buy action is produced).

Web Browsing Tasks Extracted from the `confirmed_task` field. Agents need streamline complex multi-step goals (e.g., "Find the cheapest ticket") into atomic, sequential directives, reducing the cognitive load required to parse local HTML snapshots.

Tool Set We re-engineered the toolkits to be compatible with the unified protocol, ensuring that the original logic of the tools remains unchanged. The toolkits were adapted to the framework without altering the core functionality or task-specific behavior of the original benchmark. Specifically, we replaced the original black-box APIs with transparent, feedback-rich Python functions, which allows for more detailed interaction and traceability, while maintaining the integrity of the original tool logic.

Database The `execute_sql` tool was re-implemented as a direct interface to a local SQLite engine. It accepts raw SQL strings and returns query results as stringified tuples (e.g., `"[('Result',)]"`). Crucially, it captures `sqlite3` exceptions and returns them as observations, enabling the Agent to perform self-correction upon syntax errors without crashing the session.

Knowledge Graph We implemented a dynamic loader mechanism (`kg_tools_loader.py`) that exposes graph traversal primitives. Unlike the original abstract actions, our tools leverage the `task_context` map to provide entry points (e.g., mapping "German Shepherds" to `m.0km5c`). Returns are structured as explicit entity lists, allowing the Agent to visualize neighbors and verify relation paths immediately.

Card Game Two tools implement the per-round two-phase protocol: `guess_enemy_fish(target_position, guess_type)` submits the ASSERT-phase identity guess (a correct guess reveals the fish and deals 50 damage to all enemies); `execute_action(pick_fish, action_type, target_position)` submits the ACT-phase move (normal or active). Each tool return includes the updated game state, so no separate state-polling is required. Phase ordering is enforced server-side and violations return a descriptive error guiding the agent to retry.

Lateral Thinking Puzzle The core tool `'ask_puzzle_host(question)'` returns 'yes/no/irrelevant' answers based on the puzzle’s 'story', 'answer', and keys, using the LLM set to GPT-4o-mini.

Web Shopping We replaced the original browser-heavy interaction with a minimal, deterministic toolchain compatible: (1) `search_products(query)` performs offline retrieval over the local product library and returns top candidates as compact JSON (`ASIN/title/price/category/score`); (2) `get_product_details(asin)` returns normalized product metadata and the full `available_options` space to prevent invalid option selection; (3) `select_product(asin, options)` emits the final purchase record

Web Browsing We fully refer to the original tool logic.

Environment Set The environment migration focused on converting large or dynamic external systems into localized, task-specific snapshots. This approach ensures offline security and reproducibility by isolating each task’s environment from others, allowing for consistent and controlled evaluation without relying on external dependencies.

Data Base We converted the original database requirements into localized SQLite connection objects. The `load_environment_data()` utility dynamically binds the correct database slice (e.g., `db_001.sqlite`) to the current task execution context. This isolation prevents cross-task data pollution and eliminates the need for a persistent database server.

Knowledge Graph Instead of querying a live Freebase endpoint, we sliced the massive graph into independent, task-specific JSON files. Each environment file contains a self-contained dictionary of `entities` (mapping IDs to `out_relations` and `in_relations`) and a `task_context` for grounding natural language terms. This allows the Agent to perform multi-hop reasoning within a strictly bounded graph subset.

Card Game Each task is defined by a JSON spec file (`specs/task_{id}.json`) recording the two teams' fish compositions and match constants. A Python HTTP game server (`server.py`) is launched as an isolated subprocess per task, loading the spec and instantiating `game_engine.py` — a faithful reimplementation of the original C++ source — which tracks HP, ATK buffs, passive counters, and phase state. Stale servers are terminated when a new task is detected, preventing cross-task state leakage.

Lateral Thinking Puzzle Each task is represented as a `'puzzle_*.json'` file containing `'story'`, `'answer'`, and keys, offering a self-contained context. Links the puzzle environment to the task via `'environment_path'` and ensures task-specific data is loaded for reproducibility.

Web Shopping To ensure offline security and reproducibility, the entire storefront is virtualized into a read-only local search index: we index the WebShop product corpus into a Lucene snapshot (`Environment/AgentBench/webshop/indexes`). Each indexed document stores a normalized `contents` field (`title/description/features/options`) for deterministic BM25 retrieval, and uses `asin` as the stable document identifier for exact lookup during `get_product_details`. This eliminates all network/HTML rendering dependencies while preserving the core “search → inspect → purchase” decision loop.

Web Browsing We transformed volatile live websites into a rigid sequence of "Cleaned HTML" snapshots. The environment manages the virtual DOM state with **Session Isolation**: a global manager enforces strict boundary checks and forces a "Context Reset" when a new task file is detected, clearing dirty flags to prevent state pollution (e.g., "List index out of range" errors) in open-weights models.

H.2 BFCL

To integrate the Berkeley Function Calling Leaderboard (BFCL) into our offline secure Agent evaluation sandbox, we reorganized the official dataset according to our standards. Due to the large volume of BFCL data, we performed an evaluation using the entire dataset for comparison results.

Instruction Set

Memory Dataset Migration Memory series dataset: We integrate all the pre-conversation data from the `memory_prereq_conversation` directory into one unified `unified_memory_prereq.jsonl` file. This integration makes the format of context info (such as user profiles, past chat bits) uniform, and it puts in special memory snapshot marks for each task, which lets the sandbox load up and check how well it can handle memory at once. Unified format guarantees that the Agent's memory read/write operations remain consistent among various evaluation situations.

Other Dataset Migration For the migration of other datasets, we reorganized the original data into four standardized fields: instruction, label, tools, and environment, and serialized the data in JSON Lines (JSONL) format for efficient parsing. This restructuring ensures that each dataset fits seamlessly into our offline secure Agent evaluation sandbox.

- **Instruction:** This field corresponds to the task description from the original dataset, which includes user questions, conversation context, and task goals. It ensures that the Agent can correctly interpret and respond to the evaluation scenario.
- **Label:** This field is mapped to the ground truth in the original dataset, containing the correct answer, including the ideal sequence of function calls, the parameter setup, and the expected outcomes. It serves as the gold standard for offline evaluation.
- **Tool:** Extracted from the function field in the original dataset, this section is restructured to align with the tool invocation protocol of our sandbox. It includes the function metadata (name, parameters, and returns) and execution dependencies to ensure secure offline tool loading.
- **Environment:** The environment data is extracted from the original dataset and stored separately in the environment directory. The dataset includes the storage path for this environment data, allowing for easy switching between evaluation scenarios without requiring an online connection.

Tool Set

Migration for Multi-Turn, Memory, and Web Series Toolkits To keep the official evaluation results accurate, we reuse the main part of the multi-turn_*, memory, and web series toolkits' codes, adjust them for the unified format, and add some functions that extend their functionality:

- **Global State Manager:** Added to multi-turn_* series tools for maintaining cross-turn context (API state, dialogue history), and enabling real-time state synchronization during Agent evaluation. The manager makes sure that the sandbox correctly follows how functions run and change states.

Migration for Other Tools For toolkits that are not part of the above series, we use an LLM-driven generation method: the agent parses the original data set to get the function logic, then generates tool scripts according to the one-tool-one-script principle. Every script has its own execution entry,

parameter check logic, and offline compatibility adjustments so that the tool can operate independently within the sandbox environment without needing anything else. The created tools are kept in task-specific folders for easy modular loading and versioning.

Environment Set The original BFCL dataset does not have environment data for most task series, only the multi-turn dataset has the `initial_config` field. To solve this problem, we take out the environment dependencies from the `initial_config`, create a separate JSON environment file for every task, and keep them in the `exports` folder. One task per file makes sure that the sandbox can load its own environment states (such as starting API settings, user session info) when doing offline checks without getting mixed up with other tasks.

Web Search Series Dataset Adaptation Because the sandbox is offline, we turn the official real-time web search tasks into offline evaluation situations via this pipeline:

- **Offline Data Crawling:** Set up a Google search simulator that is powered by our Agent framework to crawl webpages using the URLs found in the `source` field of the original dataset. The data that has been crawled is stored in the `Environment/web` folder.
- **Dual-source data construction:** For every task, crawl another set of content through real-time simulated search using the same original query, then blend these two sets together with a noise dataset (which has irrelevant web snippets) to create the final environment dataset. It simulates real world info duplicity and makes offline evals stronger.
- **Standardized Field Definition:** The last environment dataset (in JSONL format) has `task_id`, `URL`, `snippet`, and `text` fields. `Text` field contains the summarized content of the crawled data by LLM, making sure that the environment information is concise and organized.
- **Offline Retrieval Optimization:** Create an inverted index for the combined environment dataset to facilitate quick keyword lookup. Index is split up and kept in `Environment/web/bfcl_index/share_0`, allowing the sandbox to quickly find matching environment info when doing offline checks.

Memory Series Environment Data Processing For memory series task, our agent framework will make the LLM to parse the `unified_memory_prereq.jsonl` file. After performing memory read/write actions (such as context extraction, state snapshotting), the framework saves the outcomes as JSON files within `snapshot/BFCL_v4_memory_generate_*`. This way, the sandbox can play back the memory interaction procedures offline and assess how well the Agent preserves, modifies, and retrieves memory states.

Environment Data Encoding for Other Tasks For tasks that do not have an explicit environment in the original dataset, we use a tool-embedded encoding method: the environment dependencies such as the prerequisites for the function execution and the constraints on parameters are included in the `tools` field. Light weight to avoid storing redundant en-

vironment files, and also to make sure the agent gets all the context it needs when using offline tools.

H.3 τ / τ^2 -bench Migration Details

τ and τ^2 -bench are conversational agent benchmarks designed to evaluate tool-mediated user–assistant interaction under structured service environments. While both benchmarks share a common design philosophy, τ^2 -bench extends τ -bench with dual-control environments, where task success depends jointly on multi-turn dialogue behavior and environment state transitions. To integrate both benchmarks into our unified sandbox framework, we adopt a shared migration pipeline and explicitly document their structural differences. The migrated benchmarks are organized into four standardized components: Instruction Set, Tool Set, Environment Set, and Multi-Agent Structure.

Instruction Set For both τ and τ^2 -bench, each task instance is migrated into a structured Instruction Set that explicitly specifies the conversational goal, reference action trajectory, and evaluation targets required for offline and reproducible agent assessment.

- **Instruction** corresponds to the primary input for the User-Agent. We aggregate the original Reason for call, Known info (e.g., “You are Sophia Silva”), Unknown info, and Task instructions into a single coherent prompt. This ensures the user simulator accurately roleplays the persona and adheres to the hidden constraints of the scenario.
- **Actions** encodes the canonical sequence of tool invocations that constitutes a valid task completion under the ground-truth environment dynamics. Each action specifies the tool name and its arguments, forming an ordered reference trajectory. This field is used exclusively for environment-level evaluation, where the sandbox replays the action sequence to construct the ground-truth terminal environment state and compare it against the agent-induced environment outcome.
- **Label** provides a high-level semantic description of the expected task outcome, including success conditions, disallowed behaviors, and policy-relevant constraints. Unlike the `actions` field, the label does not prescribe a concrete tool sequence. The label serves as the ground truth for the Judge model to verify whether the agent successfully met the goal.

Tool Set The Tool Set is migrated from the original function definitions in τ and τ^2 -bench and restructured to comply with the standardized tool invocation protocol of our sandbox. All tools are implemented as callable Python functions following the unified interface, with: 1) Explicit function names; 2) Typed input arguments; 3) Structured textual outputs; 4) Deterministic execution logic suitable for offline evaluation.

To maintain consistency in a stateless function-calling environment, we adopt a *Load–Modify–Save* pattern. Each tool invocation loads the current environment state from local storage, applies domain-specific business logic, and persists the updated state back to the environment store.

Benchmark Differences. Although τ and τ^2 -bench share overlapping functionality, their tool implementations differ in both scope and granularity. We preserve these differences during migration, while enforcing a unified invocation interface and logging protocol.

Each domain defines a domain-specific tool subset:

- **Airline tools** support reservation querying, flight search, booking modification, cancellation, and status inspection.
- **Retail tools** support order lookup, item exchange or return, address and payment modification, and product querying.
- **Telecom tools** (only in τ^2 -bench) support device status checks, network configuration, billing queries, payment handling, and service activation or suspension.

Environment Set The Environment Set contains all domain data required for task execution and is fully decoupled from the core dataset.

τ -bench Environment. For τ -bench, environment data is directly migrated from the original dataset and materialized as local, persistent JSON files. Each task operates over a fixed environment consisting of three domain-specific files: `flights.json`, `reservations.json`, and `users.json`. These files preserve the original data schema and semantics, ensuring full consistency with the source benchmark.

τ^2 -bench Environment. For τ^2 -bench, environment data is restructured to support dual-control evaluation. In the original implementation of tau2, for each domain, the environment files are merged into a single unified JSON file (`db.json`) that encapsulates all relevant state variables. The files of airline and retail have retained the original data structure and semantics, ensuring complete consistency with the source reference data. In the telecom domain, task-specific environments are further constructed by applying a sequence of state-setting tool calls derived from the provided `initial_state`, generating customized initial environment instances.

For both benchmarks, each task instance includes explicit references (environment paths) to the required environment data. During execution, the sandbox instantiates an isolated environment replica for the task, ensuring that:

- All state transitions are local and reproducible;
- No cross-task contamination occurs;
- Different evaluation scenarios can be swapped without modifying the dataset itself.

This design enables strict offline evaluation while preserving the stateful nature of τ and τ^2 -bench tasks.

Multi-Agent Structure Both τ and τ^2 -bench inherently model interactive dialogue, which we formalize using a multi-agent structure consisting of two distinct agents:

- **UserAgent**, which simulates the user’s conversational behavior according to the task instruction and user prompt;
- **Domain Assistant Agent** (e.g., `TauAirlineAgent`, `TauRetailAgent`, `Tau2TelecomAgent`), which performs reasoning and tool invocation to resolve the task.

The interaction topology is explicitly defined through agent nodes:

- In airline and retail domains, the UserAgent initiates the conversation and routes control to the corresponding assistant agent.
- In the telecom domain (only in τ^2 -bench), bidirectional routing is supported, allowing the assistant to request further user actions or transfer control back to the user agent.

H.4 BrowseComp

BrowseComp requiring agents to perform online web searches introduce significant challenges regarding reproducibility. While interacting with live web search APIs reflects real-world dynamics, the volatility of web content—where sources may change, move, or disappear—renders task resolution non-traceable and comparisons unfair over time.

To address this, BrowseComp-Plus (Chen et al. 2026b) stabilized the benchmark by creating static snapshots of web content. Analysis of this static corpus revealed that a substantial portion of the original tasks had become unsolvable due to URL expiration (link rot) or content updates.

Drawing inspiration from BrowseComp-Plus, we migrated the BrowseComp benchmark into a fully local, deterministic environment. Due to the large volume of tasks and environment data in BrowseComp, we performed a full-sample evaluation for the comparison results.

Instruction Set To ensure fidelity to the original benchmark and facilitate direct comparisons, we strictly preserved the semantic content of the original BrowseComp dataset. We reformatted the raw data verbatim into a standardized instruction-following format without any modification to the task definitions or evaluation criteria.

Formally, we define the instruction set as a collection of pairs $\mathcal{D} = \{(I_i, L_i)\}_{i=1}^N$, constructed via a direct mapping from the original source:

- **Instruction (I):** The original user query or task description, preserved exactly as it appears in the source dataset (e.g., *"Which team won the 2022 World Cup?"*).
- **Label (L):** The corresponding ground-truth answer or reference string used for evaluation.

This direct conversion ensures that the difficulty and scope of the tasks remain consistent with the original design, shifting the evaluation focus solely to the agent’s ability to retrieve information within our constructed local environment.

Tool Set To support the agent’s information retrieval within our local environment, we implemented a custom **Local Search Engine**. This tool allows agents to query the static corpus efficiently without external network requests.

Indexing and Retrieval Engine. The core retrieval mechanism utilizes the BM25Okapi algorithm. We preprocess the corpus using the NLTK library to perform tokenization, stemming (PorterStemmer), and stopword removal. To maintain efficiency with large corpora, we implemented a sharding strategy where the corpus is divided into managed shards, each with its own pre-computed BM25 model and text cache.

Smart Snippet Extraction. A critical component of our tool is the *Density-Based Smart Snippet Extraction* algorithm. Unlike naive approaches that return the first N characters of a document, our approach dynamically locates the

most relevant window of text based on query term density. The extraction process follows these steps:

1. **Hit Identification:** All occurrences of the query tokens within the document are identified.
2. **Cluster Optimization:** We employ a sliding window approach (Two Pointers algorithm) to identify the variable-length segment $[start, end]$ that maximizes the number of query term "hits" such that $(end - start) \leq L_{max}$, where L_{max} is the maximum snippet length (set to 20,000 characters).
3. **Context Expansion:** The window is recentered and expanded to fill the available token budget, ensuring that the returned snippet provides sufficient context around the relevant terms.

The search tool returns the top- k (default $k = 5$) results, containing the document title, source URL, and the extracting snippet.

Environment Set The environment set represents the static knowledge base available to the agent. We constructed this dataset using a hybrid approach to ensure both coverage and solvability.

Data Composition. Our corpus is derived from two sources:

- **Legacy Snapshots:** We directly integrated the 830 validated web snapshots provided by BrowseComp-Plus. These snapshots serve as the verified baseline for our environment, ensuring consistency with previous rectification efforts.
- **Active Completion via SOTA Agents:** The remaining tasks were previously classified by BrowseComp-Plus as unverifiable or unsolvable due to the expiration of original URLs or the lack of accessible web content. To achieve comprehensive benchmark coverage, we employed an active recovery strategy. referencing the official BrowseComp Leaderboard, we selected the current state-of-the-art models—**Gemini 3 Pro Preview** and **GPT-5**—and adapted them into autonomous web-browsing agents. These agents were tasked with re-searching the open web to identify valid, up-to-date URLs capable of resolving the previously broken tasks. We then crawled and snapshotted these newly verified sources to fully reconstruct the missing environment data.

Processing Pipeline. The raw HTML data collected from the new crawling phase underwent a rigorous cleaning pipeline to simulate a high-quality "Reader Mode" for the agents:

1. **Content Extraction:** We utilized Jina Reader and 'BeautifulSoup' to strip HTML tags, scripts, and styles.
2. **Noise Filtering:** A regex-based filtering module removed common web noise, including cookie notices, navigation bars, advertisement placeholders, and privacy policy disclaimers.
3. **LLM-Based Summarization:** To handle excessive context length while preserving information density, we applied an LLM-based summarization step (using GPT-4o).

The model was prompted with strict constraints to preserve all factual content, named entities, and procedural details while removing redundancy. The system prompt enforced an "information-preserving" objective to prevent hallucination or loss of critical data points required for the benchmark tasks.

The final *Active Completion* data is stored in a local .jsonl corpus.

Index Construction. Upon finalizing the data cleaning and merging processes, we aggregated the legacy snapshots and the newly recovered data into a unified corpus. To facilitate efficient and scalable local retrieval for the agents, we constructed a sharded search index using the following methodology:

1. **Preprocessing:** We applied a standard academic NLP preprocessing pipeline using the NLTK library. This included lowercasing, punctuation removal, stopword filtering (using NLTK's English list), and Porter Stemming to reduce token dimensionality and improve recall.
2. **Sharded Architecture:** To manage memory overhead and support parallelized retrieval, the unified corpus was partitioned into independent shards, with a default capacity of 20,000 documents per shard.
3. **Serialization:** For each shard, we computed a distinct BM25Okapi model. Both the inverted index model and the corresponding raw document storage were serialized (pickled) into a local file structure.

This architecture ensures that the *Local Search Engine* (described in Section H.4) can perform low-latency lookups across the entire dataset without requiring the entire corpus to be loaded into memory simultaneously.

H.5 MultiAgentBench

MultiAgentBench (Zhu et al. 2025a) is a multi-agent benchmark whose tasks are resolved through cooperation, competition, or social interaction among multiple agents with distinct roles. From its scenario set we migrate four representative ones into our framework: *bargaining*, *coding*, *database diagnosis (dbbench)*, and *research idea generation*. To integrate them, we (i) standardize heterogeneous scenario specifications into a unified JSONL instruction schema, (ii) re-implement every original scenario tool as a compatible Python function, (iii) materialise per-task environments as fully local resources, and (iv) describe the multi-agent topology declaratively through scenario-specific `Agent.jsonl` role manifests. Throughout this process, all instructions, tool logic, and environment data are taken verbatim from the original benchmark and only re-encoded into our unified schema; we manually verified that the migrated artefacts preserve the logic of the original release on a per-task basis, so any score difference reflects framework-level standardisation rather than changes to task content.

Correction to the Evaluation Metric Throughout this paper, agent capability is reported as the Task Completion Score (TCS) defined in Eq. 6: a per-task percentage in $[0, 100]$ averaged over the N tasks of a scenario. The original MultiAgentBench release reports a different per-scenario metric—which

we refer to as $TS^{(\text{orig})}$ —that follows different scaling conventions across scenarios and is not consistently expressed on the $[0, 100]$ percentage scale that TCS requires. Below we describe how $TS^{(\text{orig})}$ is computed scenario by scenario, and state the per-task mapping we apply to obtain a TCS value that is consistent with Eq. 6 across all four migrated scenarios.

Setup. The scoring rubrics, dimension counts, and value ranges below are all inherited from the original MultiAgentBench release; we apply them without modification and use them as inputs to our TCS computation. For a scenario with N tasks, let s_i denote the raw score that the LLM judge (under the upstream rubric) assigns to task i . For the rubric-based scenarios—*bargaining*, *coding*, and *research*—the upstream rubric scores each task on a 1–5 scale across D rubric dimensions (D scenario-specific, e.g. $D = 3$ for research), and we take the dimension-wise average per task

$$\bar{s}_i = \frac{1}{D} \sum_{d=1}^D s_{i,d} \in [1, 5].$$

For *dbbench*, the upstream task ships a ground-truth root-cause label and the score is the binary indicator $s_i \in \{0, 1\}$ of whether the agent’s prediction matches it; no rubric averaging applies.

TCS as used in this paper. TCS is defined as the per-task percentage averaged over the scenario (Eq. 6); the only scenario-specific choice is how a single task’s raw score is mapped to a $[0, 100]$ percentage before averaging. For the rubric-based scenarios, mapping the per-task rubric average $\bar{s}_i \in [1, 5]$ onto $[20, 100]$ via $TCS_i = \frac{\bar{s}_i}{s_{\max}} \cdot 100$ gives

$$\overline{TCS}^{(\text{ours})} = \frac{1}{N} \sum_{i=1}^N TCS_i = \frac{\sum_{i=1}^N \bar{s}_i}{N \cdot s_{\max}} \cdot 100, \quad (11)$$

with $s_{\max} = 5$. For *dbbench*, where $s_i \in \{0, 1\}$ is already a percentage-equivalent indicator, $TCS_i = s_i \cdot 100$ and

$$\overline{TCS}_{\text{dbbench}}^{(\text{ours})} = \frac{1}{N} \sum_{i=1}^N s_i \cdot 100 \in [0, 100]. \quad (12)$$

Both formulas are direct instantiations of the unified TCS definition in Eq. 6; they differ only in the per-task percentage mapping, which is dictated by the upstream rubric (1–5 scale) or label (binary) and not chosen by us.

Instruction Set The original MultiAgentBench releases scenario data in heterogeneous formats (negotiation transcripts, code prompts, SQL anomaly descriptions, research seed papers). We unify them by re-encoding every task instance into a single line of `Benchmark/MultiAgentBench/<scenario>/*_merged_clean.jsonl` (or the equivalent `*_standardized_merged.jsonl`) consisting of two fields:

- **task_id**: a stable integer identifier used by the framework to bind the task to its environment slice and (where applicable) its per-task agent file.

- **instruction**: a single self-contained natural-language prompt that aggregates the original task description, scenario constraints, and tool-usage guidance.

Bargaining. Each instruction frames a multi-party negotiation around a real product (e.g. a replacement remote control), explicitly specifies that buyers prioritise scalability and premium features while sellers seek margin, and instructs agents to use the bargaining toolkit (offer / counter / inquire / accept / end). Hidden parameters such as buyer/seller target prices, walk-away thresholds, and personality traits are routed into the corresponding agent’s role specification (Section H.5) rather than the public instruction, so that information asymmetry is preserved.

Coding. The instruction concatenates the original content (program description), requirements (functional spec) and constraints into one “Software Development Task” block. The label is implicit: a successful solution is the `solution.py` file that the agent team writes into its workspace, which is then graded against the per-task reference solution (Section H.5) by the LLM judge.

Database. Each instruction describes the application context (e.g. a music streaming platform), summarises the schema, and asks the multi-agent team to identify the root cause of a performance regression. The candidate root-cause taxonomy is taken from the same DBA-style classification used by the original benchmark (anomalies in bulk insertion, lock contention, vacuum activity, redundant indexes, inefficient query plans, etc.), and the diagnostic team is structured as a panel of analysts (Section H.5) that collectively cover this taxonomy. The instruction also fixes the agent topology: a Manager dispatches the diagnostic effort to the analyst panel and aggregates their reports.

Research. Each instruction is a structured “Dear Research Team” brief that bundles the introduction and related-work section of a real paper as the seed, and asks the team to produce a novel research idea that goes beyond the seed work. Because every task in this scenario binds to a unique panel of researcher personas, we additionally serialise per-task agent definitions into `Agent/MultiAgentBench/research/task_<id>.jsonl` (100 files), keyed by the same `task_id`.

Tool Set The tool implementations are migrated directly from the original MultiAgentBench release with the internal task logic preserved; we re-encode each action as a stateless Python function decorated with `@tool`, exposing explicit type-annotated arguments and structured return dictionaries so that the unified `ToolCallingAgent` can invoke them through our framework. Necessary lightweight adaptations are limited to interface-level changes (e.g. rerouting file I/O to per-task environments), without altering the underlying tool semantics. Tools are loaded on demand through the `per-agent tools` field of `Agent.jsonl`.

Bargaining. Six tools implement the negotiation protocol from the original benchmark: `offer_price` and `reject_and_counter` for reasoned proposals and counter-offers, `provide_information` and `inquire_`

intentions for sharing or eliciting product details and stance, `accept_offer` for finalising a deal, and `end_negotiation` for terminating without agreement. Each tool preserves the original return schema (`success`, `offered_price`, `reason`, ...), so that subsequent agents can reason over the public negotiation history without parsing free-form chat.

Coding. The coding toolkit covers the full development lifecycle as specified in the original benchmark: `create_solution` bootstraps `solution.py` from the task description, `create_file` manages auxiliary files, `analyze_task` and `decompose_task` structure the work, `write_test_case` produces tests, `review_code` and `revise_code` drive iterative refinement, and `execute_code` and `code_debugger` provide runtime feedback. The execution semantics are unchanged from the original release; we only adapt the file I/O layer so that every write is scoped to the per-task workspace directory described in Section H.5.

Database. Five diagnostic tools—`analyze_insert_large_data`, `analyze_lock_contention`, `analyze_vacuum_activity`, `analyze_redundant_indexes`, and `analyze_select_performance`—replicate the original DBA-style analyses. The diagnostic logic and the candidate root-cause taxonomy are taken from the upstream toolkit; we adapt only the data-acquisition layer, instrumenting per-task SQLite execution to produce JSONL traces (`ops_log.jsonl`, `db_metrics.jsonl`, `trace_log.jsonl`) that capture the statement timing, lock-wait, and page-level signals required by the diagnostics. Each tool returns a structured natural-language report ranked by elapsed time, row counts, and contention statistics, identical in schema to the upstream output.

Research. The five retrieval tools—`get_related_papers`, `get_recent_papers`, `collect_publications_and_coauthors`, `get_paper_by_keyword`, and `get_paper_by_arxiv_id`—are implemented in two interchangeable variants that share identical call signatures, argument schemas, and return formats:

- **Online:** a faithful re-implementation of the original retrieval surface, calling `arxiv.Search` for paper search, `requests+BeautifulSoup` for arXiv HTML/PDF parsing, and the Semantic Scholar references endpoint for citation expansion. This variant preserves the original retrieval logic and is provided for direct comparison with the upstream benchmark.
- **Offline:** the same retrieval surface backed by a curated local paper repository (Section H.5), with a BM25-weighted inverted index that returns ranked `Paper` objects functionally equivalent to those produced by the online variant. This variant is deterministic and network-free, supporting reproducible evaluation.

Because the two variants are interchangeable at the tool-interface level, switching between them requires only a single `Toolkit` path change in the scenario YAML, with no

changes to instructions, agent definitions, or downstream tool consumers. The default toolkit used in our framework is the offline variant; the online variant is retained for upper-bound calibration and reproducibility comparisons against the original benchmark.

Idea generation itself is performed through the agent team’s natural-language outputs rather than through a dedicated tool—the toolkit only exposes retrieval, while ideation and synthesis are delegated to the language model, matching the upstream benchmark’s design.

Environment Set MultiAgentBench environment data is organized per scenario and instantiated per task to guarantee isolation and reproducibility. Each scenario’s environment is materialised from the original benchmark’s task definitions, with the underlying task content and ground-truth artefacts preserved verbatim; the framework only adapts how environment state is loaded, isolated, and reset across tasks.

Bargaining. The bargaining scenario is a pure multi-agent interaction with no external environment data: each task is fully specified by the buyer/seller role specifications (product, target prices, walk-away thresholds, personality traits), and the agents drive the negotiation entirely through tool calls (`offer_price`, `reject_and_counter`, `accept_offer`, etc.). No per-task environment is required, and isolation is guaranteed by re-initialising agent memory between tasks.

Coding. For each task we materialise an isolated workspace, in which a per-task target file serves both as the agent team’s editable artefact and as the reference solution consumed by the LLM judge. The reference solution is taken directly from the upstream benchmark’s task definition; per-run timestamped subdirectories isolate concurrent or sequential evaluation runs from each other on disk, while the reference content for a given task is identical across runs.

Database. For each original task, we materialise an isolated per-task directory that bundles:

- `init.sql` – the normalised schema and seed data, taken verbatim from the original task definition;
- `database.sqlite` (plus `-wal` / `-shm`) – a freshly built SQLite instance with WAL journaling enabled, populated by replaying the upstream `init.sql`;
- `ops_log.jsonl` – per-statement execution records (`started_at`, `ended_at`, `duration_ms`, `kind`, `full_scan`, `est_rows`, `error`), produced by replaying the original task’s operation sequence (statement order, parameters, and injected anomaly events) and tracing each statement through `sqlite3`;
- `db_metrics.jsonl` – periodic snapshots of `page_count`, `freelist_count`, and `journal_mode`, captured during the same replay;
- `trace_log.jsonl` – low-level execution traces for index-usage analysis, captured during the same replay;
- `execution_summary.json` – aggregated statistics per statement kind, derived from the above logs;

- `anomalies/` – the labelled root-cause artefacts (e.g. `insert_large_data.json`) shipped with the original benchmark, consumed by the judge but hidden from the agents.

The original benchmark uses a Postgres-backed deployment and exposes diagnostic signals through `pg_stat_statements` and `pg_locks`; we re-host the same task assets—schema, seed data, operation sequences, anomaly injection, and root-cause labels—on an instrumented SQLite engine to remove the operational dependency on a live database server. The engine substitution is benign for this benchmark because each diagnostic task is identified by a coarse-grained root-cause label (e.g. `INSERT_LARGE_DATA`, `LOCK_CONTENTION`, `REDUNDANT_INDEX`) whose signature manifests at the level of statement timing, scan patterns, lock-wait events, and index usage—signals that both engines surface and that our SQLite tracer captures by replaying the upstream operation sequence verbatim. The diagnostic tools therefore observe the same statement-level evidence and assign the same root-cause label as in the original Postgres deployment, while the underlying execution layer becomes fully local and reproducible.

Research. The research environment is centred on a curated local paper repository, containing 2,598 unique papers covering the same arXiv and Semantic Scholar sources used by the original benchmark, indexed across `title`, `abstract`, `introduction`, `sections`, `authors`, `keywords`, `domain`, `bibliography`, and `full_text`.

Corpus construction. The corpus is bootstrapped by running advanced LLM-driven crawlers—with Gemini-3-Pro and GPT-5 as the underlying agents—to retrieve, parse, and expand papers referenced or implied by each task’s seed paper, drawing from arXiv (HTML/PDF parsing for per-section text and bibliography) and the Semantic Scholar references endpoint (citation expansion). The raw crawl is then merged with previously collected records by an identity-tuple-based deduplication that prefers the most populated record on collision, after which a manual verification pass corrects parsing errors and fills in missing papers.

On-disk forms. The verified corpus is materialised in three coordinated forms backing the same retrieval interface: a canonical JSON / JSONL record set as the source of truth, a SQLite store with a BM25-weighted FTS5 inverted index over the six text fields (title weighted highest, followed by abstract, authors, domain, keywords, and full text) for primary retrieval, and a flattened search corpus with field-level metadata for auditing and non-SQLite consumers. Per-tool query/result snapshots are additionally cached so that repeated invocations of `get_related_papers`, `get_recent_papers`, and `get_paper_by_keyword` return byte-identical results across evaluation runs.

Retrieval and tools. The five research tools share a single retrieval engine that normalises and expands the query (stop-word filtering, multi-token phrase extraction, and a small domain-synonym table), retrieves candidates via BM25 with

a graceful LIKE-based fallback when FTS5 is unavailable, and reranks by exact phrase matches, token overlap, domain affinity, author hits, and logarithmic recency / citation bonuses. All five tools share the same scoring, the same backing store, and the same deterministic guarantees. At runtime, the offline retrieval toolkit reads exclusively from this local store, removing all network dependencies; the upstream online crawl is preserved as a regeneration pipeline for refreshing the corpus when needed.

Design intent. Taken together, the construction, indexing, and retrieval pipeline is designed to approximate the behavioral surface that a live academic search engine exposes to an agent: lexical retrieval over title-and-abstract anchors, BM25-style relevance ranking, recency and citation-aware tie-breaking, and stable handling of domain abbreviations and author lookups. The local store is therefore not a simplified stand-in but an offline reconstruction of the same retrieval signals that the online benchmark relies on, with determinism added as a property the live web cannot provide.

Multi-Agent Structure The agent topologies of all four migrated scenarios are inherited from the original MultiAgentBench release; our contribution at this layer is to express them as declarative artefacts in a per-scenario `Agent.jsonl` manifest, where each line specifies one agent’s name, public role description, accessible tools, and—for orchestrator agents—the list of subordinates that defines its outgoing edges. At start-up, our framework parses this file, instantiates one `ToolCallingAgent` per record, attaches the resolved tool callables, and wires routing through the declared adjacency list. Two topology families emerge:

Bargaining (chained peer topology). The bargaining scenario has no central orchestrator: four peer agents (`Agent1–Agent4`) are wired into a forward-chained graph—`Agent1 → {Agent2, Agent3, Agent4}`, `Agent2 → {Agent3, Agent4}`, `Agent3 → {Agent4}`—with `Agent1` as the entry agent that receives the user instruction. The framework’s routing layer enforces the declared edges, so each agent only forwards to its declared successors and the negotiation terminates when `Agent4` either accepts an offer or invokes `end_negotiation`. All four agents share the same six negotiation tools and each carries a role specification (buyer or seller, target price, walk-away threshold, personality traits) sourced from the original task definition and materialised through the agent’s `system_prompt` field at runtime.

Coding, dbbench, research (Manager–Agent star topology). The remaining three scenarios share a star structure in which a central `Manager` (with empty tools and a populated `node list`) decomposes the task, dispatches to its subordinate agents, and aggregates the final answer. The `Manager` itself carries no role specification; only its workers do. The fan-out and per-agent specialisation differ across scenarios:

- *coding* – `Manager → {Agent1, Agent2, Agent3}`, with role-specialised behavior specs for the framework bootstrapper, the gap filler, and the optimiser/debugger

respectively, together with call-ordering guidance among them.

- **dbbench** – Manager $\rightarrow \{\text{Agent1}, \dots, \text{Agent5}\}$, organized as a panel of five DBA-style analysts. The five analysts collectively cover the upstream benchmark’s root-cause taxonomy (Section H.5): each owns one diagnostic specialisation and is restricted, through its role specification, to one of the five analysis tools defined in Section H.5, while the Manager coordinates their reports and emits the final root-cause label.
- **research** – Manager $\rightarrow \{\text{Agent1}, \dots, \text{Agent5}\}$, where each task ships its own `task_<id>.jsonl` and the five researcher agents share the full retrieval toolkit but receive distinct per-task role specifications carrying author biographies extracted from the seed paper.

The role specifications, agent fan-outs, tool assignments, and call-ordering relations all originate in the upstream MultiAgentBench task definitions; the migration step re-encodes them into the `Agent.jsonl` schema without altering role assignments or inter-agent dependencies.

H.6 Agent-SafetyBench

To demonstrate the extensibility of our framework in the domain of AI safety research, we migrated the **Agent-SafetyBench**. This benchmark evaluates the safety of agents across diverse scenarios by analyzing both their textual responses and tool-use behaviors. Our adaptation ensures that the logical integrity of the original tasks is preserved while enabling dynamic execution within our secure sandbox.

Instruction Set We formalized the raw data into a structured instruction set, where we introduced specific fields to handle the heterogeneity of the safety tasks:

- **Instruction:** The original safety tasks were mapped directly to the instruction field.
- **Tools:** Agent-SafetyBench defines a unique subset of tools for each task. Our framework adapts to this by dynamically loading the specific tool according to this *tools* field required for each instruction.
- **Environment Path:** We introduced an environment path field. This allows the framework to identify, load, and instantiate a replica of the specific environment data into the sandbox before the agent begins interaction.

Tool Set The original benchmark provided tool definitions in static JSON format. To enable execution within our Python-based agent framework, we implemented an automated **Tool Transpilation Pipeline**. This system procedurally generates executable Python code from the JSON schemas, ensuring compatibility with standard agent libraries.

The conversion process involves four critical transformations:

1. **Type System Bridging:** We map JSON Schema types to Python’s static type hints to facilitate proper argument parsing. This includes recursive handling of complex structures, such as transforming JSON `array` types with typed items into Python `List[T]` generics (e.g.,

`List[str]`, `List[int]`), and mapping object types to `dict`.

2. **Semantic Docstring Generation:** To ensure the LLM agent accurately understands tool usage, the transpiler constructs comprehensive docstrings. It aggregates the tool description, argument descriptions, and required/optional status into a standardized format. This "prompt-ready" documentation allows the agent to infer the correct call signature directly from the function definition.
3. **Dynamic State Binding:** Unlike static function calls, our generated tools possess context-awareness. The generated code includes logic to dynamically import the corresponding environment class and invoke `load_environment_data()` at runtime. This allows the tool to instantiate a localized version of the environment state (merging data parameters) specific to the current task before executing the logic.
4. **Exception Encapsulation:** To prevent agent crashes during exploration, the transpiler wraps the execution logic in robust `try-except` blocks. Runtime errors (such as `KeyError` from missing data or `AttributeError` from schema mismatches) are caught and formatted as informative string feedback, enabling the agent to self-correct rather than terminating the session.

Logic Preservation. Crucially, while the interface was adapted to satisfy the requirements of the Python-based agent framework, the underlying functional logic of the tools remains invariant. The generated Python wrappers serve as an interface layer that delegates the actual execution to the original benchmark’s logic (via the `env_instance.call_tool` method). This design ensures that the simulation fidelity—specifically how tools interact with the environment states and the side effects they produce—is identical to the original Agent-SafetyBench, thereby preserving the validity of the safety evaluation results.

Robustness Enhancements. During migration, we identified brittleness in the original tool implementations, specifically regarding direct dictionary key access (e.g., `'data["key"]'`) which caused runtime crashes on malformed inputs. We performed manual corrections to replace these with safe access methods (e.g., `'get("key")'`). This ensures the tools remain robust during execution and can gracefully handle edge cases in the environment data.

Environment Set A significant challenge in the original Agent-SafetyBench structure was data redundancy; environment states (such as a directory of files or a list of emails) were often duplicated across multiple tasks.

To optimize storage and initialization efficiency, we implemented a **Data Aggregation and De-duplication** strategy:

- **Clustering:** We grouped tasks that share the same underlying domain (e.g., all tasks operating on the *Email* environment are clustered together).
- **Unified Instantiation:** Instead of creating fragmented environment instances for every single task, we aggregated the data into unified environment files. For example, all email-related records were merged into a single consistency-checked dataset.

This restructuring allows our framework to instantiate a single, comprehensive environment object that can serve multiple query variations, significantly reducing setup overhead.

Evaluation To ensure our results are directly comparable to the original baselines, we strictly adhered to the evaluation Protocol defined by Agent-SafetyBench.

ShieldAgent Evaluator. We utilized the Agent-SafetyBench’s original score model *ShieldAgent* model as the safety judge. The evaluation process involves a critique loop where the judge analyzes the full interaction history, including:

- The user’s query (safety probe).
- The agent’s textual response.
- The agent’s tool invocations and the resulting environment observations.

Prompt Consistency. We employed the exact safety evaluation prompt from the original implementation to prevent prompt-sensitivity bias. The evaluator classifies the interaction as either **Safe** or **Unsafe**. Finally, we report the safety scores across different models.

I Examples and Prompts

This appendix provides comprehensive examples and detailed specifications for reproducing experiments within our unified framework. We present both system-level and agent-level configuration templates , followed by the complete set of evaluation prompts used across all benchmarks. These materials are essential for ensuring full reproducibility and enabling researchers to adapt the framework to new evaluation scenarios.

I.1 System Configuration File

Example and Explanation of the System Configuration File

```
1 # =====
2 # Agent Sandbox and Evaluation - Complete Configuration Template
3 # =====
4 # This file contains all available configuration options with detailed
   comments.
5 # Use this as a reference when creating your own configuration files.
6
7 # =====
8 # 1. Benchmark Configuration
9 # =====
10 # Defines the benchmark tasks to execute
11 Benchmark:
12 # Path to the benchmark file (.jsonl, .json, or .yaml)
13 path: ./Benchmark/AgentBench/dbbench/standard.jsonl
14
15 # Task type - determines how agents interact with tasks
16 # Options:
17 #   - "single-agent task": Single-round interaction with one agent
18 #   - "single-agent multi-round": Multi-round conversation with one agent
19 #   - "multi-agent task": Multiple agents collaborate on a task
20 #   - "multi-agent multi-round": Multi-agent with multiple rounds of
   interaction
21 type: single-agent multi-round
22
23 # Whether to use per-task tools (tools specific to each task)
24 # If true, expects tools in Toolkit/[dataset_name]/task_[id]/ directories
25 per_task_tools: false
26
27 # Optional: Task range to execute (1-based indexing)
28 # Leave as null to execute all tasks
29 start_idx: null # Start from first task
30 end_idx: null # Execute through last task
31
32 # Example with specific range:
33 # start_idx: 10
34 # end_idx: 20
35
36
37 # =====
38 # 2. Toolkit Configuration
39 # =====
40 # Defines where to find the tools/functions available to agents
41 Toolkit:
42 # Path to the toolkit directory containing tool definitions
43 path: ./Toolkit/AgentBench/dbbench
44
45 # Optional: Custom tool loader script (if not using default)
46 # loader: ./Toolkit/custom_loader.py
47
48
49 # =====
50 # 3. Environment Configuration
51 # =====
52 # Defines the execution environment for tasks
```

```

53 Environment:
54 # Path to environment resources (databases, files, etc.)
55 path: ./Environment/AgentBench/dbbench
56
57 # Environment type determines how environments are managed
58 # Options:
59 # - null: No environment setup needed
60 # - "global": One shared environment for all tasks
61 # - "per-task": Each task gets its own isolated environment
62 # (Environment paths must be specified in benchmark file)
63 type: per-task
64
65
66 # =====
67 # 4. Model Configuration
68 # =====
69 # Defines which language model(s) to use and their settings
70 Model:
71 # Active provider - which provider configuration block to use
72 # Options: openai-server, transformers, vllm, anthropic, etc.
73 provider: openai-server
74
75 # Global parameters applied to all providers (can be overridden per
76 # provider)
77 parameters:
78     temperature: 0.0 # Sampling temperature (0.0 = deterministic)
79     top_p: null # Nucleus sampling (null = disabled)
80     max_tokens: 4096 # Maximum tokens to generate
81     timeout: 60 # Request timeout in seconds
82     # do_sample: true # Whether to use sampling (for some models)
83
84 # Provider-specific configurations
85 providers:
86     # OpenAI-compatible API server (including proxies)
87     openai-server:
88         model_id: gpt-4o-mini # Model identifier
89         api_base: http://xxx.xxx.xxx.xxx:xxxx/v1 # API endpoint
90         api_key: "your-api-key-here" # API authentication
91         key
92         organization: null # Optional: OpenAI
93         org ID
94         project: null # Optional: OpenAI
95         project ID
96         client_kwargs: {} # Additional client
97         arguments
98
99     # Hugging Face Transformers (local models)
100     transformers:
101         model_id: meta-llama/Llama-3.1-8B-Instruct # Model path or HF
102         hub ID
103         device: cuda # Device: cuda, cpu
104         , mps
105         torch_dtype: float16 # Model precision
106         load_in_8bit: false # Use 8-bit
107         quantization
108         load_in_4bit: false # Use 4-bit
109         quantization

```

```

101     trust_remote_code: true                                # Allow custom
model code
102     use_flash_attention: false                             # Enable flash
attention
103
104     # vLLM (high-performance serving)
105     vllm:
106         model_id: meta-llama/Llama-3.1-70B-Instruct        # Model to serve
107         tensor_parallel_size: 4                             # Number of GPUs
108         dtype: float16                                     # Model precision
109         gpu_memory_utilization: 0.9                         # GPU memory usage
110         max_model_len: 8192                                # Maximum context
length
111     trust_remote_code: true                                # Allow custom code
112
113     # Anthropic Claude models
114     anthropic:
115         model_id: claude-3-5-sonnet-20241022                # Claude model
version
116         api_key: "your-anthropic-api-key"                  # Anthropic API key
117         max_tokens: 4096                                    # Max output tokens
118
119
120 # =====
121 # 5. Agent Configuration
122 # =====
123 # Defines the agent(s) that will execute tasks
124 Agent:
125     # Agent type - must match the Benchmark type
126     # Options:
127     #     - "single-agent": Single agent for all tasks
128     #     - "single-agent multi-round": Single agent with multi-turn capability
129     #     - "multi-agent": Multiple cooperating agents
130     type: single-agent
131
132     # Path to agent definition file (.jsonl format)
133     # Contains agent prompts, roles, and configurations
134     agent_dir: ./Agent/AgentBench/dbbench/Agent.jsonl
135
136     # Agent implementation type
137     # Options:
138     #     - "ToolCallingAgent": Uses native function calling (recommended)
139     #     - "CodeAgent": Generates and executes Python code
140     agent_type: ToolCallingAgent
141
142     # Whether to stream agent outputs in real-time
143     stream_outputs: false
144
145     # Planning interval: how often agent should create execution plans
146     # -1 = use default intervals, 0 = no planning, N = plan every N steps
147     planning_interval: -1
148
149     # Maximum number of tools that can execute in parallel
150     max_tool_threads: 1
151
152     # Whether to give agents access to all tools or only specified ones
153     fill_with_all_tools: false

```

```

154
155 # For multi-agent systems: which agent receives the initial task
156 entry_agent_name: Agent
157
158 # Maximum retry attempts for failed tool calls
159 max_attempts: 3
160
161
162 # =====
163 # 6. Output Configuration
164 # =====
165 # Defines where and how to save results
166 Output:
167 # Directory for detailed execution logs
168 log_dir: ./Results/logs/AgentBench/dbbench
169
170 # Directory for structured output files (JSON/JSONL)
171 save_dir: ./Results/outputs/AgentBench/dbbench
172
173 # Optional: Path to save evaluation metrics summary
174 eval_results: ./Results/metrics.json
175
176 # Optional: Whether to include environment snapshots in output
177 include_environment: false
178
179 # Optional: Where to archive environment states
180 environment_archive_dir: ./Results/environment/AgentBench/dbbench
181
182
183 # =====
184 # 7. Evaluation Configuration (for eval_best.py)
185 # =====
186 # Defines how to evaluate agent performance using eval_best.py script
187 Evaluation:
188 # Evaluation type - determines which evaluation method to use
189 # Options:
190 # - "actions": Environment state-based evaluation (hash comparison)
191 # - "llm": LLM judge-based evaluation (semantic understanding)
192 # - "both" or "all": Use both methods (combined scoring)
193 type: actions
194
195 # Directory to save evaluation results (.jsonl files)
196 save_dir: ./Evaluation/results
197
198 # LLM Judge Configuration (required only when type is "llm", "both", or "
199 # all")
200 # Used to evaluate tasks that don't have deterministic ground truth
201 server:
202 # Model identifier for the judge
203 model_id: gpt-4o
204
205 # API endpoint
206 api_base: https://api.openai.com/v1
207
208 # API authentication key
209 api_key: "your-api-key-here"

```

```

210     # Path to evaluation prompt template (YAML file)
211     # Template should contain 'system' and 'evaluate' fields
212     # The 'evaluate' field can use placeholders: {instruction}, {label}, {
final_memory}, {result}, {log}
213     judge_prompt_template: Evaluation/prompt_templates/xxx.yaml
214
215     # Optional: Direct system prompt (overridden by template if provided)
216     system: "You are an expert evaluator assessing agent task performance."
217
218     # Optional: Direct evaluation template (overridden by template file if
provided)
219     evaluate:
220         "Task: {instruction}
221           Expected: {label}
222           Agent Result: {result}
223
224           Evaluate the agent's performance and return JSON:
225           {{score: 0.0-1.0, reasoning: explanation}}"
226
227
228 # =====
229 # Result Configuration (for eval_best.py log discovery)
230 # =====
231 # These settings help eval_best.py automatically find and filter logs
232 Result:
233     # Directory containing execution logs
234     log_dir: ./Results/logs/AgentBench/dbbench
235
236     # Directory containing result output files
237     save_dir: ./Results/outputs/AgentBench/dbbench
238
239     # Directory where environment archives are stored (post-execution)
240     environment_archive_dir: ./Results/environment/AgentBench/dbbench
241
242     # Optional: Run timestamp for filtering specific runs
243     # Format: YYYYMMDD_HHMMSS (e.g., 20260128_120000)
244     # If specified, eval_best.py will only evaluate logs matching this
timestamp
245     run_timestamp: null
246
247     # Optional: Model identifier for filtering specific model runs
248     # If specified, eval_best.py will only evaluate logs matching this model
249     model_tag: null
250
251
252 # =====
253 # 8. Execution Configuration
254 # =====
255 # Controls parallel execution and performance
256 Execution:
257     # Maximum number of tasks to run in parallel
258     # Adjust based on your system resources and API rate limits
259     max_workers: 8
260
261     # Optional: Timeout per task (seconds)
262     # task_timeout: 300
263

```

```

264 # Optional: Whether to continue on task failures
265 # continue_on_error: true
266
267
268 # =====
269 # Notes:
270 # =====
271 # 1. All paths can be relative (to project root) or absolute
272 # 2. JSONL files should have one JSON object per line
273 # 3. For per-task tools/environments, benchmark file must include paths
274 # 4. API keys should be kept secure (use environment variables in
    production)
275 # 5. Adjust max_workers based on API rate limits and system resources
276 # 6. Not all sections are required - minimal config needs: Benchmark, Model
    , Agent

```

I.2 Agent Configuration File

Example and Explanation of the Agent Configuration File

```

1  =====
2  Agent Configuration Template - Full Field Reference
3  =====
4  This template lists all configurable Agent fields with detailed
    explanations.
5  Supported agent types: ToolCallingAgent, CodeAgent
6  =====
7
8  ===== Required Fields =====
9
10 "name": "Agent",
11 Description: Unique identifier of the agent.
12 Type: string
13 Required: Yes
14 Examples: "DatabaseExpert", "DataAnalyst", "ResearchAssistant"
15 Note: In multi-agent settings, this name is used for agent references and
    delegation.
16
17 ===== Basic Configuration =====
18
19 "description": "A helpful assistant that can use tools to complete tasks.",
20 Description: Functional description of the agent.
21 Used as the default system prompt if system_prompt is not provided.
22 Type: string
23 Required: No
24 Default: Empty string
25 Example: "Expert database query assistant with SQL expertise"
26 Priority: instructions > system_prompt > description > global defaults
27
28 "agent_type": "ToolCallingAgent",
29 Description: Specifies the agent implementation type, which determines its
    behavior.
30 Type: string
31 Required: No
32 Default: "ToolCallingAgent"
33 Options:

```

```
34 - "ToolCallingAgent": Calls predefined tools (recommended for most
    benchmarks)
35 - "CodeAgent": Generates and executes Python code (e.g., data analysis
    tasks)
36 Note: Different agent types support different configuration fields.
37
38 "system_prompt": "You are a helpful assistant with expertise in various
    tasks.",
39 Description: System-level prompt defining the agent's role, behavior, and
    capabilities.
40 Type: string or path (file path)
41 Required: No
42 Default: Falls back to description or global configuration
43 Example 1 (inline text): "You are an expert database administrator..."
44 Example 2 (file path): "./Agent/prompts/my_prompt.txt"
45 Notes:
46 - If a file path is provided (.txt, .md), the content is loaded
    automatically
47 - Overrides description
48 - Multi-line text is supported
49
50 ===== Tool Configuration =====
51
52 "tools": ["tool1", "tool2", "tool3"],
53 Description: List of tools accessible to the agent.
54 Type: array of strings or null
55 Required: No
56 Default: null
57 Example: ["execute_sql", "describe_table", "show_tables"]
58 Tool selection logic:
59 - If tools is specified: only listed tools are available
60 - If tools is null and fill_with_all_tools=true: all tools are assigned
61 - If tools is null and fill_with_all_tools=false: no tools are assigned
62 Note: Tool names must be defined in the Toolkit configuration.
63
64 ===== Execution Control =====
65
66 "max_steps": 20,
67 Description: Maximum number of execution steps allowed for the agent.
68 Type: integer
69 Required: No
70 Default: 20
71 Note: Execution stops once this limit is reached.
72
73 "planning_interval": 3,
74 Description: Step interval at which the agent performs explicit planning.
75 Type: integer or null
76 Required: No
77 Default: null (planning disabled)
78 Examples:
79 - null: disable planning
80 - -1: use framework default
81 - 3: plan every 3 steps
82 - 5: plan every 5 steps
83 Note: Planning improves task coherence but increases token usage.
84
85 "max_tool_threads": 1,
```

```
86 Description: Maximum number of concurrent tool execution threads.
87 Type: integer
88 Required: No
89 Default: 1
90 Examples:
91 - 1: sequential execution (safe, recommended)
92 - 2-4: parallel execution (requires tool support)
93 Note: Some tools may not support concurrency.
94
95 ===== Output Control =====
96
97 "stream_outputs": true,
98 Description: Whether to stream agent outputs in real time.
99 Type: boolean
100 Required: No
101 Default: true
102 Use case: Enables real-time inspection of agent execution.
103
104 ===== Multi-Agent Configuration =====
105
106 "node": ["SubAgent1", "SubAgent2"],
107 Description: List of child agents for hierarchical multi-agent setups.
108 Type: array of strings or null
109 Required: No (only for multi-agent scenarios)
110 Default: null
111 Example: ["DevLead", "QALead"]
112 Use cases:
113 - Define agent hierarchies
114 - Enable task delegation from parent to child agents
115 Note: Referenced agent names must exist in the same configuration file.
116
117 ===== CodeAgent-Specific Fields =====
118
119 "additional_authorized_imports": ["numpy", "pandas", "matplotlib", "scipy
    "],
120 Description: Additional Python libraries allowed for CodeAgent execution.
121 Type: array of strings
122 Required: No (CodeAgent only)
123 Default: []
124 Examples: ["numpy", "pandas", "sklearn", "torch"]
125 Notes:
126 - Effective only when agent_type = "CodeAgent"
127 - Libraries must be installed in the runtime environment
128 - Potentially unsafe libraries (e.g., os, sys, subprocess) are discouraged
129
130 "max_iterations": 10,
131 Description: Maximum number of code execution iterations.
132 Type: integer
133 Required: No (CodeAgent only)
134 Default: 10
135
136 "code_execution_timeout": 30,
137 Description: Timeout (in seconds) for a single code execution.
138 Type: integer
139 Required: No (CodeAgent only)
140 Default: 30
141
```

```

142 ===== Advanced Configuration =====
143
144 "prompt_templates": "./Agent/templates/my_templates.yaml",
145 Description: Path to custom prompt template definitions.
146 Type: string (file path) or null
147 Required: No
148 Default: null
149 Example: "./Agent/templates/research_assistant_templates.yaml"
150 Use cases:
151 - Customize prompts for different agent stages
152 - Includes planning, tool-calling, and final response templates
153 Note: Template file must be a valid YAML file.

```

I.3 Other Prompts

Judge Prompt of AgentBench Database

```

1  system: |
2    You are an impartial judge. Your task is to determine whether the
   assistant's final output fully satisfies the given instruction.
3    You MUST return a valid JSON object with keys "score" (0 or 1) and "
   explanation" (a short justification).
4    Do not include any extra text outside JSON.
5
6  evaluate: |
7    You will be given:
8    - The task instruction ('Instruction')
9    - The expected correct output ('expectedoutcome')
10   - The assistant's final output ('Agent final output')
11   - Optional memory ('Memory')
12
13   Your job is to determine whether the assistant correctly completed the
   task.
14
15   ## Scoring Rules
16
17   1. Output MUST be valid JSON:
18     {{
19       "score": 0 or 1,
20       "explanation": "short reason"
21     }}
22
23   2. Award 'score = 1' ONLY IF the assistant's final output:
24     - Fully satisfies the Instruction
25     - Matches the expectedoutcome
26     - Contains no contradictions, hallucinations, or missing required
   information
27     - Does not include irrelevant or fabricated content
28
29   Otherwise, assign 'score = 0'.
30   ## Evaluation Criteria by expectedoutcome Type
31
32   ### 1. If the lable is an SQL statement
33   (i.e., lable starts with an SQL verb like SELECT / INSERT / UPDATE /
   DELETE / WITH / CREATE / DROP / ALTER)
34
35   To get score=1, **all** of the following conditions must be met:

```

```

36  * **SQL Match** : The Memory must show a tool call executing an SQL
    statement that *exactly* matches the SQL in the lable (minor case and
    whitespace differences are acceptable).
37  * **Tool Success** : The Memory must indicate that the SQL tool call
    executed *successfully* (e.g., no database errors).
38  * **Correct Response** : The assistant's final output must be correct and
    accurately reflect the data or result returned from the successful SQL
    execution.
39
40  If any of these conditions are not met, the score=0.
41
42  ### 2. If the lable is non-SQL text
43
44  To get score=1, *all* of the following conditions must be met:
45  * **Semantic Match** : The assistant's final output must be semantically
    consistent with the reference answer(s) in the lable.
46  * **Log Consistency** : The final output must be consistent with any tool
    calls (e.g., search, computation) and their results as recorded in the
    log.
47
48  If the final output is semantically incorrect or contradicts the log, the
    score=0.
49
50  Instruction:
51      {instruction}
52
53  expectedoutcome:
54      {label}
55
56  Agent final output:
57      {result}
58
59  Memory:
60      {final_memory}

```

Judge Prompt of AgentBench Knowledge Graph

```

1  system: |
2  You are an impartial judge specialized in Knowledge Graph (KG) reasoning.
3  Your task is to determine if the assistant's response correctly extracts
    the requested entities or values from the graph.
4  Respond with VALID JSON only: {"reasoning": "a short explanation", "
    score": 1 or 0, "explanation": "brief reason"}}
5  Always reply in strict JSON format.
6
7  evaluate: |
8  You will be given a task instruction, the assistant's final response,
    reference answers (lable), and the assistant's tool execution log (log).
9
10  ## Scoring Rules
11  1. **JSON Output** : Your reply must be valid JSON with keys "score" (0 or
    1) and "explanation".
12  2. **Score=1 Standard** : The response must be fully accurate, contain the
    required Entity IDs or Numbers, and align perfectly with the tool
    execution steps in the log.
13

```

```

14  ## KG Evaluation Criteria
15
16  ### 1. Entity ID / List Match
17  * If the 'lable' contains KG Entity IDs (e.g., ["m.0xxxx"]):
18    * **Direct Match**: The 'response' or the 'final_answer' call in the '
      log' must contain these exact IDs.
19    * **List Completeness**: For multiple answers, the assistant must have
      identified ALL IDs listed in the 'lable'. Missing any ID results in
      score=0.
20
21  ### 2. Numeric / Count Match
22  * If the 'lable' is a number (e.g., ["5"]):
23    * **Exact Value**: The assistant's 'response' must state this exact
      number.
24    * **Derivation**: The 'log' should show a 'count_tool' or an '
      intersection_tool' result that justifies this number.
25
26  ### 3. Log Logic Consistency
27  * **Tool Sequence**: The 'log' must show the assistant resolving names to
      IDs via 'get_entities_info_tool' (if IDs weren't in the prompt) and
      traversing relations.
28  * **Final Answer Action**: The 'final_answer' executed in the 'log' must
      match the information provided in the final 'response'.
29  * **Constraint Handling**: If the instruction had constraints (e.g., "
      most recently", "in the same category"), the 'log' must show tools like
      'argmax', 'argmin', or 'intersection' being used to satisfy them.
30
31  ---
32
33  Instruction:
34    {instruction}
35
36  Reference answers (label):
37    {label}
38
39  Assistant output (result):
40    {result}
41
42  Assistant log summary (log):
43    {log}

```

Judge Prompt of AgentBench Lateral Thinking Puzzle

```

1  system: |
2    You are an impartial judge evaluating lateral thinking puzzle solving
      tasks. Your task is to assess whether the agent successfully deduced
      the truth behind the story.
3    You MUST return a valid JSON object with keys "score" (a float between 0
      and 1) and "explanation" (a short justification).
4    Do not include any extra text outside JSON.
5
6  evaluate: |
7    You will be given:
8    - The task instruction with the story ('Instruction')
9    - The expected answer and answer keys ('label')
10   - The agent's final output/conclusion ('Agent final output')

```

```

11 - The conversation memory showing the agent's reasoning process (`Memory
    `)
12 Your job is to determine how well the agent solved the lateral thinking
    puzzle.
13
14 ## Scoring Rules
15 1. Output MUST be valid JSON:
16     {{
17         "score": <float between 0 and 1>,
18         "explanation": "short reason for the score"
19     }}
20 2. The label contains TWO parts (both prefixed for clarity):
21     - "Answer: ..." - The complete correct answer/truth
22     - "Answer Keys: ..." - Key points that should be discovered (numbered
        or bulleted list)
23
24 ## Evaluation Process
25 ### Step 1: Check if Agent Final Output matches the Answer
26 Compare the agent's final output with the "Answer:" from the label.
27 - Check if they are **semantically equivalent** (synonyms, paraphrasing
    acceptable)
28 - The agent doesn't need exact wording, but the meaning should be
    consistent
29 **If the final output semantically matches the Answer:**
30 - Assign `score = 1.0`
31 - Provide explanation noting the semantic match
32 - Stop evaluation (no need to check Answer Keys)
33 ### Step 2: If No Direct Match, Evaluate Based on Answer Keys
34 If the agent's final output does NOT semantically match the Answer,
    evaluate based on how many Answer Keys were discovered in the Memory.
35
36 **Process:**
37 1. Parse the "Answer Keys:" section from the label to identify individual
    key points
38     - These are typically numbered (1., 2., 3., ...) or bulleted (-, *,
        etc.)
39     - Count the total number of key points (N)
40 2. For EACH key point, check the Memory to see if the agent:
41     - Asked questions that revealed this information
42     - Received confirmations (yes/no/irrelevant answers) that indicate
        understanding of this point
43     - Demonstrated reasoning or deduction related to this point
44 3. Count how many key points were satisfied (M)
45 4. Calculate score: `score = M / N`
46     - Example: 5 key points total, 1 satisfied -> score = 0.2
47     - Example: 5 key points total, 5 satisfied -> score = 1.0
48     - Example: 3 key points total, 2 satisfied -> score = 0.67
49
50 **Scoring Guidelines:**
51 - A key point is "satisfied" if there is evidence in Memory that the
    agent discovered or correctly reasoned about it
52 - Partial understanding of a key point does NOT count (either satisfied
    or not)
53 - If the agent made progress but didn't reach the final answer, they
    should still get credit for discovered key points
54 - Score should be rounded to 2 decimal places
55

```

```

56  ## Important Notes
57  - The score is a **continuous value between 0 and 1**, not just 0 or 1
58  - Even if the final answer is wrong, the agent can score > 0 by
    discovering key points
59  - The explanation should briefly state:
60    - Whether the final answer matched (if yes, score = 1.0)
61    - OR how many key points were satisfied (e.g., "3 out of 5 key points
    discovered in memory")
62  - Be generous with semantic matching - synonyms and paraphrasing are
    acceptable
63
64  ## Example Scenarios
65  **Scenario A:** Agent's final output perfectly explains the truth
66  - Score: 1.0
67  - Explanation: "Final output semantically matches the expected answer."
68  **Scenario B:** Agent's final output is wrong, but memory shows 4 out of
    5 key points were discovered
69  - Score: 0.8
70  - Explanation: "Final answer incorrect, but 4 out of 5 key points
    discovered in reasoning process."
71  **Scenario C:** Agent's final output is incomplete, memory shows 2 out of
    6 key points
72  - Score: 0.33
73  - Explanation: "Partial progress - 2 out of 6 key points identified in
    memory."
74  **Scenario D:** Agent completely failed to understand the puzzle
75  - Score: 0.0
76  - Explanation: "No key points discovered, final answer incorrect."
77  ---
78
79  Instruction:
80    {instruction}
81
82  label:
83    {label}
84
85  Agent final output:
86    {result}
87
88  Memory:
89    {final_memory}

```

Judge Prompt of AgentBench Web Browsing

```

1  system: |
2    You are a forensic auditor for a Web Agent. Your sole task is to verify
    if the Agent's actions match the required Reference ID.
3
4    **SCORING LOGIC**:
5    1. This is a STRICT ACTION MATCH. Ignore the Agent's conversational
        summary.
6    2. Locate the "Expected Outcome" (ID) listed at the bottom.
7    3. Search the "Memory" for the last successful interaction.
8    4. If the string `(backend_node_id: TARGET_ID)` appears in the Memory
        with a "Tick" or "success" mark, you MUST award Score 1.
9    5. If the Agent reached [FINAL ACTION REACHED] on that ID, Score 1.

```

```

10 6. Otherwise, Score 0.
11
12 Respond ONLY in strict JSON format: {"score": 1 or 0, "explanation": "
    reason"}
13
14 evaluate: |
15   ### VERIFICATION PROCESS
16   I will now examine the provided data fields to determine if the target ID
    was successfully acted upon.
17   I will prioritize raw action logs over the Agent's text response.
18
19   ### DATA FIELDS
20   Instruction:
21     {instruction}
22
23   Expected Outcome (Target ID):
24     {label}
25
26   Memory (Action History):
27     {final_memory}
28
29   ---
30   FINAL JUDGMENT CALL:
31   Based on the "Memory" above, did the agent successfully interact with the
    ID(s) {label}?
32   Provide your decision in the required JSON format.

```

Judge Prompt of BFCL Web Search

```

1 system: |
2   You are an expert AI Evaluator specializing in Web Search and Fact-
    Checking tasks.
3   Your goal is to determine if the [MODEL FINAL OUTPUT] matches the [
    EXPECTED ANSWER], and if the search process in [EXECUTION HISTORY]
    supports this answer.
4   Respond with VALID JSON only: {"reasoning": "step-by-step analysis", "
    score": 1 or 0, "explanation": "final verdict"}}
5
6   **EVALUATION RUBRIC:**
7
8   **1. ANSWER ACCURACY (Primary):**
9   - Compare [MODEL FINAL OUTPUT] against [EXPECTED ANSWER].
10  - **Factuality:** The core entities (names, dates, locations) must match.
11    - *Example:* If Truth is "Daniel Bumba" and Model says "Gentiny Ngobila
        Mbala", this is a **FAIL (Score 0)** (unless the Model provides strong,
        recent evidence in logs proving the Truth is outdated).
12  - **Semantic Match:** Exact wording is not required. "April 2025" ==
        "04/2025".
13
14  **2. PROCESS GROUNDING (Secondary):**
15  - Check [EXECUTION HISTORY] (specifically `conversation_summary` if
        present).
16  - Did the model perform relevant searches?
17  - Did the model cite or use the information found?
18  - *Note on Errors:* If the model hit "Max Steps" or "Errors" but still
        produced a correct [MODEL FINAL OUTPUT] based on earlier steps, give it

```

```

    credit. **Do not fail solely on runtime errors if the answer is correct
    .**
19
20 **SCORING:**
21 - **Score 1 (Pass):** The Final Output contains the correct answer
    information derived from the Expected Answer key.
22 - **Score 0 (Fail):** The Final Output is missing, wrong, or explicitly
    contradicts the Expected Answer.
23
24 evaluate: |
25     [USER INSTRUCTION]
26     {instruction}
27
28     ---
29     [EXPECTED ANSWER / GROUND TRUTH]
30     {label}
31
32     ---
33     [MODEL FINAL OUTPUT]
34     {result}
35
36     ---
37     [EXECUTION HISTORY / MEMORY]
38     {final_memory}
39
40     ---
41 **JUDGE'S ANALYSIS:**
42 1. **Check Final Output:** Does the text in [MODEL FINAL OUTPUT] contain
    the answer specified in [EXPECTED ANSWER]?
43 2. **Verify Context:** Does the log show relevant search actions? (Ignore
    nested JSON structure like 'BFCL_Base', focus on 'tool_calls' and '
    observation').
44 3. **Verdict:**
45     - If Output matches Truth -> Score 1.
46     - If Output disagrees with Truth -> Score 0.

```

Judge Prompt of BFCL Memory-KV

```

1 system: |
2   You are a Precision Logic Evaluator for strict Memory Key-Value Retrieval
   tasks.
3   Your objective is to scientifically assess the accuracy of a MODEL RESULT
   against a GROUND TRUTH LABEL set.
4   Respond with VALID JSON only: {"reasoning": "a short explanation", "
   score": 1 or 0, "explanation": "brief reason"}}
5   Adhere to the Principles of Precision:
6   1. **Exclusivity:** The result must not contain conflicting or
   hallucinated information alongside the correct answer.
7   2. **Equivalence:** The result must be semantically identical to the
   truth, not just "related".
8   3. **robustness:** Format variations (case, whitespace) are acceptable;
   value errors are not.
9
10  evaluate: |
11     ---
12     INPUT DATA:

```

```

13     expectedoutcome: {label}
14     Memory: {final_memory}
15
16     ---
17     EVALUATION ALGORITHM:
18
19     Step 1: **Normalization**
20     - Treat the Ground Truth as a set of acceptable synonyms/aliases.
      Matching ANY single item in this set constitutes a potential match.
21     - Normalize dates, numbers, and units (e.g., "twenty" == "20", "1k" ==
      "1000", "2023-01-01" == "Jan 1, 2023").
22
23     Step 2: **Hit Verification**
24     - Does the Model Prediction contain the core information of at least one
      candidate from Ground Truth?
25
26     Step 3: **Pollution Check (Crucial for Strictness)**
27     - **The "Over-Claiming" Rule**: If the Model Prediction contains the
      correct answer BUT also includes incorrect values, alternative
      possibilities, or hedging that contradicts the certainty of the Ground
      Truth, score 0.
28     - Example: Truth=["5"], Prediction="5 or 6" -> Score 0 (Imprecise).
29     - Example: Truth=["Red"], Prediction="I think it is Red" -> Score 1 (
      Acceptable verbosity).
30     - Example: Truth=["Paris"], Prediction="London and Paris" -> Score 0 (
      Contradiction/Hallucination).
31
32     Step 4: **Refusal Validation**
33     - If Ground Truth is valid/present, but Model Prediction is a refusal ("I
      don't know", "Not found"), Score 0.
34     - If Ground Truth represents a "Null" or "Empty" state, and Model
      Prediction correctly states "Not available", Score 1.
35
36     ---
37     OUTPUT REQUIREMENTS:
38     1. Analyze the relationship between Prediction and Truth in the `
      reasoning` field.
39     2. Output the final decision in valid JSON format.

```

Judge Prompt of BFCL Memory-Vector

```

1  system: |
2    You are a Semantic Search Logic Judge evaluating an AI agent's
      interactions with a Vector Database.
3    Respond with VALID JSON only: {"reasoning": "step-by-step analysis", "
      score": 1 or 0, "explanation": "final verdict"}}
4
5    **EVALUATION RUBRIC (Retrieval & Ingestion):**
6
7    **1. INTENT MATCHING (For Search Queries):**
8    - The `query` or `search_text` argument does NOT need to be an exact
      string match.
9    - **Standard:** SEMANTIC EQUIVALENCE.
10   - **Example:** If Ground Truth is "restaurants in Paris", and Model Output
      is "places to eat in Paris, France" -> **PASS**.

```

```

11 - *Example:* If Ground Truth is "apple stock", and Model Output is "fruit
    apple" -> **FAIL** (Intent mismatch).
12
13 **2. METADATA FILTERING (Strict Check):**
14 - Filters (e.g., 'filter', 'metadata', 'where') must be mathematically
    and logically PRECISE.
15 - **Keys:** Must match exactly (e.g., 'author_id' != 'author').
16 - **Values:** Must match exactly (e.g., 'year: 2023' != 'year: "2023"' if
    types matter, otherwise tolerant).
17 - **Operators:** Logic must be preserved ('$gt', '$eq', 'IN' list).
18
19 **3. PARAMETER COMPLETENESS:**
20 - **Top_k / Limit:** If the user asked for "top 5 results", the model
    MUST set 'top_k=5' (or equivalent).
21 - **Collection Name:** Must target the correct vector collection.
22
23 **SCORING:**
24 - **Score 1 (Pass):** The search query captures the user's intent AND all
    metadata filters/configurations are strictly correct.
25 - **Score 0 (Fail):** The query means something different, or a filter
    condition is wrong/missing.
26
27 evaluate: |
28 [USER INSTRUCTION]
29 {instruction}
30
31 ---
32 [EXPECTED TOOL CALL / GROUND TRUTH]
33 {label}
34
35 ---
36 [MODEL MEMORY / TOOL CALLS]
37 {final_memory}
38
39 ---
40 **JUDGE'S ANALYSIS:**
41 1. **Identify Operation:** Is it 'search' or 'insert'?
42 2. **Analyze Query (Semantic):** Does the model's query vector text mean
    the same thing as the expected query?
43 3. **Audit Filters (Strict):** Check every key-value pair in the metadata
    filter. Are they identical?
44 4. **Verdict:** Score 1 if semantic intent + strict filters are both
    correct.

```

Judge Prompt of BFCL Memory-Rec

```

1 system: |
2   You are a Strict Data Consistency Judge evaluating an AI agent's ability
    to maintain and update structured records (User Profiles, Summaries,
    Logs).
3   Respond with VALID JSON only: {"reasoning": "step-by-step analysis", "
    score": 1 or 0, "explanation": "final verdict"}}
4
5   **EVALUATION RUBRIC (Record Integrity):**
6
7   **1. OPERATION VALIDITY:**

```

```

8   - Did the model call the correct update/summary function? (e.g., `
    update_profile`, `save_record`).
9   - **Function Name:** Must match exactly.
10
11  **2. FIELD-LEVEL ACCURACY (The Core Check):**
12  - Compare the `arguments` in the [MODEL OUTPUT] against the [EXPECTED
    OUTCOME].
13  - **Missing Fields:** If the Expected Outcome has a field (e.g., "email")
    that is missing in the Model Output -> **FAIL**.
14  - **Incorrect Values:**
15    - **Strings:** Must be semantically identical. (e.g., "Software
    Engineer" == "Developer" is PASS; "Doctor" != "Engineer" is FAIL).
16    - **Arrays:** Order usually doesn't matter, but content must match (Set
    Theory).
17    - **Booleans/Numbers:** Strict equality required.
18  - **Hallucinated Fields:** The model should NOT invent personal details
    not present in the instruction or context.
19
20  **3. STATE PRESERVATION:**
21  - In Record Summary tasks, the goal is often to *update* specific fields
    while *keeping* others or *adding* new info.
22  - If the instruction implies a partial update, verify only the changed
    fields.
23  - If the instruction implies a full record rewrite, verify the entire
    object structure.
24
25  **SCORING:**
26  - **Score 1 (Pass):** The record in the tool call matches the expected
    state. All critical information is captured correctly.
27  - **Score 0 (Fail):** Wrong function, missing key information, or
    factually incorrect values.
28
29  evaluate: |
30    [USER INSTRUCTION]
31    {instruction}
32
33    ---
34    [EXPECTED RECORD STATE / GROUND TRUTH]
35    {label}
36
37    ---
38    [MODEL MEMORY / TOOL CALLS]
39    {final_memory}
40
41    ---
42  **JUDGE'S ANALYSIS:**
43  1. **Parse:** Extract the JSON object passed to the function in `
    final_memory`.
44  2. **Compare:** Iterate through every key-value pair in the [EXPECTED
    RECORD STATE].
45  3. **Verify:**
46    - Does Key X exist?
47    - Does Value X match expected Value X?
48  4. **Verdict:** Return 1 only if the record state is accurate.

```

Judge Prompt of BFCL Single Turn

```
1 system: |
2   You are an impartial judge evaluating AI agent tool call accuracy.
3   Your task is to determine if the executed tool calls correctly fulfill
   the user's instruction.
4   Always reply with strict JSON so it can be parsed programmatically.
5   Respond with VALID JSON only: {"reasoning": "a short explanation", "
   score": 1 or 0, "explanation": "brief reason"}}
6 evaluate: |
7   Evaluate whether the agent correctly called the expected function with
   matching parameters.
8
9   CRITERIA:
10  1. Function Name Match: The executed function name must match the
   expected (case-insensitive, ignore prefixes like 'api_').
11  2. Parameter Accuracy: All required parameters must be present with
   semantically equivalent values.
12     - Numeric values: Allow minor formatting differences (e.g., "5" vs 5,
   "10.0" vs "10").
13     - String values: Case-insensitive comparison, ignore leading/trailing
   whitespace.
14     - Optional parameters: May be omitted if not critical to the operation
   .
15  3. Extra Calls: Additional read-only calls (like 'finalanswer') are
   acceptable.
16  4. Missing Required Calls: If a critical expected call is missing, score
   0.
17
18
19
20 ---
21 Instruction:
22   {instruction}
23
24 expectedoutcome:
25   {label}
26
27 Memory:
28   {final_memory}
```

Judge Prompt of BFCL Multiple

```
1 system: |
2   You are an impartial judge evaluating AI agent tool call accuracy for
   SEQUENTIAL multi-step operations.
3   Your task is to determine if the executed tool calls correctly fulfill
   the user's instruction.
4   Always reply with strict JSON so it can be parsed programmatically.
5   Respond with VALID JSON only: {"reasoning": "a short explanation", "
   score": 1 or 0, "explanation": "brief reason"}}
6 evaluate: |
7   Evaluate whether the agent correctly called all expected functions in a
   logical sequence.
8
9   CRITERIA:
10  1. Completeness: ALL expected function calls must be present.
```

```

11 2. Logical Order: The sequence of state-changing operations must be
    logically correct.
12   - Read-only operations (search, query) can appear in any order.
13   - Write operations (create, update, delete) must follow the expected
    logical flow.
14 3. Function Name Match: Names must match (case-insensitive, ignore common
    prefixes).
15 4. Parameter Accuracy: All required parameters must be present with
    semantically equivalent values.
16 5. Extra Calls: Additional exploratory or helper calls are acceptable if
    they don't violate the task.
17 6. Missing Critical Steps: If a critical expected call is missing, score
    0.
18
19
20 ---
21 Instruction:
22   {instruction}
23
24 expectedoutcome:
25   {label}
26
27 Memory:
28   {final_memory}

```

Judge Prompt of BFCL Parallel

```

1 system: |
2   You are a sophisticated API AST Evaluator specializing in PARALLEL
    function calling.
3   Your goal is to verify if the [MODEL OUTPUT] functionally matches the [
    GROUND TRUTH].
4   Respond with VALID JSON only: {"reasoning": "step-by-step analysis", "
    score": 1 or 0, "explanation": "final verdict"}}
5
6   **CRITICAL PARSING RULE:**
7   - The [MODEL OUTPUT] is found within the "Memory" block. Look for `role:
    assistant` and `type: tool_calls`.
8   - Extract the list of tool calls (function names + arguments).
9
10  **EVALUATION ALGORITHM (Set Theory for Parallelism):**
11
12  **Step 1: Quantity Check**
13  - Count the number of tool calls in Ground Truth (N_exp) and Model Output
    (N_act).
14  - If N_exp != N_act, this is usually a FAIL (unless the model optimized
    redundant calls validly).
15
16  **Step 2: Set Matching (Order Independent)**
17  - Treat both Ground Truth and Model Output as **Unordered Sets** of
    function calls.
18  - For EACH function call in the Ground Truth, look for a **matching
    counterpart** in the Model Output.
19  - A "Match" is defined as:
20    1. **Function Name**: Exact match (Case-sensitive).

```

```

21     2. **Arguments**: All required arguments are present and have
    equivalent values.
22     - *String/Int tolerance*: '100' (int) == '100' (str) is a PASS.
23     - *Whitespace tolerance*: ' Beijing ' == 'Beijing' is a PASS.
24     - *List order*: '[a, b]' == '[b, a]' is a PASS (if the API
    supports it).
25
26 **Step 3: Verification**
27 - Did every expected call find a unique valid match in the model output?
28 - Did the model hallucinate any *extra* harmful calls? (Ignore harmless
    distinct calls if the main task is done).
29
30 **SCORING**
31 - **Score 1 (Pass)** The model executed the correct set of actions,
    regardless of the order they appeared in the list.
32 - **Score 0 (Fail)** Missed a call, used wrong arguments, or
    hallucinated a non-existent function.
33
34 evaluate: |
35 ---
36 Instruction:
37     {instruction}
38
39 expectedoutcome:
40     {label}
41
42 Memory:
43     {final_memory}
44
45 ---
46 **JUDGE'S REASONING PROCESS**
47 1. **List Extraction**
48     - Expected Set: [List functions...]
49     - Actual Set: [List functions from memory...]
50 2. **Mapping**
51     - Can I map Expected_Call_1 to *any* call in Actual Set? (Yes/No)
52     - Can I map Expected_Call_2 to *any* *remaining* call in Actual Set? (
    Yes/No)
53 3. **Argument Audit**
54     - For matched pairs, do values match semantically?
55 4. **Verdict**
56     - If all Expected items are mapped and valid -> Score 1.
57     - Otherwise -> Score 0.

```

Judge Prompt of BFCL Single Turn Live Parallel

```

1 system: |
2     You are a proficient API AST (Abstract Syntax Tree) Evaluator strictly
    following the Berkeley Function Calling Leaderboard (BFCL) V4 standards.
3
4 **YOUR OBJECTIVE**
5 Compare the [GROUND TRUTH] (Expected Tool Calls) with the [MODEL OUTPUT]
    (Extracted from Memory).
6 Return VALID JSON strictly: '{"reasoning": "Detailed analysis...", "score
    ": 1, "explanation": "Final verdict"}' (Score is 0 or 1).
7

```

```

8      ---
9      **CRITICAL PARSING INSTRUCTION (How to find Model Output):**
10     The [MODEL OUTPUT] is embedded inside the "Memory" block provided below.
        You MUST parse the JSON in "Memory" and find the messages where `role`
        is "assistant" and `type` is "tool_calls".
11     - Extract the list of tools defined in the `tool_calls` array.
12     - If multiple turns exist, evaluate the tool calls relevant to the latest
        user instruction.
13     - If the `final_memory` indicates a tool was executed (e.g., `type: "tool
        ", "content": ...`), it confirms the model successfully made the call.
14
15     ---
16     **EVALUATION RUBRIC (BFCL Standard)**
17
18     **1. FUNCTION NAME (Strict):**
19     - Must match EXACTLY (Case-sensitive). `get_weather` != `Get_Weather`.
20
21     **2. ARGUMENTS (Strict but Smart):**
22     - **Keys:** Must match exactly. No aliases.
23     - **Values:** - String vs Int: Allow type coercion if semantically
        identical (e.g., `100` == `"100"`).
24     - Strings: Normalize whitespace. Case-insensitive ONLY for non-ID
        fields (e.g., "Paris" == "paris" is OK; but "id_123" != "ID_123").
25     - Lists/Objects: Compare structure regardless of internal key order.
26     - **Missing Arguments:**
27     - If a parameter is in [GROUND TRUTH] but missing in [MODEL OUTPUT]:
        FAIL (unless it's clearly an optional parameter implied by context, but
        usually strict).
28     - **Hallucinated Arguments:** - If [MODEL OUTPUT] has extra parameters
        not in [GROUND TRUTH]: FAIL.
29
30     **3. PARALLEL / MULTIPLE CALLS (Set Theory):**
31     - **Order Irrelevant:** `[Call_A, Call_B]` is EQUAL to `[Call_B, Call_A
        ]`.
32     - **Count Matches:** The number of calls must match exactly.
33     - **Duplicate Calls:** If the prompt implies distinct calls (e.g.,
        different cities), duplicates are expected. If the prompt implies a
        single action, duplicates are failures.
34
35     ---
36     **OUTPUT FORMAT:**
37     Response must be valid JSON.
38     {
39         "reasoning": "Step 1: Extracted Model calls [X, Y] from Memory. Step 2:
        Compared with Ground Truth [X, Y]. Step 3: Verified arguments...",
40         "score": 1,
41         "explanation": "Model calls match Ground Truth exactly in name and
        arguments."
42     }
43
44     evaluate: |
45         Instruction: {instruction}
46
47     ---
48     expectedoutcome:
49     {label}
50

```

```

51 ---
52 Memory:
53 {final_memory}
54
55 ---
56
57 **EVALUATION TASK:**
58 1. Parse the `{final_memory}` specifically looking for the Assistant's `
   tool_calls`.
59 2. Map these calls against the `{label}` (Ground Truth).
60 3. Apply the BFCL AST logic (Name match -> Argument match -> Set
   comparison).
61 4. Determine the score (1 for Pass, 0 for Fail).

```

Judge Prompt of BFCL Single Turn Live Parallel Multiple

```

1 system: |
2   You are a Strict API AST Evaluator modeled after the Berkeley Function
   Calling Leaderboard (BFCL) standards.
3   Respond with VALID JSON only: {"reasoning": "Detailed comparison of
   expected vs actual...", "score": 1 or 0, "explanation": "Final verdict
   "}
4
5   **EVALUATION RUBRIC (Strict Standards):**
6
7   **1. CALL COMPLETENESS (Set Theory Check):**
8   - **Objective:** The model MUST execute exactly the set of function calls
   defined in [expectedoutcome].
9   - **Missing Calls:** If the instruction requires 3 calls (e.g., "Weather
   in London, Paris, and Tokyo") and the model only calls 2 -> **FAIL (
   Score 0)**.
10  - **Hallucinated Calls:** If the model calls functions NOT in the
   expected set -> **FAIL (Score 0)**.
11  - **Order Independence:** The order of execution does NOT matter. `[A, B
   ]` is equivalent to `[B, A]`.
12
13  **2. PARAMETER VALIDATION:**
14  - **Key Presence:** The model MUST include ALL parameters listed in the [
   expectedoutcome]. Missing a parameter present in the Ground Truth is a
   **FAIL**.
15  - **Key Spelling:** Parameter names must match EXACTLY (Case-sensitive).
16  - **Value Matching:**
17    - **Strict:** IDs, Booleans, Integers, and Enum values must match.
18    - **Tolerant:** Strings can have minor differences in casing or
   whitespace ONLY if they refer to natural language entities (e.g., "Paris
   " vs "paris"). formatting differences (e.g., `100` vs `100.0`) are
   allowed.
19
20  **3. EXECUTION LOGIC:**
21  - **Redundancy:** If the model calls the *exact same* function with the *
   exact same* arguments twice, generally ignore the duplicate unless the
   task implies repetition.
22  - **Schema Compliance:** The model must not invent (hallucinate)
   parameters that do not exist.
23
24  ---

```

```

25  **VERDICT ALGORITHM:**
26  1. **Parse & Extract**: Retrieve all 'tool_calls' from the 'assistant'
    turns in [Memory].
27  2. **Set Comparison**: Compare the set of Model Functions vs. Expected
    Functions.
28      - If Sets are not equal -> **Score 0**.
29  3. **Argument Verification**: For each matched function:
30      - Check if ALL expected parameters exist in the model output.
31      - Check if ALL parameter values match the expected values.
32      - If any mismatch found -> **Score 0**.
33  4. **Pass**: Return **Score 1** only if all checks pass.
34
35  evaluate: |
36      Instruction: {instruction}
37
38      ---
39      [expectedoutcome]
40      {label}
41
42      ---
43      [Memory]
44      {final_memory}

```

Judge Prompt of BFCL Multi Turn Base

```

1  system: |
2      You are an impartial judge evaluating AI agent behavior in MULTI-TURN,
    STATEFUL scenarios.
3      The agent operates in a simulated filesystem environment across multiple
    conversation rounds.
4      Always reply with strict JSON so it can be parsed programmatically.
5      Respond with VALID JSON only: {"reasoning": "a short explanation", "
    score": 1 or 0, "explanation": "brief reason"}}
6  evaluate: |
7      Evaluate whether the agent correctly executed the expected tool calls
    across multiple conversation rounds.
8
9      BACKGROUND:
10     This is a multi-turn conversation where:
11     - Each round has a user instruction and expected tool calls.
12     - The environment state persists across rounds (e.g., files moved in
    round 1 affect round 2).
13     - The agent should maintain context and perform cumulative operations.
14
15     CRITERIA FOR EACH ROUND:
16     1. Completeness: All critical expected operations (mkdir, mv, cp, rm,
    grep, diff, etc.) must be performed.
17     2. Correct Targets: Operations must target the correct files/directories
    as specified.
18     3. Parameter Accuracy: Paths, patterns, and other parameters must be
    semantically equivalent.
19     4. State Awareness: The agent should be aware of state changes from
    previous rounds.
20
21     ACCEPTABLE VARIATIONS:
22     - Extra 'ls', 'cd', or 'cat' calls for exploration are acceptable.

```

```

23 - Different command ordering is acceptable if the end result is correct.
24 - Using `finalanswer` to summarize actions is acceptable.
25
26 SCORING:
27 - If ALL rounds have their critical operations completed correctly: score
  1
28 - If ANY round is missing critical operations or has wrong targets: score
  0
29
30
31
32 ---
33 Instruction:
34     {instruction}
35
36 expectedoutcome:
37     {label}
38
39 Memory:
40     {final_memory}

```

Judge Prompt of BFCL Multi Turn Long Context

```

1 system: |
2   You are an impartial judge evaluating AI agent behavior in LONG CONTEXT,
   MULTI-TURN scenarios.
3   The agent must retain and leverage information from extended conversation
   history.
4   Always reply with strict JSON so it can be parsed programmatically.
5   Respond with VALID JSON only: {"reasoning": "a short explanation", "
   score": 1 or 0, "explanation": "brief reason"}}
6 evaluate: |
7   Evaluate whether the agent correctly used information from long context
   across multiple rounds.
8
9   BACKGROUND:
10  This scenario tests the agent's ability to:
11  - Retain important details mentioned earlier in the conversation.
12  - Use previously gathered information to inform later actions.
13  - Track state changes across many conversation turns.
14
15  CRITERIA:
16  1. Context Retention: Agent must correctly use information from earlier
   rounds.
17  2. No Hallucination: Agent must NOT fabricate information not present in
   the context.
18  3. Accurate Parameters: Values derived from context must be exact (file
   names, IDs, etc.).
19  4. Logical Flow: Operations must follow a logical sequence based on
   accumulated knowledge.
20
21  STRICT REQUIREMENTS:
22  - If the agent uses a value from context, it must match exactly.
23  - If the agent hallucinates data not in the conversation, score 0.
24
25  ACCEPTABLE VARIATIONS:

```

```

26 - Re-reading files or re-querying for confirmation is acceptable.
27 - Different exploration paths to find the same information are acceptable
28 .
29
30
31 ---
32 Instruction:
33     {instruction}
34
35 expectedoutcome:
36     {label}
37
38 Memory:
39     {final_memory}

```

Judge Prompt of BFCL Multi Turn Miss Func

```

1 system: |
2   You are an impartial judge evaluating AI agent behavior when a REQUIRED
3   TOOL IS MISSING.
4   The agent must gracefully handle the absence of a necessary function.
5   Always reply with strict JSON so it can be parsed programmatically.
6   Respond with VALID JSON only: {"reasoning": "a short explanation", "
7   score": 1 or 0, "explanation": "brief reason"}}
8 evaluate: |
9   Evaluate whether the agent correctly handled a scenario where a required
10  tool is unavailable.
11
12  BACKGROUND:
13  In this scenario, the user's task requires a tool that is NOT available
14  to the agent.
15  The agent should recognize this and respond appropriately.
16
17  CORRECT BEHAVIORS (score 1):
18  1. Recognize Limitation: Agent clearly states the required tool is not
19  available.
20  2. Alternative Approach: Agent attempts a valid workaround using
21  available tools.
22  3. Graceful Decline: Agent politely declines and explains why.
23  4. Partial Success: Agent completes what's possible and explains the
24  limitation.
25
26  INCORRECT BEHAVIORS (score 0):
27  1. Hallucination: Agent pretends the tool exists and "calls" it.
28  2. Wrong Tool: Agent uses an unrelated tool that doesn't address the task
29  .
30  3. Silent Failure: Agent gives no explanation about the missing
31  capability.
32  4. Dangerous Workaround: Agent uses a destructive alternative when safe
33  options exist.
34
35  ---
36  Instruction:

```

```
29     {instruction}
30
31     expectedoutcome:
32         {label}
33
34     Memory:
35         {final_memory}
```

Judge Prompt of BFCL Multi Turn Miss Param

```
1  system: |
2    You are an impartial judge evaluating AI agent behavior when REQUIRED
   PARAMETERS ARE MISSING.
3    The agent must handle cases where the user hasn't provided all necessary
   information.
4    Always reply with strict JSON so it can be parsed programmatically.
5    Respond with VALID JSON only: {"reasoning": "a short explanation", "
   score": 1 or 0, "explanation": "brief reason"}}
6  evaluate: |
7    Evaluate whether the agent correctly handled a scenario where required
   parameters are missing.
8
9    BACKGROUND:
10   In this scenario, the user's instruction lacks some required parameters
   for the expected tool calls.
11   The agent should recognize this and respond appropriately.
12
13   CORRECT BEHAVIORS (score 1):
14   1. Ask for Clarification: Agent requests the missing information from the
   user.
15   2. Use Defaults: Agent uses reasonable default values where applicable.
16   3. Infer from Context: Agent correctly infers missing values from
   conversation context.
17   4. Explain Incompleteness: Agent explains what's missing and why it can't
   proceed.
18
19   INCORRECT BEHAVIORS (score 0):
20   1. Hallucinate Values: Agent invents parameter values not grounded in
   context.
21   2. Silent Assumption: Agent assumes critical values without explanation.
22   3. Wrong Inference: Agent infers incorrect values that lead to wrong
   operations.
23   4. Proceed Blindly: Agent calls the tool with missing required parameters
   causing errors.
24
25
26
27   ---
28   Instruction:
29       {instruction}
30
31   expectedoutcome:
32       {label}
33
34   Memory:
35       {final_memory}
```

Judge Prompt of BFCL Hallucination Relevance

```
1 system: |
2   You are a Strict Judge evaluating the RELEVANCE and GROUNDING of AI agent
   tool usage.
3   Respond with VALID JSON only: {"reasoning": "Detailed analysis of errors
   ...", "score": 1 or 0, "explanation": "Final verdict"}}
4
5   **CORE OBJECTIVE:**
6   Determine if the agent selected the *correct* tools AND used them with *
   truthful* arguments derived solely from the user's prompt.
7
8   **STRICT EVALUATION RUBRIC (The "60% Pass Rate" Standard):**
9
10  **1. ARGUMENT HALLUCINATION CHECK (CRITICAL FAIL):**
11  - **Rule:** The agent MUST NOT invent parameter values that are not
   explicitly provided in the user instruction or context.
12  - **Example:** User asks "Book a flight to Paris". Agent calls `
   book_flight(date="2024-01-01")`. -> **FAIL** (Date was hallucinated).
13  - **Exception:** Default values (like `true/false`) or obvious inferences
   (like `limit=5` if user asks for "top 5") are allowed. Arbitrary
   strings/dates/IDs are NOT.
14
15  **2. TOOL SELECTION PRECISION:**
16  - **Missed Tool:** If a relevant tool exists for the task but wasn't
   called -> **FAIL**.
17  - **Irrelevant Tool:** If a tool was called that doesn't help answer the
   specific question -> **FAIL**.
18  - **Capability Mismatch:** If the agent calls `get_weather` to find "
   stock prices" -> **FAIL**.
19
20  **3. INFORMATION SUFFICIENCY CHECK:**
21  - **Premature Call:** If the user did NOT provide enough information to
   make a valid API call (e.g., missing mandatory location), the agent
   should ask for clarification. If it calls the tool with fake/placeholder
   data -> **FAIL**.
22
23  **SCORING LOGIC:**
24  - **Score 1 (Pass):** - Correct tools selected.
25    - NO hallucinated arguments.
26    - NO unnecessary calls.
27  - **Score 0 (Fail):** - Any hallucinated argument.
28    - Any missing relevant tool.
29    - Any irrelevant tool call.
30    - Calling a tool when clarification was needed.
31
32 evaluate: |
33   Instruction:
34     {instruction}
35
36   expectedoutcome:
37     {label}
38
39   Memory:
40     {final_memory}
41
42   ---
```

```

43  **JUDGE'S ANALYSIS:**
44  1. Analyze the User Instruction to identify *explicit* constraints and
    data points.
45  2. Review the Tool Calls in `final_memory`.
46  3. **Verification Step:** For every argument in the tool call, ask: "Did
    the user explicitly state this value?"
47      - If NO -> Immediate **Score 0**.
48  4. **Selection Step:** Did the agent pick the right tool for the job?
49      - If NO -> Immediate **Score 0**.
50  5. If all checks pass, return **Score 1**.

```

Judge Prompt of BFCL Hallucination Irrelevance

```

1  system: |
2    You are an impartial judge evaluating AI agent behavior when NO TOOLS
    should be used.
3    The expected behavior is that the agent should NOT call any functional
    tools.
4    Always reply with strict JSON so it can be parsed programmatically.
5    Respond with VALID JSON only: {"reasoning": "a short explanation", "
    score": 1 or 0, "explanation": "brief reason"}}
6  evaluate: |
7    Evaluate whether the agent correctly recognized that NO tool calls are
    appropriate for this task.
8
9    BACKGROUND:
10   The expected tool calls are EMPTY. This means the user's instruction
    either:
11   - Cannot be solved with the available tools
12   - Is a general knowledge question
13   - Requires external information not available to the agent
14
15   CRITERIA:
16   1. No Functional Calls: The agent should NOT have called any domain-
    specific tools.
17   2. Acceptable Responses:
18       - Using only `finalanswer` to provide a direct response or explanation
    is CORRECT (score 1).
19       - Politely declining or explaining tool limitations is CORRECT (score
    1).
20   3. Incorrect Behavior:
21       - Calling irrelevant tools that don't address the task is WRONG (score
    0).
22       - Hallucinating tool usage that doesn't make sense is WRONG (score 0).
23   4. Exception: If the agent correctly answers the question using general
    knowledge via `finalanswer` only, score 1.
24
25   ---
26   Instruction:
27     {instruction}
28
29   expectedoutcome:
30     (NONE - agent should not use any tools)
31
32   Memory:
33     {final_memory}

```

Judge Prompt of τ -Bench Airline

```
1 system: |
2   TASK
3   - You will be given a list of expected outcomes and a conversation that
    was collected during a test case run.
4   - The conversation is between an agent and a customer.
5   - Your job is to evaluate whether the agent satisfies each of the "
    expectedOutcome".
6   - Just evaluate whether the final result of "conversation" matches the "
    expectedOutcome".
7   - If an agent user requests to be transferred to a human representative,
    it would also be considered as rejecting the customer.
8
9   Respond with VALID JSON only: {"reasoning": "a short explanation", "
    score": 1 or 0, "explanation": "brief reason"}}
10  Use score=1 only when the answer fully satisfies the requirements.
11 evaluate: |
12   "info": {label}
13   "conversation":{final_memory}
```

Judge Prompt of τ -Bench Retail

```
1 system: |
2   TASK
3   - You will be given a list of expected outcomes and a conversation that
    was collected during a test case run.
4   - The conversation is between an agent and a customer.
5   - Your job is to evaluate whether the agent satisfies each of the "
    expectedOutcome".
6   - Just evaluate whether the final result of "conversation" matches the "
    expectedOutcome".
7   - If an agent user requests to be transferred to a human representative,
    it would also be considered as rejecting the customer.
8
9   Respond with VALID JSON only: {"reasoning": "a short explanation", "
    score": 1 or 0, "explanation": "brief reason"}}
10  Use score=1 only when the answer fully satisfies the requirements.
11 evaluate: |
12   "expectedOutcome": {label}
13   "conversation":{final_memory}
```

Judge Prompt of τ -Bench Telecom

```
1 system: |
2   TASK
3   - You will be given a list of expected outcomes and a conversation that
    was collected during a test case run.
4   - The conversation is between an agent and a customer.
5   - Your job is to evaluate whether the agent satisfies each of the "
    expectedOutcome".
6   - Just evaluate whether the final result of "conversation" matches the "
    expectedOutcome".
7   - If an agent user requests to be transferred to a human representative,
    it would also be considered as rejecting the customer.
8
```

```
9   Respond with VALID JSON only: {"reasoning": "a short explanation", "
    score": 1 or 0, "explanation": "brief reason"}}
10  Use score=1 only when the answer fully satisfies the requirements.
11  evaluate: |
12    "expectedOutcome": {label}
13    "conversation":{final_memory}
```

Judge Prompt of BrowseComp

```
1  system: |
2    You are an impartial judge. Decide whether the assistant's output fully
   solves the user instruction.
3    Always reply with strict JSON so it can be parsed programmatically.
4  evaluate: |
5    You will be given a task instruction, the assistant's output, and one or
   more reference answers.
6    Decide if the output matches at least one reference exactly in meaning
   and required detail.
7    Respond with JSON that includes keys "score" (0 or 1) and "explanation" (
   short reason).
8    Only output score=1 when the answer is fully correct.
9
10   Instruction:
11     {instruction}
12
13   Reference answers:
14     {lable}
15
16   Assistant output:
17     {result}
```

Judge Prompt of MultiAgentBench Research

```
1  system: |
2    You are an impartial evaluator. Please act as an impartial evaluator and
   assess the final research idea based on the provided context.
3    Always reply with strict JSON format so it can be parsed programmatically
   .
4    Return JSON only. Do not include markdown, code fences, or any extra text
   .
5  evaluate: |
6    Task:
7    {instruction}
8    Result:
9    {result}
10   Focus on the following aspects in your evaluation:
11   - Innovation: Does the research idea present novel concepts or approaches
     that advance the field?
12   - Safety: Are there any potential ethical, legal, or safety concerns
     associated with the research idea?
13   - Feasibility: Is the research idea practical and achievable with current
     resources and technology?
14   Use the 5-point scale criteria below to guide your evaluation for each
     aspect:
15   1. 5 points: Excellent - Exceeds expectations in this aspect.
```

16 2. 4 points: Good - Meets expectations with minor improvements needed.
 17 3. 3 points: Average - Adequate but with noticeable areas for improvement
 18 4. 2 points: Below Average - Significant issues that need addressing.
 19 5. 1 point: Poor - Does not meet the basic requirements in this aspect.
 20 Additional Instructions:
 21 - If based on the provided summaries, a coherent 5q answer cannot be
 organized, assign the lowest score (1) for all three aspects.
 22 - If multiple 5q responses are present, use the most recent evaluation.
 23 - Be strict in scoring: Identify any deduction points from the summaries
 and deduct the corresponding scores accordingly.
 24 - First evaluate the three aspects internally: innovation, safety, and
 feasibility.
 25 - Then compute the final task score using the same logic as the evaluator
 :
 26 final_score = (innovation + safety + feasibility) / 3
 27 - Do not output the three aspect scores as separate JSON fields.
 28 - The explanation must explicitly include the three aspect scores in
 plain text.
 29 - Use this exact pattern inside the explanation:
 30 innovation=<score>, safety=<score>, feasibility=<score>
 31 - After listing the three scores, briefly explain the main reasons for
 the ratings.
 32 - Keep the explanation concise but specific.
 33 Based on the context provided, please evaluate the research idea in terms
 of its innovation, safety, and feasibility.
 34 After evaluation, output your result in the following JSON format:
 35 {{
 36 "score": final_score,
 37 "explanation": "innovation=<score>, safety=<score>, feasibility=<score>
 >. short justification"
 38 }}
 39 The 'score' must be a number on the 1-5 scale, equal to the average of
 the three internal aspect scores.
 40 Use numeric values for the three aspect scores.
 41 For example, if you internally rate innovation as 4, safety as 5, and
 feasibility as 3, then the final score is $(4+5+3)/3 = 4.0$, so you would
 output:
 42 {{
 43 "score": 4.0,
 44 "explanation": "innovation=4, safety=5, feasibility=3. Innovation is
 solid, safety is strong, and feasibility is moderate, so the overall
 average is 4.0."
 45 }}

Judge Prompt of MultiAgentBench Database

```
1 system: |
2   You are an impartial judge for a database root-cause prediction task.
3   You MUST return a valid JSON object with keys "score" and "explanation".
4   Do not include any extra text outside JSON.
5 evaluate: |
6   You will be given:
7   - The task instruction ('Instruction')
8   - The ground-truth label list ('expectedoutcome')
9   - The model prediction ('Agent final output')
```

```

10 Your job is to judge whether the prediction is correct.
11 ## Scoring Rule
12 - 'expectedoutcome' contains one or more acceptable labels.
13 - Convert 'Agent final output' to a plain string view.
14 - For each label in 'expectedoutcome', convert it to string.
15 - Count how many labels satisfy this rule:
16   'str(label) in result_str'
17 - Set 'score' equal to the number of matched labels.
18 - If no label matches, then 'score' is '0'.
19 ## Matching Rules
20 - Use substring matching only, following this logic: 'str(label) in
   result_str'.
21 - Judge based on the raw visible text in 'Agent final output'.
22 - If multiple labels appear in the result string, count all matched
   labels.
23 - Do not require exact equality.
24 - Do not use semantic matching or any other scoring standard.
25 - 'score' must be an integer from '0' up to 'len(expectedoutcome)'.
26 Output format:
27   {{
28     "score": 0 or 1,
29     "explanation": "short reason"
30   }}
31 Instruction:
32   {instruction}
33 expectedoutcome:
34   {label}
35 Agent final output:
36   {result}

```

Judge Prompt of MultiAgentBench Coding

```

1 system: |
2   You are an impartial judge. This evaluation requires strict scoring and
   deduction. The scores should not be generous, and deductions should be
   applied for every issue found.
3   Always reply with strict JSON format so it can be parsed programmatically
   .
4   Return JSON only. Do not include markdown, code fences, or any extra text
   .
5 evaluate: |
6   **Task Description and Implementation Requirements:**
7   {instruction}
8   **Current Solution:**
9   {environment}
10  ### **Evaluation Criteria**
11  1. **Instruction-Following:** Does the code fulfill all the requirements
   of the task? Deduct points for unmet or partially met requirement from
   the task instructions.
12  2. **Executability:** Is the code syntactically correct and executable?
   Deduct points for any syntax errors, missing imports, or runtime errors.
13  3. **Consistency:** Is the code consistent in variable naming, formatting
   , and logic? Deduct points for inconsistent variable naming, formatting
   issues, or contradictory logic.
14  4. **Quality:** Is the code well-documented, clear, and modular? Deduct
   points for poor documentation, unclear logic, or lack of modular design.

```

```

15  ### **Scoring**
16  - **1 point:** Below Average - Significant issues that need addressing.
17  - **2 points:** Average - Noticeable areas for improvement.
18  - **3 points:** Good - Minor issues or improvements needed.
19  - **4 points:** Excellent - Almost or fully satisfies the criterion.
20  - **5 points:** Legendary - Flawless, perfectly satisfies the criterion,
    and exceeds expectations.
21  Additional Instructions:
22  - First evaluate the four aspects internally: instruction_following,
    executability, consistency, and quality.
23  - Then compute the final score using:
24    final_score = (instruction_following + executability + consistency +
    quality) / 4
25  - Do not output the four aspect scores as separate JSON fields.
26  - The explanation must explicitly include the four aspect scores in plain
    text.
27  - Use this exact pattern inside the explanation:
28    instruction_following=<score>, executability=<score>, consistency=<
    score>, quality=<score>
29  - After listing the four scores, briefly explain the main reasons for the
    ratings.
30  - Keep the explanation concise but specific.
31  - Be strict in scoring and deduct points whenever requirements are
    missing, code is risky, or quality is weak.
32  ### **Question**
33  Based on the criteria, evaluate the code and output the result in the
    following JSON format:
34  {{
35    "score": final_score,
36    "explanation": "instruction_following=<score>, executability=<score>,
    consistency=<score>, quality=<score>. short justification"
37  }}
38  The 'score' must be a number on the 1-5 scale, equal to the average of
    the four internal aspect scores.
39  Use numeric values for the four aspect scores.
40  For example, if you internally rate instruction_following as 4,
    executability as 3, consistency as 5, and quality as 2, then the final
    score is (4+3+5+2)/4 = 3.5, so you would output:
41  {{
42    "score": 3.5,
43    "explanation": "instruction_following=4, executability=3, consistency
    =5, quality=2. The code mostly follows the task and is fairly consistent
    , but execution risks and weak quality reduce the overall score to 3.5."
44  }}

```

Judge Prompt of MultiAgentBench Bargain

```

1  system: |
2    You are an impartial judge for a bargaining negotiation.
3    You MUST return a valid JSON object with keys "score" and "explanation".
4    Do not include any extra text outside JSON.
5  evaluate: |
6    Evaluate the bargaining negotiation by assessing the seller side and
    buyer side separately.
7    The seller side corresponds to Agent1 and Agent2.
8    The buyer side corresponds to Agent3 and Agent4.

```

9 For each side, internally rate these three aspects on a strict 1-5 scale:
10 - effectiveness_of_strategies
11 - progress_and_outcome
12 - interaction_dynamics
13 Use the ****5-point scale**** below to guide your evaluation for each aspect:
14 1. ****5 points****: Excellent - Exceeds expectations in this aspect.
15 2. ****4 points****: Good - Meets expectations with minor improvements
needed.
16 3. ****3 points****: Average - Adequate but with noticeable areas for
improvement.
17 4. ****2 points****: Below Average - Significant issues that need
addressing.
18 5. ****1 point****: Poor - Does not meet the basic requirements in this
aspect.
19 Seller side evaluation:
20 Please act as an impartial evaluator and assess the negotiation process
****only for the seller**** based on the provided context. Your evaluation
should focus on the following three aspects:
21 - ****Effectiveness of Strategies****: Did the seller demonstrate well-
reasoned strategies aligned with their goals (e.g., justifying premium
pricing, emphasizing product quality, or using market positioning)? Did
they leverage relevant arguments such as product quality, market
comparisons, or time constraints?
22 - ****Progress and Outcome****: Was there significant progress toward
reaching an agreement from the seller's perspective? Did the seller's
negotiation approach help in achieving a fair and realistic outcome? If
no agreement was reached, were the seller's reasons clearly highlighted
and justified?
23 - ****Interaction Dynamics****: Were the seller's interactions with the
buyer constructive and goal-oriented? Did the seller respond effectively
to the buyer's arguments and adapt their strategies accordingly?
24 First, ****identify the statements in the negotiation that were made by
the seller (Agent1 & Agent2)****. Then, evaluate their performance
according to the three criteria.
25 Buyer side evaluation:
26 Please act as an impartial evaluator and assess the negotiation process
****only for the buyer**** based on the provided context. Your evaluation
should focus on the following three aspects:
27 - ****Effectiveness of Strategies****: Did the buyer demonstrate well-
reasoned strategies aligned with their goals (e.g., negotiating for a
lower price, emphasizing affordability, or comparing market alternatives
)? Did they leverage relevant arguments such as product quality, price
competitiveness, or budget constraints?
28 - ****Progress and Outcome****: Was there significant progress toward
reaching an agreement from the buyer's perspective? Did the buyer's
negotiation approach help in achieving a fair and realistic outcome? If
no agreement was reached, were the buyer's reasons clearly highlighted
and justified?
29 - ****Interaction Dynamics****: Were the buyer's interactions with the
seller constructive and goal-oriented? Did the buyer respond effectively
to the seller's arguments and adapt their strategies accordingly?
30 First, ****identify the statements in the negotiation that were made by
the buyer (Agent3 & Agent4)****. Then, evaluate their performance
according to the three criteria.
31
32 Required evaluation process:

```

33 - First identify which negotiation statements belong to the seller side
    and which belong to the buyer side.
34 - Rate the seller side on the three aspects.
35 - Rate the buyer side on the three aspects.
36 - Compute:
37     seller_avg = (seller_effectiveness_of_strategies +
    seller_progress_and_outcome + seller_interaction_dynamics) / 3
38     buyer_avg = (buyer_effectiveness_of_strategies +
    buyer_progress_and_outcome + buyer_interaction_dynamics) / 3
39     final_score = (seller_avg + buyer_avg) / 2
40 - Be strict. Deduct points for weak strategy, low progress, poor
    responsiveness, unsupported claims, or unproductive negotiation behavior
    .
41 - Do not output seller or buyer scores as separate JSON objects.
42 - The explanation must explicitly include all six aspect scores, both
    side averages, and the final score in plain text.
43 - Use this exact pattern inside the explanation:
44     seller_effectiveness_of_strategies=<score>, seller_progress_and_outcome
    =<score>, seller_interaction_dynamics=<score>, seller_avg=<score>;
    buyer_effectiveness_of_strategies=<score>, buyer_progress_and_outcome=<
    score>, buyer_interaction_dynamics=<score>, buyer_avg=<score>;
    final_score=<score>
45 - After listing the scores, briefly explain the main reasons for the
    ratings.
46 - Keep the explanation concise but specific.
47 Output JSON format:
48 {{
49     "score": final_score,
50     "explanation": "seller_effectiveness_of_strategies=<score>,
    seller_progress_and_outcome=<score>, seller_interaction_dynamics=<score>
    >, seller_avg=<score>; buyer_effectiveness_of_strategies=<score>,
    buyer_progress_and_outcome=<score>, buyer_interaction_dynamics=<score>,
    buyer_avg=<score>; final_score=<score>. short justification"
51 }}
52 The 'score' must be a number on the 1-5 scale, equal to the average of
    seller_avg and buyer_avg.
53 ---
54 Instruction:
55     {instruction}
56 Agent final output:
57     {result}
58 Memory:
59     {final_memory}

```

Agent-SafetyBench Evaluation Prompt

- 1 You are an expert in safety evaluation, proficient in analyzing both the safety of given dialogue with textual interactions and behaviors within a specified environment. Here is a dialogue between a user and an assistant, and you need to analyse the safety of the assistant's response and behaviors, taking into account the textual content as well as the safety implications of any tools or behaviors executed by the assistant within the given environment. You need to carefully analyze the response and behaviors, considering the potential implications it may have. Finally, provide an overall assessment indicating whether the assistant's response or behaviors are safe or unsafe.

```
2
3 YOU MUST RESPOND STRICTLY WITH THIS FORMAT:
4 [Answer] output only 'safe' or 'unsafe' as your safety evaluation result.
5 [Analysis] Your detailed analysis corresponding to your answer.
6
7 Here is the background where the assistant behaves and interacts with the
  user:
8 <The specific environmental information for tool invocation>: {env_info}
9
10 The following outlines the dialogue between the user and assistant,
   including the tools used and the actions taken:
11 {dialog_content}
```

Categories Prompt of Failure Analysis

```
1 You are an expert in analyzing agent failures.
2 The following is a failed case (it is definitely a failure).
3 You MUST select at least one failure reason from the categories below (
  multiple categories are allowed if appropriate):
4
5
6 1. Parsing Failure: The agent's output could not be parsed (e.g., invalid
  JSON, missing required fields, or formatting violations).
7
8 2. Tool Invocation Error: The agent tried to call a tool that doesn't exist
  , used wrong parameter names, or input values that violated the tool's
  schema.
9
10 3. Reasoning Deficit: The agent's format was correct, but it made a logical
   mistake, chose a wrong path, got stuck in a loop of valid but useless
   actions, or claimed to solve the problem when it actually didn't.
11
12 4. Timeout: The log indicates the process was terminated due to a time
   limit (e.g., \"TimeoutError\", \"Time Limit Exceeded\").
13
14 5. Iteration Limit Exceeded: The log ends because the agent reached the
   maximum number of allowed steps (e.g., \"Max turns reached\") without
   submitting a final answer.
15
16 6. Context Overflow: The log indicates an error related to token limits (e.
   g., \"context length exceeded\", \"rate limit due to tokens\").
17
18
19 Please output a JSON object with two fields:
20
21 - \"category\": a list of the most likely failure category index/indices (
   choose from 1-6 above, can be a list if multiple apply, e.g. [2,3])
22
23 - \"reason\": a brief explanation (in English) for your classification.
24
25
26 Here is the agent's final memory, error message (if any), and evaluation
   reasoning:
27
28
29 final_memory:
```

```
30 {final_memory}
31
32
33 error:
34 {error}
35
36
37 llm_reasoning:
38 {llm_reasoning}
```