Correction to: Continually Learning Out-of-Distribution Spatiotemporal Data for Robust Energy Forecasting

Arian Prabowo, Kaixuan Chen, Hao Xue, Subbu Sethuvenkatraman, and Flora D. Salim

Correction to:
Chapter 1 in: G. De Francisci Morales et al. (Eds.): *Machine Learning and Knowledge Discovery in Databases: Applied Data Science and Demo Track*, LNAI 14175,
https://doi.org/10.1007/978-3-031-43430-3_1

The originally published version of the chapter 1 contains unintentional errors in the table 3 and a small punctuation error in the section 6.3. These errors have been corrected.

The updated version of this chapter can be found at
https://doi.org/10.1007/978-3-031-43430-3_1

© The Author(s), under exclusive license to Springer Nature Switzerland AG 2023
G. De Francisci Morales et al. (Eds.): ECML PKDD 2023, LNAI 14175, pp. C1–C2, 2023.
https://doi.org/10.1007/978-3-031-43430-3_34

Table 3. Comparing the performance of different algorithm with or without continual learning (CL). The metric used is MAE. Results are average over 10 runs with different random seed. The standard deviation is shown.

	dataset	**FSNet (no CL)**	**FSNet**	**TCN (no CL)**	**OGD**	**ER**	**DER++**
	BC1	0.3703	**0.1583**	0.3668	0.2056	0.1820	0.1696
		±0.0607	±0.0280	±0.0379	±0.0413	±0.0217	±0.0130
	BC2	0.6272	**0.1712**	0.5176	0.2465	0.2322	0.2272
Pre-Lockdown		±0.0914	±0.0063	±0.0607	±0.0105	±0.0056	±0.0062
	BC3	0.6750	**0.2462**	0.6500	0.3308	0.2862	0.2726
		±0.0638	±0.0151	±0.0698	±0.0812	±0.0432	±0.0334
	BC4	1.0018	**0.2802**	1.1236	0.3910	0.3511	0.3408
		±0.1053	±0.0312	±0.1040	±0.0520	±0.0323	±0.0210
	BC1	0.4537	**0.1429**	0.4179	0.1797	0.1589	0.1482
		±0.0517	±0.0275	±0.0443	±0.0342	±0.0168	±0.0094
	BC2	0.6506	**0.1628**	0.5209	0.2313	0.2188	0.2148
Post-Lockdown		±0.0994	±0.0057	±0.0535	±0.0085	±0.0060	±0.0068
	BC3	0.7168	**0.2255**	0.7083	0.3014	0.2636	0.2518
		±0.0632	±0.0145	±0.0793	±0.0709	±0.0373	±0.0286
	BC4	1.8415	**0.3314**	1.8307	0.4496	0.4162	0.4043
		±0.2765	±0.0520	±0.2319	±0.0643	±0.0475	±0.0338